



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ACTION S.A.

### SPECfp<sup>®</sup>\_rate2006 = 158

### ACTINA SOLAR 710 S4 (Intel Xeon E5520)

### SPECfp\_rate\_base2006 = 153

CPU2006 license: 9008


Test sponsor: ACTION S.A.

Tested by: ACTION S.A.

Test date: Jul-2009

Hardware Availability: Jun-2009

Software Availability: Feb-2009



#### Hardware

CPU Name: Intel Xeon E5520  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.53 GHz  
 CPU MHz: 2267  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

#### Software

Operating System: SuSe Linux Enterprise Server 10 (x86\_64) with SP2, kernel 2.6.16.60-0.21-smp  
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080930 Package ID: l\_cproc\_p\_11.0.066, l\_fproc\_p\_11.0.066  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECfp\_rate2006 = 158**

**ACTINA SOLAR 710 S4 (Intel Xeon E5520)**

**SPECfp\_rate\_base2006 = 153**

**CPU2006 license:** 9008

**Test date:** Jul-2009

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Jun-2009

**Tested by:** ACTION S.A.

**Software Availability:** Feb-2009

**L3 Cache:** 8 MB I+D on chip per chip  
**Other Cache:** None  
**Memory:** 24 GB (6 x 4 GB PC3-8500, 1066 MHz, DDR3, ECC)  
**Disk Subsystem:** 147 GB SAS, 10000 RPM  
**Other Hardware:** None

**Peak Pointers:** 32/64-bit  
**Other Software:** Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	1474	148	1387	157	<b>1405</b>	<b>155</b>	8	677	161	673	161	<b>676</b>	<b>161</b>
416.gamess	16	1949	161	<b>1962</b>	<b>160</b>	1968	159	8	1020	154	1023	153	<b>1022</b>	<b>153</b>
433.milc	16	974	151	<b>976</b>	<b>151</b>	976	150	16	<b>982</b>	<b>150</b>	1015	145	980	150
434.zeusmp	16	873	167	<b>852</b>	<b>171</b>	847	172	16	835	174	<b>837</b>	<b>174</b>	853	171
435.gromacs	16	745	153	737	155	<b>745</b>	<b>153</b>	16	<b>716</b>	<b>160</b>	715	160	721	159
436.cactusADM	16	1046	183	<b>1047</b>	<b>183</b>	1062	180	16	1138	168	1120	171	<b>1137</b>	<b>168</b>
437.leslie3d	16	<b>1327</b>	<b>113</b>	1325	114	1328	113	8	679	111	682	110	<b>680</b>	<b>111</b>
444.namd	16	899	143	<b>904</b>	<b>142</b>	909	141	16	882	146	<b>888</b>	<b>145</b>	903	142
447.dealII	16	822	223	<b>811</b>	<b>226</b>	810	226	16	<b>757</b>	<b>242</b>	759	241	744	246
450.soplex	16	1119	119	<b>1115</b>	<b>120</b>	1103	121	8	606	110	539	124	<b>540</b>	<b>124</b>
453.povray	16	443	192	429	198	<b>430</b>	<b>198</b>	16	373	228	<b>370</b>	<b>230</b>	367	232
454.calculix	16	713	185	716	184	<b>715</b>	<b>185</b>	16	712	185	<b>713</b>	<b>185</b>	714	185
459.GemsFDTD	16	1765	96.2	<b>1722</b>	<b>98.6</b>	1694	100	8	815	104	<b>817</b>	<b>104</b>	818	104
465.tonto	16	954	165	<b>958</b>	<b>164</b>	967	163	16	881	179	<b>896</b>	<b>176</b>	906	174
470.lbm	16	2191	100	<b>2184</b>	<b>101</b>	2183	101	8	1010	109	<b>1011</b>	<b>109</b>	1012	109
481.wrf	16	954	187	<b>975</b>	<b>183</b>	978	183	16	954	187	<b>975</b>	<b>183</b>	978	183
482.sphinx3	16	1827	171	1809	172	<b>1812</b>	<b>172</b>	16	1759	177	1750	178	<b>1750</b>	<b>178</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## General Notes

'numactl' was used to bind copies to the cores  
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECfp\_rate2006 = 158**

**ACTINA SOLAR 710 S4 (Intel Xeon E5520)**

**SPECfp\_rate\_base2006 = 153**

**CPU2006 license:** 9008

**Test date:** Jul-2009

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Jun-2009

**Tested by:** ACTION S.A.

**Software Availability:** Feb-2009

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:  
-xSSE4.2 -ipo -O3 -no-prec-div -static



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECfp\_rate2006 = 158**

**ACTINA SOLAR 710 S4 (Intel Xeon E5520)**

**SPECfp\_rate\_base2006 = 153**

**CPU2006 license:** 9008

**Test date:** Jul-2009

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Jun-2009

**Tested by:** ACTION S.A.

**Software Availability:** Feb-2009

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: ifort -m32

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 444.namd: -DSPEC\_CPU\_LP64  
 447.deallI: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -fno-alias

470.lbm: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
 -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECfp\_rate2006 = 158**

**ACTINA SOLAR 710 S4 (Intel Xeon E5520)**

**SPECfp\_rate\_base2006 = 153**

**CPU2006 license:** 9008

**Test date:** Jul-2009

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Jun-2009

**Tested by:** ACTION S.A.

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

### C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep-

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)

437.leslie3d: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -opt-prefetch

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ACTION S.A.**

**SPECfp\_rate2006 = 158**

**ACTINA SOLAR 710 S4 (Intel Xeon E5520)**

**SPECfp\_rate\_base2006 = 153**

**CPU2006 license:** 9008

**Test date:** Jul-2009

**Test sponsor:** ACTION S.A.

**Hardware Availability:** Jun-2009

**Tested by:** ACTION S.A.

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -auto-ilp32

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 03:38:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 18 August 2009.