



SPEC® CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176


Test Sponsor: Supermicro

Tested by: Supermicro

Test Date: Mar-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019



Hardware

CPU Name: Intel Xeon Platinum 8280
 Max MHz.: 4000
 Nominal: 2700
 Enabled: 224 cores, 8 chips, 2 threads/core
 Orderable: 2,4,8 Chips
 Cache L1: 32 KB I + 32 KB D on chip per core
 L2: 1 MB I+D on chip per core
 L3: 38.5 MB I+D on chip per chip
 Other: None
 Memory: 3 TB (96 x 32 GB 2Rx4 PC4-2933Y-R)
 Storage: 1 x 2TB SATA III SSD
 Other: None

Software

OS: SUSE Linux Enterprise Server 12 SP4 4.12.14-94.41-default
 Compiler: C/C++: Version 19.0.1.144 of Intel C/C++ Compiler Build 20181018 for Linux;
 Fortran: Version 19.0.1.144 of Intel Fortran Compiler Build 20181018 for Linux
 Parallel: No
 Firmware: Supermicro BIOS version 3.0a released Mar-2019 tested as Feb-2019
 File System: xfs
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit
 Peak Pointers: Not Applicable
 Other: None



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Sponsor: Supermicro

Tested by: Supermicro

Test Date: Mar-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r	448	2110	2130	2171	2070	2168	2070							
507.cactusBSSN_r	448	597	949	599	947	599	947							
508.namd_r	448	429	993	427	997	431	988							
510.parest_r	448	2392	490	2329	503	2349	499							
511.povray_r	448	728	1440	725	1440	725	1440							
519.lbm_r	448	903	523	903	523	902	524							
521.wrf_r	448	1085	925	1095	917	1084	926							
526.blender_r	448	501	1360	503	1360	502	1360							
527.cam4_r	448	573	1370	574	1370	571	1370							
538.imagick_r	448	370	3010	369	3020	369	3020							
544.nab_r	448	341	2210	342	2210	341	2210							
549.fotonik3d_r	448	2536	689	2536	689	2552	684							
554.roms_r	448	1773	402	1800	396	1773	402							

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

General Notes

Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/cpu2017/lib/ia32:/home/cpu2017/lib/intel64"

Binaries compiled on a system with 1x Intel Core i9-7900X CPU + 32GB RAM memory using Redhat Enterprise Linux 7.5

Transparent Huge Pages enabled by default

Prior to runcpu invocation

Filesystem page cache synced and cleared with:

`sync; echo 3 > /proc/sys/vm/drop_caches`

runcpu command invoked through numactl i.e.:

`numactl --interleave=all runcpu <etc>`

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

General Notes (Continued)

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Platform Notes

BIOS Settings:

SNC = Enable

IMC Interleave = 1-Way

Monitor/Mwait = Disable

Power Technology = Custom

Power Performance Tuning = BIOS Control EPB

Energy PERF BIAS CFG mode = Performance

Hardware P-state = Native Mode

XPT Prefetch = Enable

KTI Prefetch = Disable

Stale AtoS = Disable

LLC dead line alloc = Disable

Local/Remote Threshold = Medium

Patrol Scrub = Disable

Sysinfo program /home/cpu2017/bin/sysinfo

Rev: r5974 of 2018-05-19 9bcde8f2999c33d61f64985e45859ea9

running on linux Fri Mar 15 15:46:04 2019

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) Platinum 8280 CPU @ 2.70GHz

8 "physical id"s (chips)

448 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 28

siblings : 56

physical 0: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30

physical 1: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30

physical 2: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30

physical 3: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30

physical 4: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

Platform Notes (Continued)

```
28 29 30
physical 5: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30
physical 6: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30
physical 7: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24 25 26 27
28 29 30
```

From lscpu:

Architecture:	x86_64
CPU op-mode(s):	32-bit, 64-bit
Byte Order:	Little Endian
CPU(s):	448
On-line CPU(s) list:	0-447
Thread(s) per core:	2
Core(s) per socket:	28
Socket(s):	8
NUMA node(s):	16
Vendor ID:	GenuineIntel
CPU family:	6
Model:	85
Model name:	Intel(R) Xeon(R) Platinum 8280 CPU @ 2.70GHz
Stepping:	6
CPU MHz:	2700.000
CPU max MHz:	4000.0000
CPU min MHz:	1000.0000
BogoMIPS:	5400.00
Virtualization:	VT-x
L1d cache:	32K
L1i cache:	32K
L2 cache:	1024K
L3 cache:	39424K
NUMA node0 CPU(s):	0,225-231,238-243,252-259,266-271
NUMA node1 CPU(s):	1-7,14-19,28-35,42-47,224
NUMA node2 CPU(s):	8-13,20-27,36-41,48-55
NUMA node3 CPU(s):	56-63,70-75,84-91,98-103
NUMA node4 CPU(s):	64-69,76-83,92-97,104-111
NUMA node5 CPU(s):	112-119,126-131,140-147,154-159
NUMA node6 CPU(s):	120-125,132-139,148-153,160-167
NUMA node7 CPU(s):	168-175,182-187,196-203,210-215
NUMA node8 CPU(s):	176-181,188-195,204-209,216-223
NUMA node9 CPU(s):	232-237,244-251,260-265,272-279
NUMA node10 CPU(s):	280-287,294-299,308-315,322-327
NUMA node11 CPU(s):	288-293,300-307,316-321,328-335
NUMA node12 CPU(s):	336-343,350-355,364-371,378-383
NUMA node13 CPU(s):	344-349,356-363,372-377,384-391
NUMA node14 CPU(s):	392-399,406-411,420-427,434-439

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

Platform Notes (Continued)

```
NUMA node15 CPU(s): 400-405,412-419,428-433,440-447
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp
lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc cpuid
aperfmpfperf pni pclmulqdq dtes64 ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm
pcid dca sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c
rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb cat_l3 cdp_l3 invpcid_single ssbd
mba ibrs ibpb stibp tpr_shadow vnmi flexpriority ept vpid fsgsbase tsc_adjust bmi1
hle avx2 smep bmi2 erms invpcid rtm cqm mpx rdt_a avx512f avx512dq rdseed adx smap
clflushopt clwb intel_pt avx512cd avx512bw avx512vl xsaveopt xsavexc xgetbv1 xsaves
cqm_llc cqm_occup_llc cqm_mbm_total cqm_mbm_local dtherm ida arat pln pts hwp
hwp_act_window hwp_epp hwp_pkg_req pku ospke avx512_vnni flush_lld arch_capabilities
```

```
/proc/cpuinfo cache data
cache size : 39424 KB
```

```
From numactl --hardware
WARNING: a numactl 'node' might or might not correspond to a
physical chip.
```

```
available: 16 nodes (0-15)
node 0 cpus: 0 225 226 227 228 229 230 231 238 239 240 241 242 243 252 253 254 255 256
257 258 259 266 267 268 269 270 271
node 0 size: 193530 MB
node 0 free: 185809 MB
node 1 cpus: 1 2 3 4 5 6 7 14 15 16 17 18 19 28 29 30 31 32 33 34 35 42 43 44 45 46 47
224
node 1 size: 192095 MB
node 1 free: 185997 MB
node 2 cpus: 8 9 10 11 12 13 20 21 22 23 24 25 26 27 36 37 38 39 40 41 48 49 50 51 52
53 54 55
node 2 size: 193530 MB
node 2 free: 187537 MB
node 3 cpus: 56 57 58 59 60 61 62 63 70 71 72 73 74 75 84 85 86 87 88 89 90 91 98 99
100 101 102 103
node 3 size: 193530 MB
node 3 free: 187541 MB
node 4 cpus: 64 65 66 67 68 69 76 77 78 79 80 81 82 83 92 93 94 95 96 97 104 105 106
107 108 109 110 111
node 4 size: 193530 MB
node 4 free: 187545 MB
node 5 cpus: 112 113 114 115 116 117 118 119 126 127 128 129 130 131 140 141 142 143
144 145 146 147 154 155 156 157 158 159
node 5 size: 193530 MB
node 5 free: 187539 MB
node 6 cpus: 120 121 122 123 124 125 132 133 134 135 136 137 138 139 148 149 150 151
152 153 160 161 162 163 164 165 166 167
node 6 size: 193530 MB
node 6 free: 187545 MB
```

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

Platform Notes (Continued)

```

node 7 cpus: 168 169 170 171 172 173 174 175 182 183 184 185 186 187 196 197 198 199
200 201 202 203 210 211 212 213 214 215
node 7 size: 193530 MB
node 7 free: 187497 MB
node 8 cpus: 176 177 178 179 180 181 188 189 190 191 192 193 194 195 204 205 206 207
208 209 216 217 218 219 220 221 222 223
node 8 size: 193501 MB
node 8 free: 186963 MB
node 9 cpus: 232 233 234 235 236 237 244 245 246 247 248 249 250 251 260 261 262 263
264 265 272 273 274 275 276 277 278 279
node 9 size: 193530 MB
node 9 free: 187555 MB
node 10 cpus: 280 281 282 283 284 285 286 287 294 295 296 297 298 299 308 309 310 311
312 313 314 315 322 323 324 325 326 327
node 10 size: 193530 MB
node 10 free: 187548 MB
node 11 cpus: 288 289 290 291 292 293 300 301 302 303 304 305 306 307 316 317 318 319
320 321 328 329 330 331 332 333 334 335
node 11 size: 193530 MB
node 11 free: 187546 MB
node 12 cpus: 336 337 338 339 340 341 342 343 350 351 352 353 354 355 364 365 366 367
368 369 370 371 378 379 380 381 382 383
node 12 size: 193530 MB
node 12 free: 187545 MB
node 13 cpus: 344 345 346 347 348 349 356 357 358 359 360 361 362 363 372 373 374 375
376 377 384 385 386 387 388 389 390 391
node 13 size: 193530 MB
node 13 free: 187553 MB
node 14 cpus: 392 393 394 395 396 397 398 399 406 407 408 409 410 411 420 421 422 423
424 425 426 427 434 435 436 437 438 439
node 14 size: 193530 MB
node 14 free: 187543 MB
node 15 cpus: 400 401 402 403 404 405 412 413 414 415 416 417 418 419 428 429 430 431
432 433 440 441 442 443 444 445 446 447
node 15 size: 193527 MB
node 15 free: 187545 MB
node distances:
node 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
 0: 10 21 21 31 31 31 31 31 31 11 21 21 31 31 21 21
 1: 21 10 11 21 21 21 21 31 31 21 31 31 31 31 31 31
 2: 21 11 10 21 21 21 21 31 31 21 31 31 31 31 31 31
 3: 31 21 21 10 11 31 31 21 21 31 21 21 31 31 31 31
 4: 31 21 21 11 10 31 31 21 21 31 21 21 31 31 31 31
 5: 31 21 21 31 31 10 11 21 21 31 31 21 21 31 31 31
 6: 31 21 21 31 31 11 10 21 21 31 31 21 21 31 31 31
 7: 31 31 31 21 21 21 21 10 11 31 31 31 31 31 21 21
 8: 31 31 31 21 21 21 21 11 10 31 31 31 31 31 21 21

```

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

Platform Notes (Continued)

```
9: 11 21 21 31 31 31 31 31 31 10 21 21 31 31 21 21  
10: 21 31 31 21 21 31 31 31 31 21 10 11 21 21 31 31  
11: 21 31 31 21 21 31 31 31 31 21 11 10 21 21 31 31  
12: 31 31 31 31 31 21 21 31 31 21 21 10 11 21 21 21  
13: 31 31 31 31 31 21 21 31 31 21 21 11 10 21 21 21  
14: 21 31 31 31 31 31 31 21 21 21 31 31 21 21 10 11  
15: 21 31 31 31 31 31 31 21 21 21 31 31 21 21 11 10
```

From /proc/meminfo

```
MemTotal: 3169303840 kB  
HugePages_Total: 0  
Hugepagesize: 2048 kB
```

```
/usr/bin/lsb_release -d  
SUSE Linux Enterprise Server 12 SP4
```

From /etc/*release* /etc/*version*

```
SuSE-release:  
  SUSE Linux Enterprise Server 12 (x86_64)  
  VERSION = 12  
  PATCHLEVEL = 4  
  # This file is deprecated and will be removed in a future service pack or release.  
  # Please check /etc/os-release for details about this release.  
os-release:  
  NAME="SLES"  
  VERSION="12-SP4"  
  VERSION_ID="12.4"  
  PRETTY_NAME="SUSE Linux Enterprise Server 12 SP4"  
  ID="sles"  
  ANSI_COLOR="0;32"  
  CPE_NAME="cpe:/o:suse:sles:12:sp4"
```

uname -a:

```
Linux linux 4.12.14-94.41-default #1 SMP Wed Oct 31 12:25:04 UTC 2018 (3090901) x86_64  
x86_64 x86_64 GNU/Linux
```

Kernel self-reported vulnerability status:

```
CVE-2017-5754 (Meltdown): Not affected  
CVE-2017-5753 (Spectre variant 1): Mitigation: __user pointer sanitization  
CVE-2017-5715 (Spectre variant 2): Mitigation: Indirect Branch Restricted Speculation,  
IBPB, IBRS_FW
```

run-level 3 Mar 15 11:02 last=5

SPEC is set to: /home/cpu2017

```
Filesystem Type Size Used Avail Use% Mounted on
```

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

Platform Notes (Continued)

```
/dev/sda3      xfs   1.8T  162G  1.6T  10% /home
```

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS American Megatrends Inc. 3.0a 02/15/2019

Memory:

96x Hynix HMA84GR7CJR4N-WM 32 GB 2 rank 2933, configured at 2934

(End of data from sysinfo program)

Compiler Version Notes

```
=====
```

CC 519.lbm_r(base) 538.imagick_r(base) 544.nab_r(base)

```
=====
```

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

```
=====
```

```
=====
```

CXXC 508.namd_r(base) 510.parest_r(base)

```
=====
```

Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

```
=====
```

```
=====
```

CC 511.povray_r(base) 526.blender_r(base)

```
=====
```

Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

```
=====
```

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.0.1.144 Build 20181018
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

```
=====
```

```
=====
```

FC 507.cactuBSSN_r(base)

```
=====
```

Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.0.1.144 Build 20181018

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Date: Mar-2019

Test Sponsor: Supermicro

Hardware Availability: Apr-2019

Tested by: Supermicro

Software Availability: Feb-2019

Compiler Version Notes (Continued)

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.
Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,

Version 19.0.1.144 Build 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
64, Version 19.0.1.144 Build 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

FC 503.bwaves_r(base) 549.fotonik3d_r(base) 554.roms_r(base)

=====

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
64, Version 19.0.1.144 Build 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

CC 521.wrf_r(base) 527.cam4_r(base)

=====

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
64, Version 19.0.1.144 Build 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.0.1.144 Build 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

icc -m64 -std=c11

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

ifort -m64 icc -m64 -std=c11

Benchmarks using both C and C++:

icpc -m64 icc -m64 -std=c11

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Sponsor: Supermicro

Tested by: Supermicro

Test Date: Mar-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

Base Compiler Invocation (Continued)

Benchmarks using Fortran, C, and C++:

```
icpc -m64icc -m64 -std=c11 ifort -m64
```

Base Portability Flags

```
503.bwaves_r: -DSPEC_LP64
507.cactusBSSN_r: -DSPEC_LP64
508.namd_r: -DSPEC_LP64
510.parest_r: -DSPEC_LP64
511.povray_r: -DSPEC_LP64
519.lbm_r: -DSPEC_LP64
521.wrf_r: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
526.blender_r: -DSPEC_LP64 -DSPEC_LINUX -funsigned-char
527.cam4_r: -DSPEC_LP64 -DSPEC_CASE_FLAG
538.imagick_r: -DSPEC_LP64
544.nab_r: -DSPEC_LP64
549.fotonik3d_r: -DSPEC_LP64
554.roms_r: -DSPEC_LP64
```

Base Optimization Flags

C benchmarks:

```
-xCORE-AVX512 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=4
```

C++ benchmarks:

```
-xCORE-AVX512 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=4
```

Fortran benchmarks:

```
-xCORE-AVX512 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=4 -auto
-nostandard-realloc-lhs -align array32byte
```

Benchmarks using both Fortran and C:

```
-xCORE-AVX512 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=4 -auto
-nostandard-realloc-lhs -align array32byte
```

Benchmarks using both C and C++:

```
-xCORE-AVX512 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=4
```

(Continued on next page)



SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Supermicro

SuperServer 7089P-TR4T (X11OPi, Intel Xeon Platinum 8280)

SPECrate2017_fp_base = 1070

SPECrate2017_fp_peak = Not Run

CPU2017 License: 001176

Test Sponsor: Supermicro

Tested by: Supermicro

Test Date: Mar-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

Base Optimization Flags (Continued)

Benchmarks using Fortran, C, and C++:

```
-xCORE-AVX512 -ipo -O3 -no-prec-div -qopt-prefetch  
-ffinite-math-only -qopt-mem-layout-trans=4 -auto  
-nostandard-realloc-lhs -align array32byte
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Supermicro-Platform-Settings-V1.2-SKL-revD.html>
<http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2019-04-02.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Supermicro-Platform-Settings-V1.2-SKL-revD.xml>
<http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2019-04-02.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.5 on 2019-03-15 18:46:02-0400.

Report generated on 2019-04-02 16:54:20 by CPU2017 PDF formatter v6067.

Originally published on 2019-04-02.