



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECSpeed®2017\_int\_base = 8.60

SPECSpeed®2017\_int\_peak = 8.78

CPU2017 License: 55


Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019



Hardware		Software	
CPU Name:	AMD EPYC 7642	OS:	SUSE Linux Enterprise Server 15 SP1
Max MHz:	3300		kernel 4.12.14-195-default
Nominal:	2300	Compiler:	C/C++/Fortran: Version 2.0.0 of AOCC
Enabled:	96 cores, 2 chips, 2 threads/core	Parallel:	Yes
Orderable:	1,2 chips	Firmware:	Version 1.0.1 released Sep-2019
Cache L1:	32 KB I + 32 KB D on chip per core	File System:	xfs
L2:	512 KB I+D on chip per core	System State:	Run level 3 (multi-user)
L3:	256 MB I+D on chip per chip, 16 MB shared / 3 cores	Base Pointers:	64-bit
Other:	None	Peak Pointers:	32/64-bit
Memory:	512 GB (16 x 32 GB 2Rx4 PC4-3200AA-R)	Other:	jemalloc: jemalloc memory allocator library v5.2.0
Storage:	1 x 480 GB SAS SSD	Power Management:	BIOS set to prefer performance at the cost of additional power usage.
Other:	None		



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55  
Test Sponsor: Dell Inc.  
Tested by: Dell Inc.

Test Date: Oct-2019  
Hardware Availability: Feb-2020  
Software Availability: Aug-2019

## Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s	96	<b><u>378</u></b>	<b><u>4.70</u></b>	378	4.70	378	4.70	1	<b><u>360</u></b>	<b><u>4.93</u></b>	<b><u>360</u></b>	<b><u>4.94</u></b>	358	4.95
602.gcc_s	96	<b><u>426</u></b>	<b><u>9.36</u></b>	428	9.30	425	9.37	96	<b><u>426</u></b>	<b><u>9.36</u></b>	428	9.30	<b><u>425</u></b>	9.37
605.mcf_s	96	<b><u>324</u></b>	<b><u>14.6</u></b>	326	14.5	323	14.6	1	<b><u>305</u></b>	<b><u>15.5</u></b>	305	15.5	<b><u>304</u></b>	15.5
620.omnetpp_s	96	<b><u>344</u></b>	<b><u>4.73</u></b>	338	4.83	346	4.71	96	<b><u>344</u></b>	<b><u>4.73</u></b>	338	4.83	<b><u>346</u></b>	4.71
623.xalancbmk_s	96	<b><u>154</u></b>	<b><u>9.20</u></b>	153	9.27	155	9.12	1	<b><u>145</u></b>	<b><u>9.75</u></b>	<b><u>145</u></b>	<b><u>9.80</u></b>	<b><u>144</u></b>	9.82
625.x264_s	96	146	12.1	148	11.9	<b><u>148</u></b>	<b><u>11.9</u></b>	1	<b><u>144</u></b>	12.3	<b><u>144</u></b>	<b><u>12.2</u></b>	<b><u>145</u></b>	12.1
631.deepsjeng_s	96	302	4.75	300	4.78	<b><u>300</u></b>	<b><u>4.77</u></b>	1	<b><u>297</u></b>	<b><u>4.82</u></b>	298	4.81	<b><u>297</u></b>	4.82
641.leela_s	96	413	4.13	<b><u>411</u></b>	<b><u>4.15</u></b>	410	4.16	96	<b><u>413</u></b>	4.13	<b><u>411</u></b>	<b><u>4.15</u></b>	<b><u>410</u></b>	4.16
648.exchange2_s	96	181	16.3	<b><u>181</u></b>	<b><u>16.3</u></b>	180	16.3	96	<b><u>181</u></b>	16.3	<b><u>181</u></b>	<b><u>16.3</u></b>	<b><u>180</u></b>	16.3
657.xz_s	96	299	20.7	300	20.6	<b><u>299</u></b>	<b><u>20.6</u></b>	96	301	20.5	<b><u>299</u></b>	<b><u>20.7</u></b>	299	20.7
SPECspeed®2017_int_base =			<b><u>8.60</u></b>											
SPECspeed®2017_int_peak =			<b><u>8.78</u></b>											

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Notes

The AMD64 AOCC Compiler Suite is available at  
<http://developer.amd.com/amd-aocc/>

## Submit Notes

The config file option 'submit' was used.  
'numactl' was used to bind copies to the cores.  
See the configuration file for details.

## Operating System Notes

'ulimit -s unlimited' was used to set environment stack size  
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:  
numactl --interleave=all runcpu <etc>

Set dirty\_ratio=8 to limit dirty cache to 8% of memory  
Set swappiness=1 to swap only if necessary  
Set zone\_reclaim\_mode=1 to free local node memory and avoid remote memory sync then drop\_caches=3 to reset caches before invoking runcpu

dirty\_ratio, swappiness, zone\_reclaim\_mode and drop\_caches were all set using privileged echo (e.g. echo 1 > /proc/sys/vm/swappiness).

Transparent huge pages set to 'always' for this run (OS default)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
GOMP_CPU_AFFINITY = "0-191"
LD_LIBRARY_PATH =
    "/root/cpu2017-1.0.5/cpu2017-1.1.0/amd_speed_aocc200_rome_C_lib/64;/root
    /cpu2017-1.0.5/cpu2017-1.1.0/amd_speed_aocc200_rome_C_lib/32:"
MALLOC_CONF = "retain:true"
OMP_DYNAMIC = "false"
OMP_SCHEDULE = "static"
OMP_STACKSIZE = "128M"
OMP_THREAD_LIMIT = "192"
```

Environment variables set by runcpu during the 600.perlbench\_s peak run:

```
GOMP_CPU_AFFINITY = "0"
```

Environment variables set by runcpu during the 605.mcf\_s peak run:

```
GOMP_CPU_AFFINITY = "0"
```

Environment variables set by runcpu during the 623.xalancbmk\_s peak run:

```
GOMP_CPU_AFFINITY = "0"
OMP_STACKSIZE = "128M"
```

Environment variables set by runcpu during the 625.x264\_s peak run:

```
GOMP_CPU_AFFINITY = "0"
```

Environment variables set by runcpu during the 631.deepsjeng\_s peak run:

```
GOMP_CPU_AFFINITY = "0"
```

Environment variables set by runcpu during the 657.xz\_s peak run:

```
GOMP_CPU_AFFINITY = "0-95"
```

## General Notes

Binaries were compiled on a system with 2x AMD EPYC 7601 CPU + 512GB Memory using Fedora 26

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

jemalloc: configured and built with GCC v9.1.0 in Ubuntu 19.04 with -O3 -fno-omit-frame-pointer  
jemalloc 5.2.0 is available here:

<https://github.com/jemalloc/jemalloc/releases/download/5.2.0/jemalloc-5.2.0.tar.bz2>



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes

BIOS settings:

NUMA Nodes Per Socket set to 4  
CCX as NUMA Domain set to Enabled  
System Profile set to Custom  
CPU Power Management set to Maximum Performance  
Memory Frequency set to Maximum Performance  
Turbo Boost Enabled  
Cstates set to Enabled  
Memory Patrol Scrub Disabled  
Memory Refresh Rate set to 1x  
PCI ASPM L1 Link Power Management Disabled  
Determinism Slider set to Power Determinism  
Efficiency Optimized Mode Disabled  
Memory Interleaving set to Disabled

Sysinfo program /root/cpu2017-1.0.5/cpu2017-1.1.0/bin/sysinfo  
Rev: r6365 of 2019-08-21 295195f888a3d7edb1e6e46a485a0011  
running on linux-g3ob Sat Oct 26 06:33:46 2019

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : AMD EPYC 7642 48-Core Processor
  2 "physical id"s (chips)
  192 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores : 48
  siblings   : 96
  physical 0: cores 0 1 2 4 5 6 8 9 10 12 13 14 16 17 18 20 21 22 24 25 26 28 29 30
              32 33 34 36 37 38 40 41 42 44 45 46 48 49 50 52 53 54 56 57 58 60 61 62
  physical 1: cores 0 1 2 4 5 6 8 9 10 12 13 14 16 17 18 20 21 22 24 25 26 28 29 30
              32 33 34 36 37 38 40 41 42 44 45 46 48 49 50 52 53 54 56 57 58 60 61 62
```

From lscpu:

```
Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Byte Order:            Little Endian
Address sizes:         43 bits physical, 48 bits virtual
CPU(s):                192
On-line CPU(s) list:  0-191
Thread(s) per core:   2
Core(s) per socket:   48
Socket(s):             2
NUMA node(s):          32
```

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

Vendor ID: AuthenticAMD  
CPU family: 23  
Model: 49  
Model name: AMD EPYC 7642 48-Core Processor  
Stepping: 0  
CPU MHz: 2295.709  
BogoMIPS: 4591.41  
Virtualization: AMD-V  
L1d cache: 32K  
L1i cache: 32K  
L2 cache: 512K  
L3 cache: 16384K  
NUMA node0 CPU(s): 0-2,96-98  
NUMA node1 CPU(s): 3-5,99-101  
NUMA node2 CPU(s): 6-8,102-104  
NUMA node3 CPU(s): 9-11,105-107  
NUMA node4 CPU(s): 12-14,108-110  
NUMA node5 CPU(s): 15-17,111-113  
NUMA node6 CPU(s): 18-20,114-116  
NUMA node7 CPU(s): 21-23,117-119  
NUMA node8 CPU(s): 24-26,120-122  
NUMA node9 CPU(s): 27-29,123-125  
NUMA node10 CPU(s): 30-32,126-128  
NUMA node11 CPU(s): 33-35,129-131  
NUMA node12 CPU(s): 36-38,132-134  
NUMA node13 CPU(s): 39-41,135-137  
NUMA node14 CPU(s): 42-44,138-140  
NUMA node15 CPU(s): 45-47,141-143  
NUMA node16 CPU(s): 48-50,144-146  
NUMA node17 CPU(s): 51-53,147-149  
NUMA node18 CPU(s): 54-56,150-152  
NUMA node19 CPU(s): 57-59,153-155  
NUMA node20 CPU(s): 60-62,156-158  
NUMA node21 CPU(s): 63-65,159-161  
NUMA node22 CPU(s): 66-68,162-164  
NUMA node23 CPU(s): 69-71,165-167  
NUMA node24 CPU(s): 72-74,168-170  
NUMA node25 CPU(s): 75-77,171-173  
NUMA node26 CPU(s): 78-80,174-176  
NUMA node27 CPU(s): 81-83,177-179  
NUMA node28 CPU(s): 84-86,180-182  
NUMA node29 CPU(s): 87-89,183-185  
NUMA node30 CPU(s): 90-92,186-188  
NUMA node31 CPU(s): 93-95,189-191  
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mttr pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr\_opt pdpe1gb rdtscp lm constant\_tsc rep\_good nopl xtopology nonstop\_tsc cpuid extd\_apicid aperfmpfperf pn1

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
pclmulqdq monitor ssse3 fma cx16 sse4_1 sse4_2 x2apic movbe popcnt aes xsave avx  
f16c rdrand lahf_lm cmp_legacy svm extapic cr8_legacy abm sse4a misalignsse  
3dnowprefetch osvw ibs skinit wdt tce topoext perfctr_core perfctr_nb bpext  
perfctr_l2 mwaitx cpb cat_l3 cdp_l3 hw_pstate sme ssbd sev ibrs ibpb stibp vmmcall  
fsgsbase bmi1 avx2 smep bmi2 cqmq rdt_a rdseed adx smap clflushopt clwb sha_ni  
xsaveopt xsavec xgetbv1 xsaves cqmq_llc cqmq_occup_llc cqmq_mbm_total cqmq_mbm_local  
clzero irperf xsaveerptr arat npt lbrv svm_lock nrrip_save tsc_scale vmcb_clean  
flushbyasid decodeassists pausefilter pfthreshold avic v_vmsave_vmlload vgif umip  
rdpid overflow_recov succor smca
```

```
/proc/cpuinfo cache data  
cache size : 512 KB
```

From numactl --hardware    WARNING: a numactl 'node' might or might not correspond to a physical chip.

```
available: 32 nodes (0-31)  
node 0 cpus: 0 1 2 96 97 98  
node 0 size: 15676 MB  
node 0 free: 15615 MB  
node 1 cpus: 3 4 5 99 100 101  
node 1 size: 16126 MB  
node 1 free: 16081 MB  
node 2 cpus: 6 7 8 102 103 104  
node 2 size: 16126 MB  
node 2 free: 16088 MB  
node 3 cpus: 9 10 11 105 106 107  
node 3 size: 16125 MB  
node 3 free: 16087 MB  
node 4 cpus: 12 13 14 108 109 110  
node 4 size: 16126 MB  
node 4 free: 15948 MB  
node 5 cpus: 15 16 17 111 112 113  
node 5 size: 16126 MB  
node 5 free: 16039 MB  
node 6 cpus: 18 19 20 114 115 116  
node 6 size: 16126 MB  
node 6 free: 15735 MB  
node 7 cpus: 21 22 23 117 118 119  
node 7 size: 16125 MB  
node 7 free: 16022 MB  
node 8 cpus: 24 25 26 120 121 122  
node 8 size: 16126 MB  
node 8 free: 16056 MB  
node 9 cpus: 27 28 29 123 124 125  
node 9 size: 16126 MB  
node 9 free: 16084 MB  
node 10 cpus: 30 31 32 126 127 128
```

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
node 10 size: 16126 MB
node 10 free: 16087 MB
node 11 cpus: 33 34 35 129 130 131
node 11 size: 16125 MB
node 11 free: 16077 MB
node 12 cpus: 36 37 38 132 133 134
node 12 size: 16126 MB
node 12 free: 16087 MB
node 13 cpus: 39 40 41 135 136 137
node 13 size: 16126 MB
node 13 free: 16088 MB
node 14 cpus: 42 43 44 138 139 140
node 14 size: 16126 MB
node 14 free: 16087 MB
node 15 cpus: 45 46 47 141 142 143
node 15 size: 16113 MB
node 15 free: 16074 MB
node 16 cpus: 48 49 50 144 145 146
node 16 size: 16126 MB
node 16 free: 16088 MB
node 17 cpus: 51 52 53 147 148 149
node 17 size: 16126 MB
node 17 free: 16087 MB
node 18 cpus: 54 55 56 150 151 152
node 18 size: 16126 MB
node 18 free: 16087 MB
node 19 cpus: 57 58 59 153 154 155
node 19 size: 16096 MB
node 19 free: 16057 MB
node 20 cpus: 60 61 62 156 157 158
node 20 size: 16126 MB
node 20 free: 16087 MB
node 21 cpus: 63 64 65 159 160 161
node 21 size: 16126 MB
node 21 free: 16088 MB
node 22 cpus: 66 67 68 162 163 164
node 22 size: 16126 MB
node 22 free: 16088 MB
node 23 cpus: 69 70 71 165 166 167
node 23 size: 16125 MB
node 23 free: 16086 MB
node 24 cpus: 72 73 74 168 169 170
node 24 size: 16126 MB
node 24 free: 16085 MB
node 25 cpus: 75 76 77 171 172 173
node 25 size: 16126 MB
node 25 free: 16089 MB
```

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
node 26 cpus: 78 79 80 174 175 176
node 26 size: 16126 MB
node 26 free: 16088 MB
node 27 cpus: 81 82 83 177 178 179
node 27 size: 16125 MB
node 27 free: 16088 MB
node 28 cpus: 84 85 86 180 181 182
node 28 size: 16126 MB
node 28 free: 16087 MB
node 29 cpus: 87 88 89 183 184 185
node 29 size: 16126 MB
node 29 free: 16087 MB
node 30 cpus: 90 91 92 186 187 188
node 30 size: 16126 MB
node 30 free: 16088 MB
node 31 cpus: 93 94 95 189 190 191
node 31 size: 16124 MB
node 31 free: 16084 MB
node distances:
```

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
20	21	22	23	24	25	26	27	28	29	30	31									
0:	10	11	11	11	12	12	12	12	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
1:	11	10	11	11	12	12	12	12	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
2:	11	11	10	11	12	12	12	12	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
3:	11	11	11	10	12	12	12	12	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
4:	12	12	12	12	10	11	11	11	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
5:	12	12	12	12	11	10	11	11	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
6:	12	12	12	12	11	11	10	11	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
7:	12	12	12	12	11	11	11	10	12	12	12	12	12	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
8:	12	12	12	12	12	12	12	12	12	10	11	11	11	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
9:	12	12	12	12	12	12	12	12	12	11	10	11	11	12	12	12	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
10:	12	12	12	12	12	12	12	12	12	12	11	11	10	11	12	12	12	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
11:	12	12	12	12	12	12	12	12	12	11	11	11	10	10	12	12	12	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									
12:	12	12	12	12	12	12	12	12	12	12	12	12	12	12	10	11	11	32	32	
32	32	32	32	32	32	32	32	32	32	32	32									

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

13:	12	12	12	12	12	12	12	12	12	12	12	12	12	12	11	10	11	11	32	32	32	32		
32	32	32	32	32	32	32	32	32	32	32	32	32	32	32										
14:	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	11	11	10	11	32	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32									
15:	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	11	11	10	32	32	32	32	
32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32								
16:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	10	11	11	11	
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
17:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	11	10	11	11
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
18:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	11	11	10	11
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
19:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	11	11	11	10
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
20:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
10	11	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
21:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
11	10	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
22:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
11	11	10	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
23:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
11	11	11	10	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
24:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	10	11	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
25:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	11	10	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
26:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	11	11	10	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
27:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	11	11	11	10	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
28:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
29:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
30:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
31:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	

From /proc/meminfo

MemTotal: 527927004 kB

HugePages\_Total: 0

Hugepagesize: 2048 kB

From /etc/\*release\* /etc/\*version\*

os-release:

NAME="SLES"

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
VERSION="15-SP1"
VERSION_ID="15.1"
PRETTY_NAME="SUSE Linux Enterprise Server 15 SP1"
ID="sles"
ID_LIKE="suse"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:15:sp1"
```

```
uname -a:
Linux linux-g3ob 4.12.14-195-default #1 SMP Tue May 7 10:55:11 UTC 2019 (8fba516)
x86_64 x86_64 x86_64 GNU/Linux
```

Kernel self-reported vulnerability status:

CVE-2018-3620 (L1 Terminal Fault):	Not affected
Microarchitectural Data Sampling:	Not affected
CVE-2017-5754 (Meltdown):	Not affected
CVE-2018-3639 (Speculative Store Bypass):	Mitigation: Speculative Store Bypass disabled via prctl and seccomp
CVE-2017-5753 (Spectre variant 1):	Mitigation: __user pointer sanitization
CVE-2017-5715 (Spectre variant 2):	Mitigation: Full AMD retpoline, IBPB: conditional, IBRS_FW, STIBP: conditional, RSB filling

run-level 3 Oct 24 12:29

```
SPEC is set to: /root/cpu2017-1.0.5/cpu2017-1.1.0
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2        xfs   440G   32G  409G   8%  /
```

```
From /sys/devices/virtual/dmi/id
  BIOS:    Dell Inc. 1.0.1 09/21/2019
  Vendor:  Dell Inc.
  Product: PowerEdge C6525
  Product Family: PowerEdge
```

Additional information from dmidecode follows. **WARNING:** Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

```
4x 802C80B3802C 36ASF4G72PZ-3G2E2 32 GB 2 rank 3200
4x 802C869D802C 36ASF4G72PZ-3G2E2 32 GB 2 rank 3200
8x 80AD863280AD HMA84GR7CJR4N-XN 32 GB 2 rank 3200
```

(End of data from sysinfo program)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Compiler Version Notes

=====

C | 600.perlbench\_s(base, peak) 602.gcc\_s(base, peak) 605.mcf\_s(base,  
| peak) 625.x264\_s(base, peak) 657.xz\_s(base, peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

=====

C++ | 623.xalancbmk\_s(peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

=====

C++ | 620.omnetpp\_s(base, peak) 623.xalancbmk\_s(base)  
| 631.deepsjeng\_s(base, peak) 641.leela\_s(base, peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

=====

C++ | 623.xalancbmk\_s(peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

=====

C++ | 620.omnetpp\_s(base, peak) 623.xalancbmk\_s(base)  
| 631.deepsjeng\_s(base, peak) 641.leela\_s(base, peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Compiler Version Notes (Continued)

AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====  
Fortran | 648.exchange2\_s(base, peak)

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins

AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

## Base Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Fortran benchmarks:

flang

## Base Portability Flags

600.perlbench\_s: -DSPEC\_LINUX\_X64 -DSPEC\_LP64  
602.gcc\_s: -DSPEC\_LP64  
605.mcf\_s: -DSPEC\_LP64  
620.omnetpp\_s: -DSPEC\_LP64  
623.xalancbmk\_s: -DSPEC\_LINUX -DSPEC\_LP64  
625.x264\_s: -DSPEC\_LP64  
631.deepsjeng\_s: -DSPEC\_LP64  
641.leela\_s: -DSPEC\_LP64  
648.exchange2\_s: -DSPEC\_LP64  
657.xz\_s: -DSPEC\_LP64



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Base Optimization Flags

C benchmarks:

```
-floop -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize -Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -ffast-math  
-march=znver2 -fstruct-layout=3 -mllvm -unroll-threshold=50  
-fremap-arrays -mllvm -function-specialize -mllvm -enable-gvn-hoist  
-mllvm -reduce-array-computations=3 -mllvm -global-vectorize-slp  
-mllvm -vector-library=LIBMVEC -mllvm -inline-threshold=1000  
-flv-function-specialization -z muldefs -DSPEC_OPENMP -fopenmp  
-DUSE_OPENMP -fopenmp=libomp -lomp -lpthread -ldl -lmvec -lamdlibm  
-ljemalloc -lflang
```

C++ benchmarks:

```
-floop -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize -Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-Wl,-mllvm -Wl,-suppress-fmas -O3 -ffast-math -march=znver2  
-mllvm -loop-unswitch-threshold=200000 -mllvm -vector-library=LIBMVEC  
-mllvm -unroll-threshold=100 -flv-function-specialization  
-mllvm -enable-partial-unswitch -z muldefs -DSPEC_OPENMP -fopenmp  
-DUSE_OPENMP -fopenmp=libomp -lomp -lpthread -ldl -lmvec -lamdlibm  
-ljemalloc -lflang
```

Fortran benchmarks:

```
-floop -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize -Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -ffast-math  
-Wl,-mllvm -Wl,-inline-recursion=4 -Wl,-mllvm -Wl,-lsr-in-nested-loop  
-Wl,-mllvm -Wl,-enable-iv-split -O3 -march=znver2 -funroll-loops  
-Mrecursive -mllvm -vector-library=LIBMVEC -z muldefs  
-mllvm -disable-indvar-simplify -mllvm -unroll-aggressive  
-mllvm -unroll-threshold=150 -DSPEC_OPENMP -fopenmp -DUSE_OPENMP  
-fopenmp=libomp -lomp -lpthread -ldl -lmvec -lamdlibm -ljemalloc  
-lflang
```

## Base Other Flags

C benchmarks:

```
-Wno-return-type
```

C++ benchmarks:

```
-Wno-return-type
```

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Base Other Flags (Continued)

Fortran benchmarks:

-Wno-return-type

## Peak Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Fortran benchmarks:

flang

## Peak Portability Flags

600.perlbench\_s: -DSPEC\_LINUX\_X64 -DSPEC\_LP64  
602.gcc\_s: -DSPEC\_LP64  
605.mcf\_s: -DSPEC\_LP64  
620.omnetpp\_s: -DSPEC\_LP64  
623.xalancbmk\_s: -DSPEC\_LINUX -D\_FILE\_OFFSET\_BITS=64  
625.x264\_s: -DSPEC\_LP64  
631.deepsjeng\_s: -DSPEC\_LP64  
641.leela\_s: -DSPEC\_LP64  
648.exchange2\_s: -DSPEC\_LP64  
657.xz\_s: -DSPEC\_LP64

## Peak Optimization Flags

C benchmarks:

600.perlbench\_s: -flto -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-fprofile-instr-generate(pass 1)  
-fprofile-instr-use(pass 2) -Ofast -march=znver2  
-mno-sse4a -fstruct-layout=5  
-mllvm -vectorize-memory-aggressively  
-mllvm -function-specialize -mllvm -enable-gvn-hoist

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Peak Optimization Flags (Continued)

600.perlbench\_s (continued):

```
-mllvm -unroll-threshold=50 -fremap-arrays  
-mllvm -vector-library=LIBMVEC  
-mllvm -reduce-array-computations=3  
-mllvm -global-vectorize-slp -mllvm -inline-threshold=1000  
-flv-function-specialization -DSPEC_OPENMP -fopenmp  
-DUSE_OPENMP -lmvec -lamdlibm -fopenmp=libomp -lomp  
-lpthread -ldl -ljemalloc -lflang
```

602.gcc\_s: basepeak = yes

```
605.mcf_s: -flto -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver2 -mno-sse4a -fstruct-layout=5  
-mllvm -vectorize-memory-aggressively  
-mllvm -function-specialize -mllvm -enable-gvn-hoist  
-mllvm -unroll-threshold=50 -fremap-arrays  
-mllvm -vector-library=LIBMVEC  
-mllvm -reduce-array-computations=3  
-mllvm -global-vectorize-slp -mllvm -inline-threshold=1000  
-flv-function-specialization -DSPEC_OPENMP -fopenmp  
-DUSE_OPENMP -lmvec -lamdlibm -fopenmp=libomp -lomp  
-lpthread -ldl -ljemalloc -lflang
```

625.x264\_s: Same as 600.perlbench\_s

```
657.xz_s: -flto -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver2 -mno-sse4a -fstruct-layout=5  
-mllvm -vectorize-memory-aggressively  
-mllvm -function-specialize -mllvm -enable-gvn-hoist  
-mllvm -unroll-threshold=50 -fremap-arrays  
-mllvm -vector-library=LIBMVEC  
-mllvm -reduce-array-computations=3  
-mllvm -global-vectorize-slp -mllvm -inline-threshold=1000  
-flv-function-specialization -DSPEC_OPENMP -fopenmp  
-DUSE_OPENMP -fopenmp=libomp -lomp -lpthread -ldl  
-lmvec -lamdlibm -ljemalloc -lflang
```

C++ benchmarks:

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECspeed®2017\_int\_base = 8.60

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Peak Optimization Flags (Continued)

620.omnetpp\_s: basepeak = yes

```
623.xalancbmk_s: -m32 -flto -Wl,-mllvm -Wl,-function-specialize
-Wl,-mllvm -Wl,-region-vectorize
-Wl,-mllvm -Wl,-vector-library=LIBMVEC
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast
-march=znver2 -flv-function-specialization
-mllvm -unroll-threshold=100
-mllvm -enable-partial-unswitch
-mllvm -loop-unswitch-threshold=200000
-mllvm -vector-library=LIBMVEC
-mllvm -inline-threshold=1000 -DSPEC_OPENMP -fopenmp
-DUSE_OPENMP -fopenmp=libomp -lomp -lpthread -ldl
-ljemalloc
```

```
631.deepsjeng_s: -flto -Wl,-mllvm -Wl,-function-specialize
-Wl,-mllvm -Wl,-region-vectorize
-Wl,-mllvm -Wl,-vector-library=LIBMVEC
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast
-march=znver2 -flv-function-specialization
-mllvm -unroll-threshold=100
-mllvm -enable-partial-unswitch
-mllvm -loop-unswitch-threshold=200000
-mllvm -vector-library=LIBMVEC
-mllvm -inline-threshold=1000 -DSPEC_OPENMP -fopenmp
-DUSE_OPENMP -fopenmp=libomp -lomp -lpthread -ldl
-lmvec -lamdlibm -ljemalloc -lflang
```

641.leela\_s: basepeak = yes

Fortran benchmarks:

648.exchange2\_s: basepeak = yes

## Peak Other Flags

C benchmarks:

-Wno-return-type

C++ benchmarks (except as noted below):

-Wno-return-type

623.xalancbmk\_s: -Wno-return-type

-L/sppo/dev/cpu2017/v110/amd\_speed\_aocc200\_rome\_C\_lib/32

(Continued on next page)



# SPEC CPU®2017 Integer Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECspeed®2017\_int\_base = 8.60

SPECspeed®2017\_int\_peak = 8.78

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2019

Hardware Availability: Feb-2020

Software Availability: Aug-2019

## Peak Other Flags (Continued)

Fortran benchmarks:

-Wno-return-type

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/aocc200-flags-B1-speed-Dell.html>

<http://www.spec.org/cpu2017/flags/Dell-Platform-Flags-PowerEdge-revE7.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/aocc200-flags-B1-speed-Dell.xml>

<http://www.spec.org/cpu2017/flags/Dell-Platform-Flags-PowerEdge-revE7.xml>

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.0 on 2019-10-26 06:33:45-0400.

Report generated on 2019-12-26 11:31:56 by CPU2017 PDF formatter v6255.

Originally published on 2019-12-24.