



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55


Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2019

Hardware Availability: Feb-2020

Software Availability: Aug-2019



Hardware		Software	
CPU Name:	AMD EPYC 7642	OS:	SUSE Linux Enterprise Server 15 SP1
Max MHz:	3300		kernel 4.12.14-195-default
Nominal:	2300	Compiler:	C/C++/Fortran: Version 2.0.0 of AOCC
Enabled:	96 cores, 2 chips, 2 threads/core	Parallel:	No
Orderable:	1,2 chips	Firmware:	Version 1.0.1 released Sep-2019
Cache L1:	32 KB I + 32 KB D on chip per core	File System:	xfs
L2:	512 KB I+D on chip per core	System State:	Run level 3 (multi-user)
L3:	256 MB I+D on chip per chip, 16 MB shared / 3 cores	Base Pointers:	64-bit
Other:	None	Peak Pointers:	32/64-bit
Memory:	512 GB (16 x 32 GB 2Rx4 PC4-3200AA-R)	Other:	jemalloc: jemalloc memory allocator library v5.2.0
Storage:	1 x 480 GB SAS SSD	Power Management:	BIOS set to prefer performance at the cost of additional power usage.
Other:	None		



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55  
Test Sponsor: Dell Inc.  
Tested by: Dell Inc.

Test Date: Oct-2019  
Hardware Availability: Feb-2020  
Software Availability: Aug-2019

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	192	697	439	699	437	<b>697</b>	<b>438</b>	192	674	454	667	458	<b>670</b>	<b>456</b>		
502.gcc_r	192	624	436	620	438	<b>623</b>	<b>437</b>	192	480	566	477	570	<b>479</b>	<b>568</b>		
505.mcf_r	192	502	618	499	622	<b>500</b>	<b>620</b>	192	391	794	390	796	<b>390</b>	<b>795</b>		
520.omnetpp_r	192	<b>963</b>	<b>262</b>	964	261	962	262	192	<b>963</b>	<b>262</b>	964	261	962	262		
523.xalancbmk_r	192	<b>396</b>	<b>513</b>	394	515	396	511	192	<b>329</b>	<b>616</b>	329	616	330	615		
525.x264_r	192	271	1240	271	1240	<b>271</b>	<b>1240</b>	192	267	1260	<b>266</b>	<b>1270</b>	265	1270		
531.deepsjeng_r	192	<b>414</b>	<b>532</b>	413	532	415	530	192	403	546	410	536	<b>403</b>	<b>545</b>		
541.leela_r	192	606	525	608	523	<b>607</b>	<b>523</b>	192	606	525	608	523	<b>607</b>	<b>523</b>		
548.exchange2_r	192	<b>347</b>	<b>1450</b>	347	1450	353	1430	192	<b>347</b>	<b>1450</b>	347	1450	353	1430		
557.xz_r	192	<b>574</b>	<b>362</b>	572	362	574	361	192	573	362	<b>573</b>	<b>362</b>	574	361		

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Notes

The AMD64 AOCC Compiler Suite is available at  
<http://developer.amd.com/amd-aocc/>

## Submit Notes

The config file option 'submit' was used.  
'numactl' was used to bind copies to the cores.  
See the configuration file for details.

## Operating System Notes

'ulimit -s unlimited' was used to set environment stack size  
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:  
numactl --interleave=all runcpu <etc>

Set dirty\_ratio=8 to limit dirty cache to 8% of memory  
Set swappiness=1 to swap only if necessary  
Set zone\_reclaim\_mode=1 to free local node memory and avoid remote memory sync then drop\_caches=3 to reset caches before invoking runcpu

dirty\_ratio, swappiness, zone\_reclaim\_mode and drop\_caches were all set using privileged echo (e.g. echo 1 > /proc/sys/vm/swappiness).

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECCrate®2017\_int\_base = 557

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECCrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Operating System Notes (Continued)

Transparent huge pages set to 'always' for this run (OS default)

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH =
    "/root/cpu2017-1.0.5/cpu2017-1.1.0/amd_rate_aocc200_rome_C_lib/64;/root/
     cpu2017-1.0.5/cpu2017-1.1.0/amd_rate_aocc200_rome_C_lib/32:"
MALLOC_CONF = "retain:true"
```

## General Notes

Binaries were compiled on a system with 2x AMD EPYC 7601 CPU + 512GB Memory using Fedora 26

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

jemalloc: configured and built with GCC v9.1.0 in Ubuntu 19.04 with -O3 -znver2 -fllto  
jemalloc 5.2.0 is available here:

<https://github.com/jemalloc/jemalloc/releases/download/5.2.0/jemalloc-5.2.0.tar.bz2>

## Platform Notes

BIOS settings:

NUMA Nodes Per Socket set to 4  
CCX as NUMA Domain set to Enabled  
System Profile set to Custom  
CPU Power Management set to Maximum Performance  
Memory Frequency set to Maximum Performance  
Turbo Boost Enabled  
Cstates set to Enabled  
Memory Patrol Scrub Disabled  
Memory Refresh Rate set to 1x  
PCI ASPM L1 Link Power Management Disabled  
Determinism Slider set to Power Determinism  
Efficiency Optimized Mode Disabled  
Memory Interleaving set to Disabled

Sysinfo program /root/cpu2017-1.0.5/cpu2017-1.1.0/bin/sysinfo

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECCrate®2017\_int\_base = 557

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECCrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

Rev: r6365 of 2019-08-21 295195f888a3d7edb1e6e46a485a0011  
running on linux-g3ob Thu Oct 24 12:45:47 2019

SUT (System Under Test) info as seen by some common utilities.  
For more information on this section, see  
<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : AMD EPYC 7642 48-Core Processor
  2 "physical id"s (chips)
  192 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores : 48
  siblings   : 96
  physical 0: cores 0 1 2 4 5 6 8 9 10 12 13 14 16 17 18 20 21 22 24 25 26 28 29 30
              32 33 34 36 37 38 40 41 42 44 45 46 48 49 50 52 53 54 56 57 58 60 61 62
  physical 1: cores 0 1 2 4 5 6 8 9 10 12 13 14 16 17 18 20 21 22 24 25 26 28 29 30
              32 33 34 36 37 38 40 41 42 44 45 46 48 49 50 52 53 54 56 57 58 60 61 62
```

From lscpu:

```
Architecture:           x86_64
CPU op-mode(s):        32-bit, 64-bit
Byte Order:            Little Endian
Address sizes:         43 bits physical, 48 bits virtual
CPU(s):                192
On-line CPU(s) list:  0-191
Thread(s) per core:   2
Core(s) per socket:   48
Socket(s):             2
NUMA node(s):          32
Vendor ID:             AuthenticAMD
CPU family:            23
Model:                 49
Model name:            AMD EPYC 7642 48-Core Processor
Stepping:               0
CPU MHz:                2295.709
BogoMIPS:               4591.41
Virtualization:        AMD-V
L1d cache:              32K
L1i cache:              32K
L2 cache:                512K
L3 cache:                16384K
NUMA node0 CPU(s):     0-2,96-98
NUMA node1 CPU(s):     3-5,99-101
NUMA node2 CPU(s):     6-8,102-104
NUMA node3 CPU(s):     9-11,105-107
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

NUMA node4 CPU(s): 12-14,108-110  
NUMA node5 CPU(s): 15-17,111-113  
NUMA node6 CPU(s): 18-20,114-116  
NUMA node7 CPU(s): 21-23,117-119  
NUMA node8 CPU(s): 24-26,120-122  
NUMA node9 CPU(s): 27-29,123-125  
NUMA node10 CPU(s): 30-32,126-128  
NUMA node11 CPU(s): 33-35,129-131  
NUMA node12 CPU(s): 36-38,132-134  
NUMA node13 CPU(s): 39-41,135-137  
NUMA node14 CPU(s): 42-44,138-140  
NUMA node15 CPU(s): 45-47,141-143  
NUMA node16 CPU(s): 48-50,144-146  
NUMA node17 CPU(s): 51-53,147-149  
NUMA node18 CPU(s): 54-56,150-152  
NUMA node19 CPU(s): 57-59,153-155  
NUMA node20 CPU(s): 60-62,156-158  
NUMA node21 CPU(s): 63-65,159-161  
NUMA node22 CPU(s): 66-68,162-164  
NUMA node23 CPU(s): 69-71,165-167  
NUMA node24 CPU(s): 72-74,168-170  
NUMA node25 CPU(s): 75-77,171-173  
NUMA node26 CPU(s): 78-80,174-176  
NUMA node27 CPU(s): 81-83,177-179  
NUMA node28 CPU(s): 84-86,180-182  
NUMA node29 CPU(s): 87-89,183-185  
NUMA node30 CPU(s): 90-92,186-188  
NUMA node31 CPU(s): 93-95,189-191

Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mttr pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr\_opt pdpe1gb rdtscp lm constant\_tsc rep\_good nopl xtTopology nonstop\_tsc cpuid extd\_apicid aperfmpfperf pnpi pclmulqdq monitor ssse3 fma cx16 sse4\_1 sse4\_2 x2apic movbe popcnt aes xsave avx f16c rdrand lahf\_lm cmp\_legacy svm extapic cr8\_legacy abm sse4a misalignsse 3dnowprefetch csvw ibs skinit wdt tce topoext perfctr\_core perfctr\_nb bpext perfctr\_12 mwaitx cpb cat\_13 cdp\_13 hw\_pstate sme ssbd sev ibrs ibpb stibp vmmcall fsgsbase bmi1 avx2 smep bmi2 cqmq rdt\_a rdseed adx smap clflushopt clwb sha\_ni xsaveopt xsavec xgetbv1 xsaves cqmq\_llc cqmq\_occup\_llc cqmq\_mbm\_total cqmq\_mbm\_local clzero irperf xsaveerptr arat npt lbrv svm\_lock nrrip\_save tsc\_scale vmcb\_clean flushbyasid decodeassists pausefilter pfthreshold avic v\_vmsave\_vmload vgif umip rdpid overflow\_recov succor smca

/proc/cpuinfo cache data  
cache size : 512 KB

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

available: 32 nodes (0-31)

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECCrate®2017\_int\_base = 557

SPECCrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
node 0 cpus: 0 1 2 96 97 98
node 0 size: 15676 MB
node 0 free: 15572 MB
node 1 cpus: 3 4 5 99 100 101
node 1 size: 16126 MB
node 1 free: 16036 MB
node 2 cpus: 6 7 8 102 103 104
node 2 size: 16126 MB
node 2 free: 16030 MB
node 3 cpus: 9 10 11 105 106 107
node 3 size: 16125 MB
node 3 free: 16050 MB
node 4 cpus: 12 13 14 108 109 110
node 4 size: 16126 MB
node 4 free: 16031 MB
node 5 cpus: 15 16 17 111 112 113
node 5 size: 16126 MB
node 5 free: 15998 MB
node 6 cpus: 18 19 20 114 115 116
node 6 size: 16126 MB
node 6 free: 15747 MB
node 7 cpus: 21 22 23 117 118 119
node 7 size: 16125 MB
node 7 free: 16024 MB
node 8 cpus: 24 25 26 120 121 122
node 8 size: 16126 MB
node 8 free: 16061 MB
node 9 cpus: 27 28 29 123 124 125
node 9 size: 16126 MB
node 9 free: 16063 MB
node 10 cpus: 30 31 32 126 127 128
node 10 size: 16126 MB
node 10 free: 16063 MB
node 11 cpus: 33 34 35 129 130 131
node 11 size: 16125 MB
node 11 free: 16055 MB
node 12 cpus: 36 37 38 132 133 134
node 12 size: 16126 MB
node 12 free: 16055 MB
node 13 cpus: 39 40 41 135 136 137
node 13 size: 16126 MB
node 13 free: 16060 MB
node 14 cpus: 42 43 44 138 139 140
node 14 size: 16126 MB
node 14 free: 16068 MB
node 15 cpus: 45 46 47 141 142 143
node 15 size: 16113 MB
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECCrate®2017\_int\_base = 557

SPECCrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
node 15 free: 16053 MB
node 16 cpus: 48 49 50 144 145 146
node 16 size: 16126 MB
node 16 free: 16076 MB
node 17 cpus: 51 52 53 147 148 149
node 17 size: 16126 MB
node 17 free: 16079 MB
node 18 cpus: 54 55 56 150 151 152
node 18 size: 16126 MB
node 18 free: 16081 MB
node 19 cpus: 57 58 59 153 154 155
node 19 size: 16096 MB
node 19 free: 16051 MB
node 20 cpus: 60 61 62 156 157 158
node 20 size: 16126 MB
node 20 free: 16082 MB
node 21 cpus: 63 64 65 159 160 161
node 21 size: 16126 MB
node 21 free: 16079 MB
node 22 cpus: 66 67 68 162 163 164
node 22 size: 16126 MB
node 22 free: 16077 MB
node 23 cpus: 69 70 71 165 166 167
node 23 size: 16125 MB
node 23 free: 16075 MB
node 24 cpus: 72 73 74 168 169 170
node 24 size: 16126 MB
node 24 free: 16032 MB
node 25 cpus: 75 76 77 171 172 173
node 25 size: 16126 MB
node 25 free: 16073 MB
node 26 cpus: 78 79 80 174 175 176
node 26 size: 16126 MB
node 26 free: 16069 MB
node 27 cpus: 81 82 83 177 178 179
node 27 size: 16125 MB
node 27 free: 16071 MB
node 28 cpus: 84 85 86 180 181 182
node 28 size: 16126 MB
node 28 free: 16076 MB
node 29 cpus: 87 88 89 183 184 185
node 29 size: 16126 MB
node 29 free: 16081 MB
node 30 cpus: 90 91 92 186 187 188
node 30 size: 16126 MB
node 30 free: 16075 MB
node 31 cpus: 93 94 95 189 190 191
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

```
node 31 size: 16124 MB
node 31 free: 16073 MB
node distances:
node  0   1   2   3   4   5   6   7   8   9   10  11  12  13  14  15  16  17  18  19
20  21  22  23  24  25  26  27  28  29  30  31
 0: 10  11  11  11  12  12  12  12  12  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 1: 11  10  11  11  12  12  12  12  12  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 2: 11  11  10  11  12  12  12  12  12  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 3: 11  11  11  10  12  12  12  12  12  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 4: 12  12  12  12  10  11  11  11  11  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 5: 12  12  12  12  12  11  10  11  11  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 6: 12  12  12  12  11  11  10  11  11  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 7: 12  12  12  12  11  11  11  10  12  12  12  12  12  12  12  12  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 8: 12  12  12  12  12  12  12  12  12  10  11  11  11  11  11  11  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
 9: 12  12  12  12  12  12  12  12  12  11  10  11  10  11  11  11  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
10: 12  12  12  12  12  12  12  12  12  12  12  11  11  10  10  11  11  12  12
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
11: 12  12  12  12  12  12  12  12  12  12  12  11  11  11  11  10  10  12  12
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
12: 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  10  11
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
13: 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  11  10
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
14: 12  12  12  12  12  12  12  12  12  12  12  32  32  32  32  32  32  32  32
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
15: 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  10
 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32
16: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  10
 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  11  11
17: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  11
 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  11  10  11
18: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  11
 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  11  11  10
19: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  11
 12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12  11  11  10
20: 32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  32  12
 10  11  11  11  12  12  12  12  12  12  12  12  12  12  12  12  12  12  12
```

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

## SPECrate®2017\_int\_base = 557

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

**Test Date:** Oct-2019

**Test Sponsor:** Dell Inc.

## **Hardware Availability:** Feb-2020

**Tested by:** Dell Inc.

### **Software Availability:** Aug-2019

## **Platform Notes (Continued)**

21:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
11:	10	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
22:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12
11:	11	10	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
23:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
11:	11	11	10	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
24:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	10	11	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12
25:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	11	10	11	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12
26:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	11	11	10	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12
27:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	11	11	11	10	12	12	12	12	12	12	12	12	12	12	12	12	12	12
28:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	12	12	12	12	12	10	11	11	11	11	11	11	11	11	12	12	12	12
29:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	12	12	12	12	12	11	10	11	11	11	11	11	11	11	12	12	12	12
30:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	12	12	12	12	12	11	11	11	10	11	11	11	11	11	12	12	12	12
31:	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	12	12	12	12
12:	12	12	12	12	12	12	12	12	12	11	11	11	11	10	10	11	11	11	12	12	12	12

From /proc/meminfo

```
MemTotal:      527927004 kB  
HugePages_Total:      0  
Hugepagesize:     2048 kB
```

From /etc/\*release\* /etc/\*version\*

```
os-release:  
  NAME="SLES"  
  VERSION="15-SP1"  
  VERSION_ID="15.1"  
  PRETTY_NAME="SUSE Linux Enterprise Server 15 SP1"  
  ID="sles"  
  ID_LIKE="suse"  
  ANSI_COLOR="0;32"  
  CPE_NAME="cpe:/o:suse:sles:15:sp1"
```

```
uname -a:
```

Linux linux-g3ob 4.12.14-195-default #1 SMP Tue May 7 10:55:11 UTC 2019 (8fba516)  
x86\_64 x86\_64 x86\_64 GNU/Linux

## Kernel self-reported vulnerability status:

CVE-2018-3620 (L1 Terminal Fault): Not affected  
Microarchitectural Data Sampling: Not affected

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECCrate®2017\_int\_base = 557

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECCrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Platform Notes (Continued)

CVE-2017-5754 (Meltdown): Not affected

CVE-2018-3639 (Speculative Store Bypass): Mitigation: Speculative Store Bypass disabled via prctl and seccomp

CVE-2017-5753 (Spectre variant 1): Mitigation: \_\_user pointer sanitization

CVE-2017-5715 (Spectre variant 2): Mitigation: Full AMD retrpoline, IBPB: conditional, IBRS\_FW, STIBP: conditional, RSB filling

run-level 3 Oct 24 12:29

SPEC is set to: /root/cpu2017-1.0.5/cpu2017-1.1.0

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/sda2	xfs	440G	32G	409G	8%	/

From /sys/devices/virtual/dmi/id  
BIOS: Dell Inc. 1.0.1 09/21/2019  
Vendor: Dell Inc.  
Product: PowerEdge C6525  
Product Family: PowerEdge

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

4x	802C80B3802C	36ASF4G72PZ-3G2E2	32 GB	2 rank	3200
4x	802C869D802C	36ASF4G72PZ-3G2E2	32 GB	2 rank	3200
8x	80AD863280AD	HMA84GR7CJR4N-XN	32 GB	2 rank	3200

(End of data from sysinfo program)

## Compiler Version Notes

=====

C	502.gcc_r(peak)
---	-----------------

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C	500.perlbench_r(base, peak) 502.gcc_r(base) 505.mcf_r(base, peak)   525.x264_r(base, peak) 557.xz_r(base, peak)
---	--

=====

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017\_int\_base = 557

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Compiler Version Notes (Continued)

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C | 502.gcc\_r(peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C | 500.perlbench\_r(base, peak) 502.gcc\_r(base) 505.mcf\_r(base, peak)  
| 525.x264\_r(base, peak) 557.xz\_r(base, peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C++ | 523.xalancbmk\_r(peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C++ | 520.omnetpp\_r(base, peak) 523.xalancbmk\_r(base)  
| 531.deepsjeng\_r(base, peak) 541.leela\_r(base, peak)

=====

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Compiler Version Notes (Continued)

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C++ | 523.xalancbmk\_r(peak)

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: i386-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

C++ | 520.omnetpp\_r(base, peak) 523.xalancbmk\_r(base)  
| 531.deepsjeng\_r(base, peak) 541.leela\_r(base, peak)

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

=====

Fortran | 548.exchange2\_r(base, peak)

AOCC.LLVM.2.0.0.B191.2019\_07\_19 clang version 8.0.0 (CLANG: Jenkins  
AOCC\_2\_0\_0-Build#191) (based on LLVM AOCC.LLVM.2.0.0.B191.2019\_07\_19)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /sppo/dev/compilers/aocc-compiler-2.0.0/bin

## Base Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Fortran benchmarks:

flang



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2019

Hardware Availability: Feb-2020

Software Availability: Aug-2019

## Base Portability Flags

```
500.perlbench_r: -DSPEC_LINUX_X64 -DSPEC_LP64
502.gcc_r: -DSPEC_LP64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LINUX -DSPEC_LP64
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64
```

## Base Optimization Flags

C benchmarks:

```
-flicht -Wl,-mllvm -Wl,-function-specialize
-Wl,-mllvm -Wl,-region-vectorize -Wl,-mllvm -Wl,-vector-library=LIBMVEC
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -ffast-math
-march=znver2 -fstruct-layout=3 -mllvm -unroll-threshold=50
-freemap-arrays -mllvm -function-specialize -mllvm -enable-gvn-hoist
-mllvm -reduce-array-computations=3 -mllvm -global-vectorize-slp
-mllvm -vector-library=LIBMVEC -mllvm -inline-threshold=1000
-flv-function-specialization -z muldefs -lmvec -lamdlibm -ljemalloc
-lflang
```

C++ benchmarks:

```
-flicht -Wl,-mllvm -Wl,-function-specialize
-Wl,-mllvm -Wl,-region-vectorize -Wl,-mllvm -Wl,-vector-library=LIBMVEC
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-suppress-fmas -O3 -ffast-math -march=znver2
-mllvm -loop-unswitch-threshold=200000 -mllvm -vector-library=LIBMVEC
-mllvm -unroll-threshold=100 -flv-function-specialization
-mllvm -enable-partial-unswitch -z muldefs -lmvec -lamdlibm
-ljemalloc -lflang
```

Fortran benchmarks:

```
-flicht -Wl,-mllvm -Wl,-function-specialize
-Wl,-mllvm -Wl,-region-vectorize -Wl,-mllvm -Wl,-vector-library=LIBMVEC
-Wl,-mllvm -Wl,-reduce-array-computations=3 -ffast-math
-Wl,-mllvm -Wl,-inline-recursion=4 -Wl,-mllvm -Wl,-lsr-in-nested-loop
-Wl,-mllvm -Wl,-enable-iv-split -O3 -march=znver2 -funroll-loops
-Mrecursive -mllvm -vector-library=LIBMVEC -z muldefs
-mllvm -disable-indvar-simplify -mllvm -unroll-aggressive
-mllvm -unroll-threshold=150 -lmvec -lamdlibm -ljemalloc -lflang
```



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

<p><b>Dell Inc.</b></p> <p>PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)</p>	<p>SPECrate®2017_int_base = 557</p> <p><b>SPECrate®2017_int_peak = 602</b></p>
<p><b>CPU2017 License:</b> 55</p> <p><b>Test Sponsor:</b> Dell Inc.</p> <p><b>Tested by:</b> Dell Inc.</p>	<p><b>Test Date:</b> Oct-2019</p> <p><b>Hardware Availability:</b> Feb-2020</p> <p><b>Software Availability:</b> Aug-2019</p>

# Peak Compiler Invocation

### C benchmarks:

clang

## C++ benchmarks:

| clang++

## Fortran benchmarks:

Flang

## Peak Portability Flags

```
500.perlbench_r: -DSPEC_LINUX_X64 -DSPEC_LP64
502.gcc_r: -D_FILE_OFFSET_BITS=64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LINUX -D_FILE_OFFSET_BITS=64
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64
```

## Peak Optimization Flags

C benchmarks:

**(Continued on next page)**



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

SPECCrate®2017\_int\_base = 557

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECCrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Date: Oct-2019

Test Sponsor: Dell Inc.

Hardware Availability: Feb-2020

Tested by: Dell Inc.

Software Availability: Aug-2019

## Peak Optimization Flags (Continued)

502.gcc\_r: -m32 -flto -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver2 -mno-sse4a -fstruct-layout=5  
-mllvm -vectorize-memory-aggressively  
-mllvm -function-specialize -mllvm -enable-gvn-hoist  
-mllvm -unroll-threshold=50 -fremap-arrays  
-mllvm -vector-library=LIBMVEC  
-mllvm -reduce-array-computations=3  
-mllvm -global-vectorize-slp -mllvm -inline-threshold=1000  
-flv-function-specialization -fgnu89-inline -ljemalloc

505.mcf\_r: -flto -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver2 -mno-sse4a -fstruct-layout=5  
-mllvm -vectorize-memory-aggressively  
-mllvm -function-specialize -mllvm -enable-gvn-hoist  
-mllvm -unroll-threshold=50 -fremap-arrays  
-mllvm -vector-library=LIBMVEC  
-mllvm -reduce-array-computations=3  
-mllvm -global-vectorize-slp -mllvm -inline-threshold=1000  
-flv-function-specialization -lmvec -lamdlibm -ljemalloc  
-lflang

525.x264\_r: Same as 500.perlbench\_r

557.xz\_r: Same as 505.mcf\_r

C++ benchmarks:

520.omnetpp\_r: basepeak = yes

523.xalancbmk\_r: -m32 -flto -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver2 -flv-function-specialization  
-mllvm -unroll-threshold=100  
-mllvm -enable-partial-unswitch  
-mllvm -loop-unswitch-threshold=200000  
-mllvm -vector-library=LIBMVEC  
-mllvm -inline-threshold=1000 -ljemalloc

(Continued on next page)



# SPEC CPU®2017 Integer Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6525 (AMD EPYC 7642, 2.30 GHz)

SPECrate®2017\_int\_base = 557

SPECrate®2017\_int\_peak = 602

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2019

Hardware Availability: Feb-2020

Software Availability: Aug-2019

## Peak Optimization Flags (Continued)

```
531.deepsjeng_r: -floop -Wl,-mllvm -Wl,-function-specialize  
-Wl,-mllvm -Wl,-region-vectorize  
-Wl,-mllvm -Wl,-vector-library=LIBMVEC  
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast  
-march=znver2 -flv-function-specialization  
-mllvm -unroll-threshold=100  
-mllvm -enable-partial-unswitch  
-mllvm -loop-unswitch-threshold=200000  
-mllvm -vector-library=LIBMVEC  
-mllvm -inline-threshold=1000 -lmvec -lamdlibm -ljemalloc  
-lflang
```

```
541.leela_r: basepeak = yes
```

Fortran benchmarks:

```
548.exchange2_r: basepeak = yes
```

## Peak Other Flags

C benchmarks:

```
502.gcc_r: -L/sppo/dev/cpu2017/v110/amd_rate_aocc200_rome_C_lib/32
```

C++ benchmarks:

```
523.xalancbmk_r: -L/sppo/dev/cpu2017/v110/amd_rate_aocc200_rome_C_lib/32
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/aocc200-flags-B1-speed-Dell.html>

<http://www.spec.org/cpu2017/flags/Dell-Platform-Flags-PowerEdge-revE7.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/aocc200-flags-B1-speed-Dell.xml>

<http://www.spec.org/cpu2017/flags/Dell-Platform-Flags-PowerEdge-revE7.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.0 on 2019-10-24 12:45:47-0400.

Report generated on 2019-12-26 11:31:47 by CPU2017 PDF formatter v6255.

Originally published on 2019-12-24.