



SPEChpc™ 2021 Small Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion


SPEChpc 2021_sml_base = 0.6174

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_sml_peak = 0.6510

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021



Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	OMP	16	10	2529	0.613	2537	0.611			OMP	16	10	2529	0.613	2537	0.611		
613.soma_s	OMP	16	10	1279	1.25	1289	1.24			OMP	2	80	1223	1.31	1218	1.31		
618.tealeaf_s	OMP	16	10	7251	0.283	7193	0.285			OMP	16	10	7251	0.283	7193	0.285		
619.civleaf_s	OMP	16	10	5608	0.294	5610	0.294			OMP	16	10	4897	0.337	4897	0.337		
621.miniswp_s	OMP	16	10	532	2.07	533	2.06			OMP	4	40	481	2.29	481	2.29		
628.pot3d_s	OMP	16	10	5947	0.282	5943	0.282			OMP	40	4	6046	0.277	6039	0.277		
632.sph_exa_s	OMP	16	10	1314	1.75	1314	1.75			OMP	40	4	1305	1.76	1304	1.76		
634.hpgmgfv_s	OMP	16	10	2805	0.348	2831	0.344			OMP	8	20	2804	0.348	2779	0.351		
635.weather_s	OMP	16	10	4406	0.590	4391	0.592			OMP	40	4	3657	0.711	3651	0.712		

SPEChpc 2021_sml_base = 0.6174

SPEChpc 2021_sml_peak = 0.6510

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Small Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_sml_base = 0.6174

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_sml_peak = 0.6510

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021

Hardware Summary

Type of System: SMP
Compute Node: Fusionserver 2288H V6
Interconnect: None
Compute Nodes Used: 1
Total Chips: 2
Total Cores: 80
Total Threads: 160
Total Memory: 1 TB
Max. Peak Threads: 80

Software Summary

Compiler: Intel oneAPI Compiler 2021.4.0
MPI Library: Intel MPI Library for Linux* OS, Version 2021.4.0 Build 20210831
Other MPI Info: --
Other Software: --
Base Parallel Model: OMP
Base Ranks Run: 16
Base Threads Run: 10
Peak Parallel Models: OMP
Minimum Peak Ranks: 2
Maximum Peak Ranks: 40
Max. Peak Threads: 80
Min. Peak Threads: 4

Node Description: Fusionserver 2288H V6

Hardware

Number of nodes: 1
Uses of the node: Compute
Vendor: xFusion
Model: FusionServer 2288H V6
CPU Name: Intel Xeon Platinum 8380
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 80
Cores per chip: 40
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.4 GHz
CPU MHz: 2300
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 1.25 MB I+D on chip per core
L3 Cache: 60 MB I+D on chip per chip
Other Cache: None
Memory: 1 TB (16 x 64 GB 2Rx4 PC4-3200R)
Disk Subsystem: 2 x 480 GB SATA 2.5" SSD (RAID 1)
Other Hardware: None
Accel Count: None
Accel Model: --
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: MCX653105A-EFAT
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 100 Gb/s
Ports Used: 1

Software

Accelerator Driver: --
Adapter: MCX653105A-EFAT
Adapter Driver: 5.4-3.1.0
Adapter Firmware: 20.32.1010
Operating System: CentOS Linux release 8.2.2004
4.18.0-193.el8.x86_644
Local File System: xfs
Shared File System: NFS
System State: Multi-user, run level 3
Other Software: None

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_sml_base = 0.6174

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_sml_peak = 0.6510

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021

Node Description: Fusionserver 2288H V6

Hardware (Continued)

Interconnect Type: Mellanox HDR

Interconnect Description: None

Hardware

Vendor: None
Model: None
Switch Model: None
Number of Switches: 0
Number of Ports: 0
Data Rate: None
Firmware: None
Topology: None
Primary Use: None

Software

: --

Submit Notes

The config file option 'submit' was used.

```
export LD_PRELOAD="/usr/lib64/libhugetlbfs.so $LD_PRELOAD"
```

```
export OMP_PROC_BIND=true
```

```
mpiexec.hydra -bootstrap ssh -hostfile ${top}/lnode --bind-to core -np $ranks -ppn $ppn -genv OMP_NUM_THREADS=$threads $command
```

Compiler Version Notes

```
=====  
CC 605.lbm_s(base, peak) 613.soma_s(base, peak) 618.tealeaf_s(base, peak)  
621.miniswp_s(base, peak) 634.hpgmgfv_s(base, peak)  
=====
```

```
Intel(R) oneAPI DPC++/C++ Compiler 2021.4.0 (2021.4.0.20210924)  
Target: x86_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /home/opt/compiler/oneapi/2021.4.0/compiler/2021.4.0/linux/bin  
=====
```

```
=====  
CXXC 632.sph_exa_s(base, peak)  
=====
```

```
Intel(R) oneAPI DPC++/C++ Compiler 2021.4.0 (2021.4.0.20210924)  
Target: x86_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /home/opt/compiler/oneapi/2021.4.0/compiler/2021.4.0/linux/bin  
=====
```

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_sml_base = 0.6174

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_sml_peak = 0.6510

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021

Compiler Version Notes (Continued)

```

=====
FC 619.clvleaf_s(base, peak) 628.pot3d_s(base, peak) 635.weather_s(base,
  peak)
=====
ifx (IFORT) 2021.4.0 Beta 20210924
Copyright (C) 1985-2021 Intel Corporation. All rights reserved.
=====

```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx -lstdc++(*)`

C++ benchmarks:
`mpiicpc -cxx=icx -lstdc++(*)`

Fortran benchmarks:
`mpiifort -fc=ifx -lstdc++(*)`

(*) Indicates a compiler flag that was found in a non-compiler variable.

Base Portability Flags

613.soma_s: -DSPEC_NO_VAR_ARRAY_REDUCE

Base Optimization Flags

C benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -ansi-alias`

C++ benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -ansi-alias`

Fortran benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -nostandard-realloc-lhs -align array64byte`



SPEChpc™ 2021 Small Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_sml_base = 0.6174

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_sml_peak = 0.6510

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021

Peak Compiler Invocation

C benchmarks:

```
mpiicc -cc=icx -lstdc++(*)
```

C++ benchmarks:

```
mpiicpc -cxx=icx -lstdc++(*)
```

Fortran benchmarks:

```
mpiifort -fc=ifx -lstdc++(*)
```

(*) Indicates a compiler flag that was found in a non-compiler variable.

Peak Portability Flags

```
613.soma_s: -DSPEC_NO_VAR_ARRAY_REDUCE
```

Peak Optimization Flags

C benchmarks:

```
605.lbm_s: basepeak = yes
```

```
613.soma_s: -Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512  
-fiopenmp -ansi-alias
```

```
618.tealeaf_s: basepeak = yes
```

```
621.miniswp_s: Same as 613.soma_s
```

```
634.hpgmgfv_s: -Ofast -ipo -xCORE-AVX512  
-mllvm -hir-nontemporal-cacheline-count=0 -fiopenmp  
-ansi-alias
```

C++ benchmarks:

```
-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -ffast-math  
-fiopenmp -ansi-alias
```

Fortran benchmarks:

```
619.clvleaf_s: -Ofast -ipo -xCORE-AVX512  
-mllvm -hir-nontemporal-cacheline-count=0 -fiopenmp  
-nonstandard-realloc-lhs -align array64byte
```

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_sml_base = 0.6174

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_sml_peak = 0.6510

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021

Peak Optimization Flags (Continued)

628.pot3d_s: -Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512
-fiopenmp -nostandard-realloc-lhs -align array64byte

635.weather_s: Same as 619.clvleaf_s

The flags file that was used to format this result can be browsed at

<http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.xml>

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.0.3 on 2022-07-27 02:13:21-0400.
Report generated on 2022-08-24 18:40:59 by hpc2021 PDF formatter v1.0.3.
Originally published on 2022-08-24.