



SPEC® OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)

SPECompG_peak2012 = 134

Superdome Flex (Intel Xeon Gold 6154, 3.00 GHz)

SPECompG_base2012 = 128

OMP2012 license:1


Test sponsor: HPE

Tested by: HPE

Test date: Dec-2017

Hardware Availability: Mar-2018

Software Availability: Mar-2018



Hardware		Software
CPU Name:	Intel Xeon Gold 6154	Operating System: SUSE Linux Enterprise Server 12 SP2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.70 GHz	Kernel 4.4.74-92.38-default
CPU MHz:	3000	Compiler: C/C++/Fortran: Version 18.0.0.128 of Intel Composer XE for Linux, Build 20170811
CPU MHz Maximum:	3700	Auto Parallel: No
FPU:	Integrated	File System: tmpfs
CPU(s) enabled:	576 cores, 32 chips, 18 cores/chip	System State: Multi-user, run level 3
CPU(s) orderable:	4-32 chips	Base Pointers: 64-bit
Primary Cache:	32 KB I + 32 KB D on chip per core	Peak Pointers: 64-bit
Secondary Cache:	1 MB I+D on chip per core	Other Software: HPE Foundation Software 1.0, Build 717a270.sles12sp2-1709012000
L3 Cache:	24.75 MB I+D on chip per chip	
Other Cache:	None	
Memory:	12 TB (384 x 32 GB 2Rx4 PC4-2666V-R)	
Disk Subsystem:	tmpfs	
Other Hardware:	None	
Base Threads Run:	513	
Minimum Peak Threads:	512	

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

SPECompG_peak2012 = 134

Superdome Flex (Intel Xeon Gold 6154, 3.00 GHz)

SPECompG_base2012 = 128

OMP2012 license:1

Test sponsor: HPE

Tested by: HPE

Test date: Dec-2017

Hardware Availability: Mar-2018

Software Availability: Mar-2018

Maximum Peak Threads: 576

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	513	5.65	819	<u>5.60</u>	<u>827</u>	5.59	828	576	<u>5.33</u>	<u>869</u>	5.52	839	<u>5.31</u>	872
351.bwaves	513	26.9	168	<u>26.9</u>	<u>168</u>	27.0	168	517	27.1	167	<u>26.9</u>	<u>168</u>	26.9	169
352.nab	513	69.2	56.2	<u>69.2</u>	<u>56.2</u>	69.2	56.2	513	69.2	56.2	<u>69.2</u>	<u>56.2</u>	69.2	56.2
357.bt331	513	<u>47.7</u>	<u>99.3</u>	47.8	99.3	47.7	99.4	531	47.5	99.7	48.0	98.8	<u>47.6</u>	<u>99.7</u>
358.botsalgn	513	29.5	147	29.5	148	<u>29.5</u>	<u>147</u>	576	26.7	163	<u>26.7</u>	<u>163</u>	26.7	163
359.botsspar	513	69.1	76.0	<u>70.0</u>	<u>75.0</u>	70.1	74.9	513	69.1	76.0	<u>70.0</u>	<u>75.0</u>	70.1	74.9
360.ilbdc	513	<u>36.6</u>	<u>97.3</u>	36.5	97.5	36.6	97.3	576	33.9	105	33.8	105	<u>33.8</u>	<u>105</u>
362.fma3d	513	78.8	48.2	78.7	48.3	<u>78.8</u>	<u>48.2</u>	567	<u>73.7</u>	<u>51.6</u>	73.8	51.5	73.6	51.6
363.swim	513	<u>28.4</u>	<u>160</u>	28.4	159	28.3	160	567	26.6	170	26.4	171	<u>26.5</u>	<u>171</u>
367.imagick	513	54.4	129	55.3	127	<u>54.9</u>	<u>128</u>	576	54.1	130	<u>54.0</u>	<u>130</u>	53.6	131
370.mgrid331	513	34.0	130	<u>34.1</u>	<u>130</u>	34.1	130	512	30.1	147	30.2	146	<u>30.2</u>	<u>146</u>
371.applu331	513	84.4	71.8	85.1	71.2	<u>84.8</u>	<u>71.4</u>	513	84.4	71.8	85.1	71.2	<u>84.8</u>	<u>71.4</u>
372.smithwa	513	14.1	381	<u>14.1</u>	<u>380</u>	16.0	334	576	<u>12.8</u>	<u>418</u>	12.9	417	12.8	419
376.kdtree	513	<u>40.8</u>	<u>110</u>	40.4	111	41.1	109	576	38.2	118	<u>38.1</u>	<u>118</u>	38.0	118

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
COPTIMIZE=-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp -ansi-alias -mcmodel=medium -shared-intel
CXXOPTIMIZE=-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp -ansi-alias -mcmodel=medium -shared-intel
FOPTIMIZE=-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp -mcmodel=medium -shared-intel
```

Submit Notes

The config file option 'submit' was used.

For all benchmarks threads were bound to cores using the following submit command:

```
dplace $command
```

This binds threads in order of creation, beginning with the master thread on logical cpu 0, the first slave thread on logical cpu 1, and so on.

Operating System Notes

Transparent Hugepages :

```
Transparent Hugepages are disabled by
echo never > /sys/kernel/mm/transparent_hugepage/enabled
```

Software Environment:

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)

SPECompG_peak2012 = 134

Superdome Flex (Intel Xeon Gold 6154, 3.00 GHz)

SPECompG_base2012 = 128

OMP2012 license:1

Test date: Dec-2017

Test sponsor: HPE

Hardware Availability: Mar-2018

Tested by: HPE

Software Availability: Mar-2018

Operating System Notes (Continued)

```
export KMP_AFFINITY=disabled
export KMP_STACKSIZE=200M
export KMP_SCHEDULE=static,balanced
export OMP_DYNAMIC=FALSE
ulimit -s unlimited
```

The tmpfs filesystem was set up with:
mount -t tmpfs -o rw,remount,mode=1777,mpol=interleave tmpfs /dev/shm

Platform Notes

Rack Management Controller settings:
modify npar pnum=0 ras=hpc
modify npar pnum=0 hthread=off

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Base Portability Flags

350.md: -free
367.imagick: -std=c99

Base Optimization Flags

C benchmarks:
-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp -ansi-alias
-mcmodel=medium -shared-intel

C++ benchmarks:
-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp -ansi-alias
-mcmodel=medium -shared-intel

Fortran benchmarks:
-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp
-mcmodel=medium -shared-intel



SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)

SPECompG_peak2012 = 134

Superdome Flex (Intel Xeon Gold 6154, 3.00 GHz)

SPECompG_base2012 = 128

OMP2012 license:1

Test date: Dec-2017

Test sponsor: HPE

Hardware Availability: Mar-2018

Tested by: HPE

Software Availability: Mar-2018

Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Peak Portability Flags

350.md: -free
367.imagick: -std=c99

Peak Optimization Flags

C benchmarks:

352.nab: basepeak = yes
358.botsalgn: -O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp
-ansi-alias -mcmodel=medium -shared-intel

359.botsspar: basepeak = yes

367.imagick: Same as 358.botsalgn

372.smithwa: Same as 358.botsalgn

C++ benchmarks:

-O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp -ansi-alias
-mcmodel=medium -shared-intel

Fortran benchmarks:

350.md: -O3 -qopt-zmm-usage=high -xCORE-AVX512 -ipol -qopenmp
-mcmodel=medium -shared-intel

351.bwaves: Same as 350.md

357.bt331: Same as 350.md

360.ilbdc: Same as 350.md

362.fma3d: Same as 350.md

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)

SPECompG_peak2012 = 134

Superdome Flex (Intel Xeon Gold 6154, 3.00 GHz)

SPECompG_base2012 = 128

OMP2012 license:1

Test date: Dec-2017

Test sponsor: HPE

Hardware Availability: Mar-2018

Tested by: HPE

Software Availability: Mar-2018

Peak Optimization Flags (Continued)

363.swim: Same as 350.md

370.mgrid331: Same as 350.md

371.applu331: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/HPE-OMP2012-ic18.html>

http://www.spec.org/omp2012/flags/HPE-Superdome_Flex-RevA.html

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/omp2012/flags/HPE-OMP2012-ic18.xml>

http://www.spec.org/omp2012/flags/HPE-Superdome_Flex-RevA.xml

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v25.

Report generated on Wed Jan 3 13:04:57 2018 by SPEC OMP2012 PS/PDF formatter v541.

Originally published on 3 January 2018.