



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
**SGI 2200 2X 400MHz R12k**

SPECint\_rate2000 = **7.79**  
SPECint\_rate\_base2000 = **7.27**

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	627	5.18	2	605	5.36
175.vpr	2	369	8.79	2	362	8.98
176.gcc	2	353	7.23	2	353	7.22
181.mcf	2	371	11.2	2	373	11.2
186.crafty	2	303	7.65	2	301	7.72
197.parser	2	646	6.47	2	608	6.87
252.eon	2	361	8.35	2	365	8.26
253.perlbnk	2	734	5.69	2	733	5.70
254.gap	2	562	4.54	2	553	4.62
255.vortex	2	649	6.80	2	357	12.3
256.bzip2	2	451	7.72	2	407	8.56
300.twolf	2	666	10.4	2	666	10.5

### Hardware

CPU: R12000  
CPU MHz: 400  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
CPU(s) orderable: 2, 4, 6, 8  
Parallel: No  
Primary Cache: 32KBI + 32KBD on chip  
Secondary Cache: 8MB(I+D) off chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 2048MB  
Disk Subsystem: 2 x 18 GB SCSI (striped)  
Other Hardware: None

### Software

Operating System: IRIX 6.5.8f  
Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90  
File System: xfs  
System State: Single-user

## Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)  
PASS2 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -DUSG -Dalloca=\_\_builtin\_alloca -DMIPS -DHOST\_WORDS\_BIG\_ENDIAN  
186.crafty: -DSGI  
253.perlbnk: -DSPEC\_CPU2000\_SGI -DI\_FCNTL  
254.gap: -DSYS\_IS\_USG -DSYS\_HAS\_TIME\_PROTO -DSYS\_HAS\_SIGNAL\_PROTO -DSYS\_HAS\_IOCTL\_PROTO  
300.twolf: -DHAVE\_SIGNED\_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb\_create /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
PASS2 = -fb\_opt /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)  
175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee\_limit=5000:linear=on -LNO:prefetch Ahead=2  
-INLINE:aggressive=on -OPT:Olimit=0:alias=disjoint:alias=restrict -lmalloc (FEEDBACK)  
181.mcf: -Ofast=ip27 -IPA:min\_hot=14 -lmalloc (FEEDBACK)  
176.gcc: -Ofast=ip27 (FEEDBACK)  
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -lmalloc (FEEDBACK)  
197.parser: -Ofast=ip27 -IPA:min\_hot=14 (FEEDBACK)



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
**SGI 2200 2X 400MHz R12k**

**SPECint\_rate2000 = 7.79**  
**SPECint\_rate\_base2000 = 7.27**

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

## Notes/Tuning Information (Continued)

```

252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -lmalloc (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
. -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0
. -CG:ld_latency=5 -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: -Ofast=ip27 -IPA:use_intrinsic (FEEDBACK)

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096
setenv PAGESIZE_TEXT 4096
setenv PAGESIZE_STACK 4096
systune -i ; percent_totalmem_4m_pages = 50 ; nlpages_4m = 128
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak

```