



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS80 Model 8 68/1001

SPECint2000 = 621
SPECint_base2000 = 561

SPEC license #: 2 Tested by: Compaq NH Test date: Jun-2001 Hardware Avail: Jun-2001 Software Avail: Aug-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	300	466	297	471	
175.vpr	1400	290	482	289	485	
176.gcc	1100	173	636	148	745	
181.mcf	1800	481	374	353	509	
186.crafty	1000	124	803	124	803	
197.parser	1800	445	405	347	519	
252.eon	1300	163	798	159	818	
253.perlbnk	1800	298	605	285	633	
254.gap	1100	356	309	291	378	
255.vortex	1900	253	752	223	852	
256.bzip2	1500	248	606	232	647	
300.twolf	3000	366	821	356	843	

Hardware

CPU: Alpha 21264C
CPU MHz: 1001
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1 to 8
Parallel: No
Primary Cache: 64KB(I)+64KB(D) on chip
Secondary Cache: 8MB off chip per CPU
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: mfs (Memory File System)
Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1
+Patch Kit 2
Compiler: Compaq C V6.4-214-46B59
Program Analysis Tools V2.0
Spike V5.2 DTK (1.461 46B5P)
Compaq C++ V6.3-010-46B2F
File System: mfs
System State: Multi-user

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
C++: cxx -arch ev6 -O2 ONESTEP

Peak:

All but 252.eon: cc -g3 -arch ev6 ONESTEP
164.gzip: -fast -O4 -non_shared +CFB
175.vpr: -fast -O4 -assume restricted_pointers +CFB
176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
+CFB +IFB
181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
253.perlbnk: -fast -non_shared +CFB +IFB
254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
256.bzip2: -fast -O4 -non_shared +CFB
300.twolf: -fast -O4 -assume restricted_pointers -all
-ldensemalloc -none +CFB +IFB



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS80 Model 8 68/1001

SPECint2000 = 621
SPECint_base2000 = 561

SPEC license #: 2 | Tested by: Compaq NH | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlbmk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64

Information on UNIX V5.1 Patches can be found at
<http://ftpl1.service.digital.com/public/unix/v5.1/>

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a beta kit in August, 2001, and as a production release in October, 2001. The C compiler for this SPEC submission has been



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS80 Model 8 68/1001

SPECint2000 =	621
SPECint_base2000 =	561

SPEC license #:	2	Tested by:	Compaq NH	Test date:	Jun-2001	Hardware Avail:	Jun-2001	Software Avail:	Aug-2001
-----------------	---	------------	-----------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

available at the same location, as a production release, since May, 2001.

Sysconfigtab settings:

```
max_proc_per_user = 4096
max_threads_per_user = 4096
per_proc_data_size = 21474836480
max_per_proc_data_size = 21474836480
per_proc_address_space = 21474836480
max_per_proc_address_space = 21474836480
```