



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 2600

SPECfp_rate2000 = 6.29

SPECfp_rate_base2000 = 5.66

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Apr-2001 Hardware Avail: Sep-2000 Software Avail: Mar-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	546	6.79	2	546	6.79
171.swim	2	1368	5.26	2	1355	5.31
172.mgrid	2	1108	3.77	2	1103	3.79
173.applu	2	1378	3.54	2	630	7.73
177.mesa	2	460	7.06	2	455	7.14
178.galgel	2	467	14.4	2	467	14.4
179.art	2	387	15.6	2	332	18.2
183.quake	2	890	3.39	2	846	3.57
187.facerec	2	600	7.35	2	577	7.64
188.amp	2	996	5.12	2	934	5.47
189.lucas	2	1369	3.39	4	2059	4.51
191.fma3d	2	1052	4.63	4	2065	4.72
200.sixtrack	2	638	4.00	2	638	4.00
301.apsi	2	1041	5.79	4	2006	6.01

Hardware

CPU: UltraSPARC-III
CPU MHz: 600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1-2
Parallel: None
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 4MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 1GB
Disk Subsystem: 1 x 18GB
Other Hardware: --

Software

Operating System: Solaris 8 10/00
Compiler: Forte Developer 6 update 1 w/ latest patches
File System: UFS
System State: Single User

Notes/Tuning Information

Portability:

178.galgel: -e -fixed

Base C flags: -fast -xcrossfile -xprofile -xalias_level=std

Base F90 flags: -fast -xcrossfile -xprofile

Peak:

168.wupwise: basepeak=yes

171.swim: -fast -xchip=ultra2

172.mgrid: f77 -fast -xregs=syst

173.applu: f77 -fast -Qoption iropt -Adata_access, -Mt6000, -Mm12000, -Mr40000, -Ma400, -whole -xregs=syst

177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile

178.galgel: basepeak=yes

179.art: -fast -xalias_level=strong -xdepend -xregs=syst -xprofile -dn -lmopt

183.quake: -fast -xalias_level=strong -xdepend -xprofile -lmopt

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 2600

SPECfp_rate2000 = 6.29
SPECfp_rate_base2000 = 5.66

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: Apr-2001 | Hardware Avail: Sep-2000 | Software Avail: Mar-2001

Notes/Tuning Information (Continued)

```
187.facerec: -fast -xcrossfile -stackvar -xprofile
188.ammf: -fast -xcrossfile -xalias_level=strong -xdepend -xregs=syst
          -W2,-whole -xprefetch -xprofile
189.lucas: -fast -qoption f90comp -array_pad_rows,1024 -Qoption iropt -whole -xprofile
191.fma3d: -fast -xcrossfile -stackvar -xprofile
200.sixtrack: -fast -xcrossfile -xprofile
301.apsi: -fast -qoption f90comp -expansion -xprofile
```

Note: ONESTEP=yes for all benchmarks.

Stack size set to unlimited by: ulimit -s unlimited

Forte Developer 6 update 1 patches include:

109503-07,109504-01,109505-08,109506-06,109508-01,109510-01,109513-06

Patch 111228-01 and obp 4.0.40 (or later) is required.

System configuration details located (as of June 2001) at
<http://www.sun.com/desktop/sunblade1000>