



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1700+

SPECfp2000 = 580

SPECfp_base2000 = 535

SPEC license #: 49 Tested by: AMD Austin TX Test date: Sep-2001 Hardware Avail: Oct-2001 Software Avail: Sep-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	205	780	205	780	
171.swim	3100	364	851	364	851	
172.mgrid	1800	346	520	346	521	
173.applu	2100	431	487	426	493	
177.mesa	1400	179	783	174	807	
178.galgel	2900	596	486	336	862	
179.art	2600	659	395	626	415	
183.quake	1300	278	468	227	572	
187.facerec	1900	310	614	309	616	
188.amp	2200	553	398	517	426	
189.lucas	2000	350	571	348	575	
191.fma3d	2100	357	589	357	589	
200.sixtrack	1100	296	372	287	383	
301.apsi	2600	597	436	515	505	

Hardware

CPU: AMD Athlon (TM) XP 1700+
CPU MHz: 1466
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2x128MB PC2400 DDR SDRAM CL2
Disk Subsystem: Seagate ST320420A
Other Hardware: None

Software

Operating System: Windows 2000
Compiler: Compaq Visual Fortran 6.6
Intel C/C++ 5.0.1 build 010525Z
Intel Fortran 5.0.1 build 010525Z
Microsoft Visual Studio 6.0 SP5 (libraries)
MicroQuill Smartheap Library 5.0
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
icl and ifl are the Intel C/C++ and Fortran compilers
f90 is the Compaq Fortran compiler
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability:
178.galgel: -FI -Fe$@ -link -stack:32000000
Baseline: C icl -QxK -Qipo +FDO shlw32M.lib
Baseline: Fortran ifl -O3 -QxK -Qipo +FDO
Peak tuning:
168.wupwise: ifl -O3 -QxK -Qwp_ipo +FDO
171.swim: ifl -O3 -QxK -Qwp_ipo +FDO
172.mgrid: ifl -O3 -QxK -Qwp_ipo +FDO
173.applu: ifl -O3 -QxK -Qwp_ipo -Qscalar_rep- -Qauto +FDO
177.mesa: icl -O3 -QxK -Qwp_ipo -Oa -Qunroll10 +FDO shlw32M.lib
178.galgel: f90 -Optimize:5 -fast
179.art: icl -O3 -QxK -QaxW -Qwp_ipo -Oa +FDO shlw32M.lib
183.quake: icl -O3 -QxK -Qwp_ipo -Qrcd -Oa +FDO shlw32M.lib
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1700+

SPECfp2000 = 580

SPECfp_base2000 = 535

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Sep-2001 | Hardware Avail: Oct-2001 | Software Avail: Sep-2001

Notes/Tuning Information (Continued)

```
187.facerec: f90 -Optimize:5 -fast
188.ammf: icl -O3 -QxK -Qwp_ipo -Oa +FDO
189.lucas: ifl -O3 -QxK -Qwp_ipo +FDO shlw32M.lib
191.fma3d: ifl -O3 -QxK -Qwp_ipo +FDO
200.sixtrack: ifl -QxK -QaxW -Qwp_ipo -Qprefetch +FDO
301.apsi: f90 -Optimize:5 -fast
```

Library ordering for 189.lucas (to include SmartHeap correctly with default libs):

```
LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwind.lib libm.lib shlw32M.lib LIBC.lib libirc.lib OLDNAMES.lib
```

ONESTEP is used for all base and peak runs

The tested system can be assembled using an ATX case such as the Antec KS-282, a 300W power supply such as the Sparkle FSP300-60GT, and a PCI or AGP video card. The System bus and memory bus run at 266MHz