



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 280R

SPECfp_rate2000 = 14.3

SPECfp_rate_base2000 = 12.1

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Nov-2001 Hardware Avail: Dec-2001 Software Avail: Feb-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	310	12.0	2	310	12.0
171.swim	2	664	10.8	2	664	10.8
172.mgrid	2	533	7.83	2	533	7.83
173.applu	2	915	5.33	2	418	11.7
177.mesa	2	298	10.9	2	289	11.3
178.galgel	2	205	32.7	2	165	40.9
179.art	2	31.8	190	2	31.8	190
183.equake	2	254	11.9	2	162	18.7
187.facerec	2	246	17.9	2	246	17.9
188.amp	2	521	9.79	2	505	10.1
189.lucas	2	996	4.66	2	549	8.46
191.fma3d	2	693	7.03	2	650	7.49
200.sixtrack	2	355	7.19	2	355	7.19
301.apsi	2	745	8.09	2	653	9.24

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 900
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: None
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 2GB
 Disk Subsystem: 2 x 36GB
 Other Hardware: --

Software

Operating System: Solaris 8 10/01
 Compiler: Forte Developer 7 EA
 Forte Developer 6 update 2
 File System: tmpfs
 System State: Multi-User

Notes/Tuning Information

Portability:
 178.galgel: -e -fixed

Base Flags:
 Base C flags: -fast -xipo=2 -xalias_level=std -xprofile
 Base F90 flags: -fast -xcrossfile -lprism32 -xprofile

Peak Flags:
 168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: -fast -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
 -xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg -Qlp=1-av=192-fa=1
 -Qoption f90comp -O3
 177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile
 178.galgel: -fast -xcrossfile -xregs=syst -Qoption iropt -Addint:sf=9 -lsunperf -xprofile



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 280R

SPECfp_rate2000 = 14.3
SPECfp_rate_base2000 = 12.1

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Nov-2001 Hardware Avail: Dec-2001 Software Avail: Feb-2002

Notes/Tuning Information (Continued)

```
179.art: basepeak=yes
183.earthquake: -fast -xalias_level=strong -xdepend -W2,-whole,-Amemopt:arrayloc -xprefetch
                -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -xprofile
187.facerec: basepeak=yes
188.ammamp: -fast -xcrossfile -xalias_level=std -lprism32 -xprofile
189.lucas: -fast -Qoption f90comp -array_pad_rows,2002 -Qoption iropt -whole
           -xdepend -xprefetch -Qoption cg -Qms_pipe-pref,-Qlp=1-t=3-fa=1
           -lprism32 -xprofile
191.fma3d: -fast -xcrossfile -stackvar -xdepend -xprefetch
           -Qoption cg -Qlp=1-av=256-t=3-fa=1 -xprofile
200.sixtrack: basepeak=yes
301.apsi: -fast -Qoption iropt -Mt450 -lprism32 -xprofile
```

Forte Developer 7 (final) will ship May-2002

ONESTEP=yes for all benchmarks in base and peak except for C benchmarks in fp base

Shell Environments:

```
LD_LIBRARY_PATH=/usr/lib:/ForteD7/FD7/lib/v8plusb:/ForteD7/FD7/YNH/lib/v8plusb
PRISM_HEAP=268435456
PRISM_MODE=2
```

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

```
set shmsys:shminfo_shmmin=1
set shmsys:shminfo_shmmax=1477846784
set shmsys:shminfo_shmmni=256
set shmsys:shminfo_shmseg=400
```

System configuration details located (as of December 2001) at
<http://www.sun.com/servers/workgroup/280r/>