



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.26 GHz, Pentium 4 processor)

SPECfp2000 = 829

SPECfp_base2000 = 815

SPEC license #: 13 Tested by: Intel Corporation Test date: Apr-2002 Hardware Avail: May-2002 Software Avail: Oct-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	145	1105	143	1116	
171.swim	3100	227	1367	223	1389	
172.mgrid	1800	227	793	221	813	
173.applu	2100	242	869	235	892	
177.mesa	1400	150	931	149	940	
178.galgel	2900	274	1058	272	1068	
179.art	2600	476	546	458	568	
183.quake	1300	150	868	144	905	
187.facerec	1900	183	1038	182	1045	
188.amp	2200	412	534	407	540	
189.lucas	2000	182	1099	182	1099	
191.fma3d	2100	286	734	286	735	
200.sixtrack	1100	266	414	256	430	
301.apsi	2600	407	639	407	639	

Hardware

CPU: Pentium 4 processor (2.26 GHz, 533 MHz bus)
CPU MHz: 2267
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
Disk Subsystem: IBM DTLA-307030 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 5.0.1 Build 010525Z
Intel Fortran Compiler 5.0.1 Build 010525Z
Microsoft Visual C++ 6.0 SP5(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.amp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.26 GHz, Pentium 4 processor)

SPECfp2000 = 829

SPECfp_base2000 = 815

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Apr-2002 | Hardware Avail: May-2002 | Software Avail: Oct-2001

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 5/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz