



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480

SPECfp_rate2000 = 15.5
SPECfp_rate_base2000 = 13.6

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: May-2002 Hardware Avail: Jun-2002 Software Avail: May-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	292	12.7	2	292	12.7
171.swim	2	384	18.7	2	384	18.7
172.mgrid	2	482	8.66	2	482	8.66
173.applu	2	757	6.43	2	399	12.2
177.mesa	2	288	11.3	2	278	11.7
178.galgel	2	209	32.2	2	169	39.8
179.art	2	31.6	191	2	31.6	191
183.equake	2	241	12.5	2	152	19.8
187.facerec	2	239	18.4	2	239	18.4
188.amp	2	507	10.1	2	479	10.7
189.lucas	2	620	7.48	2	448	10.4
191.fma3d	2	628	7.75	2	563	8.66
200.sixtrack	2	484	5.27	2	484	5.27
301.apsi	2	558	10.8	2	555	10.9

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 900
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 32KBI+64KBD on chip per CPU
 Secondary Cache: 8MB(I+D) off chip per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 4GB
 Disk Subsystem: 1 x 36GB + 1 x 18GB
 Other Hardware: None

Software

Operating System: Solaris 8 02/02
 Compiler: Sun ONE Studio 7
 with patch 111704-01
 Sun Performance Library 7
 File System: tmpfs
 System State: Multi-User

Notes/Tuning Information

Portability:
 178.galgel: -e -fixed

Base Flags:
 Base C flags: -fast -xipo=2 -xalias_level=std -xprofile
 Base F90 flags: -fast -xcrossfile -lprism32 -xprofile

Peak Flags:
 168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: -fast -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
 -xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg -Qlp=1-av=192-fa=1
 -Qoption f90comp -O3
 177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile
 178.galgel: -fast -xcrossfile -xregs=syst -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf -xprofile



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480

SPECfp_rate2000 = 15.5

SPECfp_rate_base2000 = 13.6

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: May-2002 | Hardware Avail: Jun-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```
179.art: basepeak=yes
183.quake: -fast -xalias_level=strong -W2,-whole,-Amemopt:arrayloc
           -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -xprofile
187.facerec: basepeak=yes
188.ammop: -fast -xcrossfile -xalias_level=std -lprism32 -xprofile
189.lucas: -fast -Qoption f90comp -array_pad_rows,2002 -Qoption iropt -whole
           -Qoption cg -Qms_pipe-pref,-Qlp=1-t=3-fa=1
           -lprism32 -xprofile
191.fma3d: -fast -xcrossfile -stackvar -Qoption cg -Qlp=1-av=256-t=3-fa=1 -xprofile
200.sixtrack: basepeak=yes
301.apsi: -fast -Qoption iropt -Mt450 -lprism32 -xprofile
ONESTEP=yes for all benchmarks in peak and Fortran benchmarks in base
```

Shell Environments:

```
LD_LIBRARY_PATH=/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb
PRISM_HEAP=268435456
PRISM_MODE=2
```

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

```
set shmsys:shminfo_shmmin=1
set shmsys:shminfo_shmmax=1477846784
set shmsys:shminfo_shmmni=256
set shmsys:shminfo_shmseg=400
```

System configuration details located (as of June 2002) at
<http://www.sun.com/servers/entry/>