



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer ES45 68/1250

SPECint_rate2000 = NC
SPECint_rate_base2000 = NC

SPEC license #: 2

Tested by:

HP NH

Test date:

Jul-2002

Hardware Avail:

Aug-2002

Software Avail:

Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

5	4	3	2	1		Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
						164.gzip	2	NC	NC	2	NC	NC
						175.vpr	2	NC	NC	2	NC	NC
						176.gcc	2	NC	NC	2	NC	NC
						181.mcf	2	NC	NC	2	NC	NC
						186.crafty	2	NC	NC	2	NC	NC
						197.parser	2	NC	NC	2	NC	NC
						252.eon	2	NC	NC	2	NC	NC
						253.perlbench	2	NC	NC	2	NC	NC
						254.gap	2	NC	NC	2	NC	NC
						255.vortex	2	NC	NC	2	NC	NC
						256.bzip2	2	NC	NC	2	NC	NC
						300.twolf	2	NC	NC	2	NC	NC

Hardware		Software	
CPU:	Alpha 21264C	Operating System:	Tru64 UNIX T5.1B
CPU MHz:	1250	Compiler:	Compaq C V6.5-011-48C5K
FPU:	Integrated		Spike V5.2 (506 48C5K)
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip		Compaq C++ V6.5-028
CPU(s) orderable:	1 to 4		ufs
Parallel:	No	System State:	Multi-user
Primary Cache:	64KB(I)+64KB(D) on chip		
Secondary Cache:	16MB off chip per CPU		
L3 Cache:	None		
Other Cache:	None		
Memory:	16GB		
Disk Subsystem:	9 GB SCSI		
Other Hardware:	None		

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
C++: cxx -arch ev6 -O2 ONESTEP

Peak:

All but 252.eon: cc -g3 -arch ev6 ONESTEP
164.gzip: -fast -O4 -non_shared +CFB
175.vpr: -fast -O4 -assume restricted_pointers +CFB
176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
+CFB +IFB



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer ES45 68/1250

SPECint_rate2000 = NC
SPECint_rate_base2000 = NC

SPEC license #: 2

Tested by:

HP NH

Test date:

Jul-2002

Hardware Avail:

Aug-2002

Software Avail:

Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

```
181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
  252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
253.perlbmk: -fast -non_shared +CFB +IFB
  254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
  256.bzip2: -fast -O4 -non_shared +CFB
  300.twolf: -fast -O4
             -ldensemalloc -non_shared +CFB +IFB
```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use      -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer ES45 68/1250

SPECint_rate2000 = NC
SPECint_rate_base2000 = NC

SPEC license #: 2

Tested by:

HP NH

Test date:

Jul-2002

Hardware Avail:

Aug-2002

Software Avail:

Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

vm:

```
vm_bigpg_enabled = 1
vm_bigpg_thresh=16
vm_swap_eager = 0
```

proc:

```
max_per_proc_address_space = 0x400000000000
max_per_proc_data_size = 0x400000000000
max_per_proc_stack_size = 0x400000000000
max_proc_per_user = 2048
max_threads_per_user = 0
maxusers = 16384
per_proc_address_space = 0x400000000000
per_proc_data_size = 0x400000000000
per_proc_stack_size = 0x400000000000
```

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlchk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64

Submitted_by: "Craig, Steve" <Steve.Craig@hp.com>
Submitted: Thu Aug 1 16:05:09 2002
Submission: cpu2000-20020801-01514.sub