



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
hp AlphaServer DS25 68/1000

SPECint\_rate2000 = 15.5  
SPECint\_rate\_base2000 = 14.3

SPEC license #: 2 | Tested by: HP | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

| 24 | 21 | 18 | 15 | 12 | 9 | 6 | 3 | Benchmark   | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|----|----|----|----|----|---|---|---|-------------|-------------|--------------|------------|--------|---------|-------|
|    |    |    |    |    |   |   |   | 164.zip     | 2           | 303          | 10.7       | 2      | 299     | 10.9  |
|    |    |    |    |    |   |   |   | 175.vpr     | 2           | 266          | 12.2       | 2      | 263     | 12.3  |
|    |    |    |    |    |   |   |   | 176.gcc     | 2           | 158          | 16.2       | 2      | 142     | 18.0  |
|    |    |    |    |    |   |   |   | 181.mcf     | 2           | 327          | 12.8       | 2      | 250     | 16.7  |
|    |    |    |    |    |   |   |   | 186.crafty  | 2           | 123          | 18.9       | 2      | 123     | 18.9  |
|    |    |    |    |    |   |   |   | 197.parser  | 2           | 433          | 9.65       | 2      | 346     | 12.1  |
|    |    |    |    |    |   |   |   | 252.eon     | 2           | 164          | 18.4       | 2      | 159     | 19.0  |
|    |    |    |    |    |   |   |   | 253.perlbnk | 2           | 313          | 13.4       | 2      | 295     | 14.2  |
|    |    |    |    |    |   |   |   | 254.gap     | 2           | 245          | 10.4       | 2      | 207     | 12.3  |
|    |    |    |    |    |   |   |   | 255.vortex  | 2           | 224          | 19.7       | 2      | 210     | 21.0  |
|    |    |    |    |    |   |   |   | 256.bzip2   | 2           | 226          | 15.4       | 2      | 212     | 16.4  |
|    |    |    |    |    |   |   |   | 300.twolf   | 2           | 379          | 18.4       | 2      | 374     | 18.6  |

### Hardware

CPU: Alpha 21264C  
 CPU MHz: 1000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
 CPU(s) orderable: 1 to 2  
 Parallel: No  
 Primary Cache: 64KB(I)+64KB(D) on chip  
 Secondary Cache: 8MB off chip per CPU  
 L3 Cache: None  
 Other Cache: None  
 Memory: 8GB  
 Disk Subsystem: 18.2GB SCSI  
 Other Hardware: None

### Software

Operating System: Tru64 UNIX V5.1A  
 Compiler: Compaq C V6.4-215-46B70  
 Program Analysis Tools V2.0  
 Spike V5.2 DTK (1.471.2.2 46B5P)  
 Compaq C++ V6.3-010-46B2F  
 File System: AdvFS  
 System State: Multi-user

## Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP  
 C++: cxx -arch ev6 -O2 ONESTEP

### Peak:

All but 252.eon: cc -g3 -arch ev6 ONESTEP  
 164.zip: -fast -O4 -non\_shared +CFB  
 175.vpr: -fast -O4 -assume restricted\_pointers +CFB  
 176.gcc: -fast -O4 -xtaso\_short -all -ldensemalloc -none  
 +CFB +IFB  
 181.mcf: -fast -xtaso\_short +CFB +IFB +PFB  
 186.crafty: same as base  
 197.parser: -fast -O4 -xtaso\_short -non\_shared +CFB  
 252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none  
 253.perlbnk: -fast -non\_shared +CFB +IFB  
 254.gap: -fast -O4 -non\_shared +CFB +IFB +PFB  
 255.vortex: -fast -non\_shared +CFB +IFB  
 256.bzip2: -fast -O4 -non\_shared +CFB  
 300.twolf: -fast -O4 -assume restricted\_pointers -all  
 -ldensemalloc -none +CFB +IFB



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
hp AlphaServer DS25 68/1000

SPECint\_rate2000 = 15.5  
SPECint\_rate\_base2000 = 14.3

SPEC license #: 2 | Tested by: HP | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

## Notes/Tuning Information (Continued)

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo\_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo\_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo\_post\_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo\_runN"), and then this command (in phase "fdo\_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

```
Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlbnk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64
```

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a production release in October, 2001. The C compiler for this SPEC submission has been available at the same location, as a production release, since August, 2001.