



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS320 68/1224

SPECfp_rate2000 = NC
SPECfp_rate_base2000 = NC

SPEC license #: 2 | Tested by: HP | Test date: Sep-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

5	4	3	2	1	Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
.....	168.wupwise	1	NC	NC	1	NC	NC
.....	171.swim	1	NC	NC	1	NC	NC
.....	172.mgrid	1	NC	NC	1	NC	NC
.....	173.applu	1	NC	NC	1	NC	NC
.....	177.mesa	1	NC	NC	1	NC	NC
.....	178.galgel	1	NC	NC	1	NC	NC
.....	179.art	1	NC	NC	1	NC	NC
.....	183.quake	1	NC	NC	1	NC	NC
.....	187.facerec	1	NC	NC	1	NC	NC
.....	188.ammp	1	NC	NC	1	NC	NC
.....	189.lucas	1	NC	NC	1	NC	NC
.....	191.fma3d	1	NC	NC	1	NC	NC
.....	200.sixtrack	1	NC	NC	1	NC	NC
.....	301.apsi	1	NC	NC	1	NC	NC

Hardware

CPU: Alpha 21264C
CPU MHz: 1224
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1 to 32
Parallel: No
Primary Cache: 64KB(I)+64KB(D) on chip
Secondary Cache: 16MB off chip per CPU
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: 9 GB SCSI
Other Hardware: None

Software

Operating System: Tru64 UNIX T5.1B
Compiler: Compaq C V6.5-011-48C5K
Spike V5.2 (506 48C5K)
Compaq Fortran V5.5-1877-48BBF
Compaq Fortran 77 V5.5-1877-48BBF
KAP Fortran V4.4 k340504 20010517
KAP Fortran 77 V4.1 k310440 980926
KAP C V4.2 k010737S 010515

File System: ufs
System State: Multi-user

Notes/Tuning Information

Baseline C: cc -arch ev6 -fast -O4 ONESTEP
Fortran: f90 -arch ev6 -fast -O5 ONESTEP

Peak:
All use -arch ev6 -non_shared ONESTEP (except applu and ammp)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS320 68/1224

SPECfp_rate2000 = NC
SPECfp_rate_base2000 = NC

SPEC license #: 2 | Tested by: HP | Test date: Sep-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

Individual benchmark tuning:

```

168.wupwise: kf77 -call_shared -inline all -tune ev67
              -unroll 12 -automatic -align commons -arch ev67
              -fkapargs=' -aggressive=c -fuse
              -fuselevel=1 -so=2 -r=1 -o=1 -interleave
              -ur=6 -ur2=060 ' +PFB
171.swim: same as base
172.mgrid: kf90 -call_shared -arch generic -O5 -inline
              manual -nopipeline -unroll 9 -automatic -transform_loops
              -fkapargs=' -aggressive=a -fuse -interleave
              -ur=2 -ur3=5 -cachesize=128,16000 ' +PFB
173.applu: kf90 -O5 -transform_loops
              -fkapargs=' -o=0 -nointerleave -ur=14
              -ur2=260 -ur3=18' +PFB
177.mesa: kcc -fast -O4 +CFB +IFB
178.galgel: f90 -O5 -fast -unroll 5 -automatic
179.art: kcc -assume whole_program -ldensemalloc
           -call_shared -assume restricted_pointers
           -unroll 16 -inline none -ckapargs='
           -fuse -fuselevel=1 -ur=3' +PFB
183.quake: cc -call_shared -arch generic -fast -O4
              -ldensemalloc -assume restricted_pointers
              -inline speed -unroll 13 -xtaso_short +PFB
187.facerec: f90 -O4 -nopipeline -inline all
              -non_shared -speculate all -unroll 7
              -automatic -assume accuracy_sensitive
              -math_library fast +IFB
188.ammp: cc -arch host -O4 -ifo -assume nomath_errno
            -assume trusted_short_alignment -fp_reorder
            -readonly_strings -ldensemalloc -xtaso_short
            -assume restricted_pointers -unroll 9
            -inline speed +CFB +IFB +PFB
189.lucas: kf90 -O5 -fkapargs='-ur=1' +PFB
191.fma3d: kf90 -O4 -transform_loops -fkapargs='-cachesize=128,16000' +PFB
200.sixtrack: f90 -fast -O5 -assume accuracy_sensitive
              -notransform_loops +PFB
301.apsi: kf90 -O5 -inline none -call_shared -speculate all
           -align commons -fkapargs=' -aggressive=ab
           -tune=ev5 -fuse -ur=1 -ur2=60 -ur3=20
           -cachesize=128,16000'

```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS320 68/1224

SPECfp_rate2000 = NC
SPECfp_rate_base2000 = NC

SPEC license #: 2 | Tested by: HP | Test date: Sep-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp  
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp  
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe  
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*  
mv ${baseexe} oldexe  
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err  
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

vm:

```
vm_bigpg_enabled = 1  
vm_bigpg_thresh=16  
vm_swap_eager = 0
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS320 68/1224

SPECfp_rate2000 = NC
SPECfp_rate_base2000 = NC

SPEC license #: 2 | Tested by: HP | Test date: Sep-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

proc:

```
max_per_proc_address_space = 0x400000000000
max_per_proc_data_size = 0x400000000000
max_per_proc_stack_size = 0x400000000000
max_proc_per_user = 2048
max_threads_per_user = 0
maxusers = 16384
per_proc_address_space = 0x400000000000
per_proc_data_size = 0x400000000000
per_proc_stack_size = 0x400000000000
```

```
Portability: galgel: -fixed
submit = runon cpu
System is single QBB (4-cpu) with only 1 cpu enabled at console
```

```
Submitted_by: "Craig, Steve" <Steve.Craig@hp.com>
Submitted: Mon Sep 9 13:56:51 2002
Submission: cpu2000-20020909-01615.sub
```