



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
CELSIUS R610

SPECfp2000 = 930  
SPECfp\_base2000 = 914

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Feb-2003 Hardware Avail: Feb-2003 Software Avail: Jan-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	113	1420	115	1392	
171.swim	3100	257	1206	255	1218	
172.mgrid	1800	224	804	225	802	
173.applu	2100	245	857	244	859	
177.mesa	1400	122	1149	121	1157	
178.galgel	2900	216	1340	217	1338	
179.art	2600	454	573	452	575	
183.earthquake	1300	112	1163	95.0	1368	
187.facerec	1900	163	1167	160	1188	
188.amp	2200	389	565	389	565	
189.lucas	2000	186	1074	186	1077	
191.fma3d	2100	211	996	209	1006	
200.sixtrack	1100	219	503	207	531	
301.apsi	2600	392	663	392	664	

### Hardware

CPU: Xeon processor (2.8 GHz, 533 MHz bus)  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 2  
 Parallel: No  
 Primary Cache: 12K micro-ops I + 8KBD on chip  
 Secondary Cache: 512KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 1024 MB (2 512 MB PC2100 DDR ECC modules)  
 Disk Subsystem: ATA-100  
 Other Hardware:

### Software

Operating System: Windows 2000 Professional  
 Compiler: Intel(R) C++ Compiler, Version 7.0 Build 20030114Z  
 Intel(R) Fortran Compiler, Version 7.0 Build 20030114Z  
 Microsoft Visual Studio .NET: 7.00.9466 (for libraries)  
 MicroQuill SmartHeap Library 6.03a  
 File System: FAT32  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
  178.galgel: -FI /F32000000
Peak tuning:
  168.wupwise: -Qipo -QaxW -Oa +FDO
  171.swim: -Qipo -QaxW -O3 +FDO
  172.mgrid: -Qipo -QaxW -O3 +FDO
  173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
  177.mesa: -Qipo -QxW +FDO
  178.galgel: -Qipo -QxW -O3 +FDO
  179.art: -Qipo -QxW +FDO
  183.earthquake: -Qipo -QxW -O3 -Oa -Qrcd +FDO shlw32M.lib
  187.facerec: -Qipo -QaxW -O3 +FDO
  188.amp: -Qipo -QxW -O3 +FDO
  189.lucas: -Qipo -QxW +FDO
  191.fma3d: -Qipo -QaxW -O3 +FDO
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
CELSIUS R610

SPECfp2000 = 930

SPECfp\_base2000 = 914

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Feb-2003 | Hardware Avail: Feb-2003 | Software Avail: Jan-2003

## Notes/Tuning Information (Continued)

```
200.sixtrack: -Qipo -QaxW +FDO
301.apsi:     -Qipo -QxW  -O3 +FDO
Extra Libraries
shlW32M.lib : MicroQuill SmartHeap Library 6.03a
              www.microquill.com
The system bus runs at 533 MHz
Only one CPU installed on the system board.
```