



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 630 Model 6C4 (1200 MHz, 4 CPU)

SPECfp_rate2000 = 35.1

SPECfp_rate_base2000 = 34.2

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: Feb-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	148	50.1	4	148	50.3
171.swim	4	406	35.4	4	406	35.4
172.mgrid	4	308	27.2	4	283	29.5
173.applu	4	375	26.0	4	374	26.1
177.mesa	4	236	27.5	4	198	32.9
178.galgel	4	146	92.1	4	136	98.8
179.art	4	332	36.3	4	354	34.1
183.equake	4	170	35.4	4	170	35.4
187.facerec	4	204	43.2	4	203	43.4
188.amp	4	396	25.8	4	396	25.8
189.lucas	4	285	32.6	4	281	33.0
191.fma3d	4	355	27.5	4	343	28.4
200.sixtrack	4	216	23.6	4	212	24.1
301.apsi	4	384	31.4	4	379	31.8

Hardware

CPU: POWER4+
 CPU MHz: 1200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip, 1 chip/SCM
 CPU(s) orderable: 1,2,4 (order by # cores)
 Parallel: No
 Primary Cache: 64KBI+32KBD (on chip) per core
 Secondary Cache: 1536KB unified (on chip) per chip
 L3 Cache: 8MB unified (off-chip) per SCM, 2 SCMs in SUT
 Other Cache: None
 Memory: 16 GB
 Disk Subsystem: 1x36GB SCSI
 Other Hardware: None

Software

Operating System: AIX 5L V5.2 PTF 2
 Compiler: IBM C for AIX, Version 6.0
 IBM XL FORTRAN for AIX, Version 8.1.0.3
 Other Software: ESSL 3.3, MASS 3.0
 File System: AIX/JFS
 System State: Multi-User

Notes/Tuning Information

Portability Flags

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu, 178.galgel, 200.sixtrack, 301.apsi
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

Base Optimization Flags:

C:
 -O5 -qalign=natural -blpdata -lmass
 Fortran:
 -O5 -qalign=natural -blpdata -lmass

Floating Point Peak Flags

168.wupwise
 -O5 -qipa=partition=large
 171.swim
 -O4 -q64 -blpdata
 172.mgrid



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 630 Model 6C4 (1200 MHz, 4 CPU)

SPECfp_rate2000 = 35.1

SPECfp_rate_base2000 = 34.2

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: Feb-2003

Notes/Tuning Information (Continued)

```

-05 -qarch=pwr3 -qtune=pwr3 -blpdata
173.applu
-03 -qarch=pwr3 -qtune=pwr3 -lmass -qhot -blpdata
177.mesa
-qpdf1/pdf2
fdpr -v -R3
-03 -qarch=pwr3 -qtune=pwr3 -qipa=level=2 -qalign=natural -blpdata
178.galgel
-qpdf1/pdf2
fdpr -v -R3
-05 -qalign=natural -qessl -lessl -lmass -blpdata
179.art
-04 -lhmu
183.quake
BASEPEAK = 1
187.facerec
fdpr -v -R3
-05 -lmass -blpdata
188.ammp
BASEPEAK = 1
189.lucas
-03 -q64 -blpdata
191.fma3d
-qpdf1/pdf2
-05 -qarch=pwr4 -qtune=pwr3 -lhmu -qalign=natural -blpdata
200.sixtrack
-qpdf1/pdf2
-05 -lmass
301.apsi
-05 -qarch=pwr4 -qtune=pwr3 -blpdata

```

SCM: Acronym for "Single-Chip Module"

SUT: Acronym for "System Under Test"

```

fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O.
APAR IY 38292 was applied to AIX to enable new hardware support.
ulimits set to unlimited.
C: IBM VAC++ invoked as xlc
Fortran 77 and 90: IBM XL Fortran for AIX invoked as xlf90.
Large page mode and memory affinity were set as follows:
vmo -r -o lpgg_regions=128 -o lpgg_size=16777216 -o memory_affinity=1
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -r
export MEMORY_AFFINITY=MCM

```