



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
SGI Altix 3000 (1000MHz, Itanium 2)

SPECint2000 = 683  
SPECint\_base2000 = 683

SPEC license #: 4 Tested by: SGI Test date: May-2003 Hardware Avail: Feb-2003 Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	300 600 900 1200			
164.gzip	1400	229	612	229	612	[Bar chart showing ratio 612]			
175.vpr	1400	213	657	213	657	[Bar chart showing ratio 657]			
176.gcc	1100	132	834	132	834	[Bar chart showing ratio 834]			
181.mcf	1800	322	559	322	559	[Bar chart showing ratio 559]			
186.crafty	1000	144	695	144	695	[Bar chart showing ratio 695]			
197.parser	1800	372	484	372	484	[Bar chart showing ratio 484]			
252.eon	1300	156	836	156	836	[Bar chart showing ratio 836]			
253.perlbnk	1800	263	684	263	684	[Bar chart showing ratio 684]			
254.gap	1100	203	543	203	543	[Bar chart showing ratio 543]			
255.vortex	1900	194	980	194	980	[Bar chart showing ratio 980]			
256.bzip2	1500	226	662	226	662	[Bar chart showing ratio 662]			
300.twolf	3000	372	807	372	807	[Bar chart showing ratio 807]			

### Hardware

CPU: Intel Itanium 2  
CPU MHz: 1000  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 4-64  
Parallel: No  
Primary Cache: 16KBI + 16KBD (on chip) per CPU  
Secondary Cache: 256KB (on chip) per CPU  
L3 Cache: 3.0MB (on chip) per CPU  
Other Cache: N/A  
Memory: 2 GB  
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)  
Other Hardware: None

### Software

Operating System: SGI ProPack(TM) v2.1  
Compiler: Intel(R) C++ Compiler for Linux 7.1 (Build 20030422)  
File System: xfs  
System State: Single-user

## Notes/Tuning Information

+FDO: PASS1=-prof\_gen PASS2=-prof\_use

### Baseline optimization flags:

C programs: -ipo -O3 +FDO  
C++ programs: -ipo -O2 -ansi\_alias +FDO

### Portability Flags:

176.gcc: -DSPEC\_CPU2000\_LP64 -Dalloca=\_builtin\_alloca -D\_LIBC  
186.crafty: -DLINUX\_i386  
252.eon: -DSPEC\_CPU2000\_LP64 -DHAS\_ERRLIST  
253.perlbnk: -DSPEC\_CPU2000\_LP64 -DSPEC\_CPU2000\_NEED\_BOOL  
-DSPEC\_CPU2000\_LINUX\_IA64 -DSPEC\_CPU2000\_GLIBC22  
254.gap: -DSPEC\_CPU2000\_LP64 -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_IS\_USG  
-DSYS\_HAS\_IOCTL\_PROTO -DSYS\_HAS\_TIME\_PROTO -DSYS\_HAS\_SIGNAL\_PROTO  
255.vortex: -DSPEC\_CPU2000\_LP64

Processes were bound to CPUs using dplace.

Peak flags same as baseline (basepeak=true set globally).