



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1500MHz, Itanium 2)

SPECfp_rate2000 = 329
SPECfp_rate_base2000 = 327

SPEC license #: 4 | Tested by: SGI | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Jun-2003

				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
2000	1500	1000	500	168.wupwise	16	117	254	16	117	254
				171.swim	16	138	417	16	138	417
				172.mgrid	16	119	280	16	119	281
				173.applu	16	67.4	578	16	67.4	578
				177.mesa	16	123	211	16	123	211
				178.galgel	16	76.8	701	16	76.8	701
				179.art	16	40.1	1205	16	40.1	1205
				183.equake	16	59.7	404	16	59.7	404
				187.facerec	16	117	301	16	117	301
				188.amp	16	162	252	16	162	252
				189.lucas	16	174	213	16	170	218
				191.fma3d	16	220	177	16	220	177
				200.sixtrack	16	78.8	259	16	78.8	259
				301.apsi	16	281	172	16	263	184

Hardware

CPU: Intel Itanium 2
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 4-64
Parallel: No
Primary Cache: 16KBI + 16KBD (on chip) per CPU
Secondary Cache: 256KB (on chip) per CPU
L3 Cache: 6.0MB (on chip) per CPU
Other Cache: N/A
Memory: 32 GB (16*512MB DIMMS per 4cpu module)
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.2
Compiler: Intel(R) Fortran Compiler for Linux 7.1 (Build 20030507)
Intel(R) C++ Compiler for Linux 7.1 (Build 20030507)
File System: xfs
System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO -ansi_alias
Fortran programs: -ipo -O3 +FDO

Portability Flags:

178.galgel: -FI

Peak optimization flags:

168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: -O3 -ipo
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: basepeak=yes
179.art: basepeak=yes



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 3000 (1500MHz, Itanium 2)

SPECfp_rate2000 = 329

SPECfp_rate_base2000 = 327

SPEC license #: 4 | Tested by: SGI | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Jun-2003

Notes/Tuning Information (Continued)

183.equake: basepeak=yes
187.facerec: basepeak=yes
188.ammp: basepeak=yes
189.lucas: -O3 -ipo
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: -O3 -ipo

Processes were bound to CPUs using dplace.