



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell  
PowerEdge 6650 (2.8 GHz Xeon MP)

SPECfp\_rate2000 = 25.4  
SPECfp\_rate\_base2000 = 24.9

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Apr-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	196	38.0	4	197	37.7
171.swim	4	1026	14.0	4	1027	14.0
172.mgrid	4	582	14.3	4	582	14.4
173.applu	4	824	11.8	4	823	11.8
177.mesa	4	125	51.9	4	124	52.3
178.galgel	4	196	68.6	4	196	68.5
179.art	4	442	27.3	4	349	34.5
183.quake	4	361	16.7	4	363	16.6
187.facerec	4	291	30.3	4	290	30.4
188.amp	4	275	37.1	4	274	37.3
189.lucas	4	644	14.4	4	643	14.4
191.fma3d	4	507	19.2	4	507	19.2
200.sixtrack	4	213	24.0	4	210	24.3
301.apsi	4	370	32.6	4	372	32.5

### Hardware

CPU: Intel Xeon MP (400 MHz system bus)  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip (Hyper-Threading Technology disabled)  
 CPU(s) orderable: 1,2,4  
 Parallel: No  
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip  
 Secondary Cache: 512KB(I+D) on chip  
 L3 Cache: 2048KB(I+D) on chip  
 Other Cache: N/A  
 Memory: 4 x 1024MB DDR200  
 Disk Subsystem: 1 x 36GB SEAGATE ST336706LC  
 Other Hardware:

### Software

Operating System: Windows 2000 Advanced Server (SP2)  
 Compiler: Intel C++ Compiler 7.1 (20030402Z)  
 Intel Fortran Compiler 7.1 (20030402Z)  
 Microsoft Visual Studio .NET (7.0.9466)  
 File System: NTFS  
 System State: Hyper-Threading Technology disabled using BIOS switch.

## Notes/Tuning Information

```

PORTABILITY
 178.galgel: -FI /F32000000
FEEDBACK DIRECTED OPTIMIZATION
ONESTEP=YES
FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
BASE TUNING
C/F77/F90: -Qipo -QxW -O3 +FDO
PEAK TUNING
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -QxW -O3 -Oa +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Oa -Qipo -Qunroll4 -Zp4
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -O3 -QaxW -Qipo -Qunroll1 -Qscalar_rep- +FDO

```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell  
PowerEdge 6650 (2.8 GHz Xeon MP)

SPECfp\_rate2000 = 25.4  
SPECfp\_rate\_base2000 = 24.9

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Apr-2003

## Notes/Tuning Information (Continued)

188. ammp: -Oa -QxW  
189. lucas: -Qipo -QaxW  
191. fma3d: basepeak=yes  
200. sixtrack: -Qipo -QxW +FDO  
301. apsi: -Qipo -QxW -O3 +FDO