



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480 (1050MHz)

SPECint_rate2000 = 28.2
SPECint_rate_base2000 = 25.2

SPEC license #: 6 Tested by: Sun Microsystems Test date: May-2003 Hardware Avail: Jul-2003 Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	337	19.3	4	275	23.6
175.vpr	4	306	21.2	4	284	22.9
176.gcc	4	195	26.2	4	177	28.8
181.mcf	4	344	24.3	4	289	28.9
186.crafty	4	173	26.8	4	149	31.2
197.parser	4	363	23.0	4	314	26.6
252.eon	4	193	31.2	4	186	32.4
253.perlbnk	4	327	25.6	4	305	27.4
254.gap	4	294	17.4	4	248	20.6
255.vortex	4	224	39.3	4	201	43.8
256.bzip2	4	248	28.0	4	232	30.0
300.twolf	4	525	26.5	4	483	28.8

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 1050
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 16GB 8-way interleaved
 Disk Subsystem: 2 x 36GB Seagate ST336605
 Other Hardware: None

Software

Operating System: Solaris 9
 Compiler: Sun ONE Studio 8
 Sun Performance Library 8
 File System: ufs with ufs logging
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:
 C: cc
 CXX: CC

Integer base flags:
 -fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:
 ONESTEP=yes and feedback for all benchmarks

164.zip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
 -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
 175.vpr: -fast -xalias_level=std -xipo=2
 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm
 176.gcc: -fast -xipo=2 -l12amm
 181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
 186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
 Feedback adds -xlinkopt in PASS2



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480 (1050MHz)

SPECint_rate2000 = 28.2
SPECint_rate_base2000 = 25.2

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -l12amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

set cpu_bringup_set=4
set autoup=900
set tune_t_fsflushr=1

```