



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL20p G2 (3.06GHz/1MB L3 cache, Intel Xeon)

SPECfp2000 = **1193**  
SPECfp\_base2000 = **1160**

SPEC license #: 3 Test date: Aug-2003 Hardware Avail: Jul-2003 Software Avail: Jun-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	111	1444	113	1419
171.swim	3100	196	1582	185	1676
172.mgrid	1800	153	1180	151	1193
173.applu	2100	190	1104	188	1116
177.mesa	1400	112	1248	112	1248
178.galgel	2900	165	1761	164	1772
179.art	2600	286	908	270	963
183.quake	1300	113	1155	90.8	1432
187.facerec	1900	131	1445	130	1460
188.amp	2200	240	917	238	924
189.lucas	2000	142	1407	141	1415
191.fma3d	2100	185	1137	185	1137
200.sixtrack	1100	197	559	192	573
301.apsi	2600	264	986	263	988

### Hardware

CPU: Intel Xeon (3.06GHz, 533MHz bus)  
 CPU MHz: 3066  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading disabled)  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 12K micro-ops I + 8KBD on chip  
 Secondary Cache: 512KB(I+D) on chip  
 L3 Cache: 1024KB(I+D) on chip  
 Other Cache: N/A  
 Memory: 2x1024MB PC2100  
 Disk Subsystem: 2x18.2GB 15K Ultra3 SCSI  
 Other Hardware:

### Software

Operating System: Windows 2000 Server (Build 2195 SP3)  
 Compiler: Intel C++ Compiler 7.1 Build 20030801Z  
 Microsoft Visual Studio Enterprise Edition 6.0 (for libraries)  
 Intel Fortran Compiler 7.1 build 20030307Z  
 MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Hyperthreading disabled in BIOS

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxW -Qipo -O3 +FDO ONESTEP=yes
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW +FDO ONESTEP=yes
171.swim: -Qipo -QxW -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxW -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxW -O3 -Qscalar_rep- +FDO ONESTEP=yes
177.mesa: -Qipo -QxW -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxW -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxW -Oa +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QxW -O3 -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -QxW -Oa ONESTEP=yes
189.lucas: -Qipo -QaxW
191.fma3d: basepeak=1
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL20p G2 (3.06GHz/1MB L3 cache, Intel Xeon)

SPECfp2000 = 1193  
SPECfp\_base2000 = 1160

SPEC license #: 3 | Test by: Hewlett-Packard Company, Houston TX | Test date: Aug-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

## Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO ONESTEP=yes  
301.apsi: -Qipo -QxW -O3 +FDO ONESTEP=yes