



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E6900 (24 processor)

SPECint_rate2000 = 337
SPECint_rate_base2000 = 295

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2003 Hardware Avail: Mar-2004 Software Avail: Apr-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	48	342	228	48	285	273
175.vpr	48	287	272	48	268	291
176.gcc	48	253	243	48	181	337
181.mcf	48	342	293	48	288	348
186.crafty	48	162	343	48	138	402
197.parser	48	351	286	48	308	325
252.eon	48	178	407	48	171	423
253.perlbnk	48	305	328	48	287	350
254.gap	48	417	147	48	332	184
255.vortex	48	213	496	48	192	552
256.bzip2	48	247	338	48	233	358
300.twolf	48	548	305	48	504	331

Hardware

CPU: UltraSPARC s400
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 48 cores, 24 chips, 2 cores/chip
CPU(s) orderable: 4-24 (multiples of 4 chips)
Parallel: No
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)
L3 Cache: None
Other Cache: None
Memory: 96GB 16-way interleaved
Disk Subsystem: Sun StorEdge S1 Disk Array (2x36GB)
Sun StorEdge T3 Array for the Workgroup (9x36GB)
Other Hardware: None

Software

Operating System: Solaris 9 04/04
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100

175.vpr: -fast -xalias_level=std -xipo=2
-Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm

176.gcc: -fast -xipo=2 -l12amm

181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1

186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E6900 (24 processor)

SPECint_rate2000 = 337
SPECint_rate_base2000 = 295

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2003 Hardware Avail: Mar-2004 Software Avail: Apr-2004

Notes/Tuning Information (Continued)

```

Feedback adds -xlinkopt in PASS2
197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk:-xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty:-DSUN
252.eon:   -library=iostream
253.perlbnk:-DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind

The system was configured with multiple file systems.
The O/S was installed on one disk of the Sun StorEdge S1
Disk Array (ufs, ufs w/logging). The benchmark was run on
the Sun StorEdge T3 Array, using H/W Raid 5 and ufs with
ufs logging file system.