



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Supermicro**  
X6DHP-8G (3.60 GHz Xeon, 1MB L2 Cache)

SPECfp\_rate2000 = 22.2  
SPECfp\_rate\_base2000 = 22.1

SPEC license #01176 | Tested by: Supermicro Inc., San Jose, CA | Test date: Jun-2004 | Hardware Avail: Jun-2004 | Software Avail: Dec-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	106	35.0	2	106	35.0
171.swim	2	323	22.3	2	323	22.3
172.mgrid	2	217	19.2	2	217	19.2
173.applu	2	280	17.4	2	278	17.5
177.mesa	2	91.4	35.5	2	91.9	35.3
178.galgel	2	209	32.1	2	209	32.1
179.art	2	507	11.9	2	507	11.9
183.quake	2	137	22.0	2	135	22.3
187.facerec	2	143	30.8	2	139	31.7
188.amp	2	277	18.4	2	277	18.4
189.lucas	2	216	21.5	2	216	21.5
191.fma3d	2	224	21.7	2	224	21.7
200.sixtrack	2	176	14.5	2	176	14.5
301.apsi	2	275	21.9	2	275	21.9

### Hardware

CPU: Intel Xeon (3.6GHz, 800 MHz system bus)  
CPU MHz: 3600  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (HT Technology enabled)  
CPU(s) orderable: 1, 2  
Parallel: No  
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip  
Secondary Cache: 1024KB(I+D) on chip  
L3 Cache: None  
Other Cache: N/A  
Memory: 6 x 1024MB ECC CL2.5 PC 2700 DDR SDRAM  
Disk Subsystem: 1 x 73GB U320 SCSI, 10K RPM  
Other Hardware:

### Software

Operating System: Windows 2003 Enterprise Server  
Compiler: Intel C/C++ Compiler 8.0 (20031229Z)  
Intel Fortran Compiler 8.0 (20031229Z)  
Microsoft Visual Studio .NET (7.0.9466)  
MicroQuill SmartHeap Library 7.1  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### PORTABILITY

178.galgel: -FI /F32000000

### FEEDBACK DIRECTED OPTIMIZATION

ONESTEP=YES

FDO: PASS1= -Qprof\_gen PASS2=-Qprof\_use

### BASE TUNING

C/F77/F90: -QxN -Qipo -O3 +FDO

### PEAK TUNING

168.wupwise: basepeak=yes

171.swim: basepeak=yes

172.mgrid: basepeak=yes

173.applu: -QxN -Qipo -O3 -Qscalar\_rep- -Qauto +FDO

177.mesa: -QxN -Qipo -O3 -Oa +FDO

178.galgel: basepeak=yes

179.art: -Qipo -Oa -Qunroll4 -Zp4

183.quake: -QxN -Qipo -O3 -Oa -Qrcd +FDO

187.facerec: -QaxN -Qipo -O3 -Qunroll1 -Qscalar\_rep- +FDO



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Supermicro  
X6DHP-8G (3.60 GHz Xeon, 1MB L2 Cache)

SPECfp\_rate2000 = 22.2

SPECfp\_rate\_base2000 = 22.1

SPEC license #01176 | Tested by: Supermicro Inc., San Jose, CA | Test date: Jun-2004 | Hardware Avail: Jun-2004 | Software Avail: Dec-2003

## Notes/Tuning Information (Continued)

188. ammp: basepeak=yes  
189. lucas: -QaxN -Qipo -O3  
191. fma3d: basepeak=yes  
200. sixtrack: basepeak=yes  
301. apsi: basepeak=yes