



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro  
X6DVL-EG2 (3.6GHz, Intel Xeon )

SPECfp2000 = 1544

SPECfp\_base2000 = 1519

SPEC license #01176 Tested by: Supermicro Test date: Apr-2005 Hardware Avail: Dec-2004 Software Avail: Aug-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	63.2	2532	63.8	2507	
171.swim	3100	155	2002	148	2094	
172.mgrid	1800	129	1397	126	1431	
173.applu	2100	147	1433	146	1440	
177.mesa	1400	87.8	1595	87.8	1595	
178.galgel	2900	131	2208	128	2265	
179.art	2600	112	2319	112	2319	
183.quake	1300	78.1	1665	78.1	1665	
187.facerec	1900	111	1719	109	1747	
188.ammp	2200	239	922	231	954	
189.lucas	2000	115	1739	110	1826	
191.fma3d	2100	152	1380	152	1380	
200.sixtrack	1100	170	646	169	651	
301.apsi	2600	254	1024	245	1060	

### Hardware

CPU: Intel Xeon processor (3.6 GHz, 800 MHz System bus )  
 CPU MHz: 3600  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)  
 CPU(s) orderable: 1  
 Parallel: No  
 Primary Cache: 12k micro-ops I + 16KBD on chip  
 Secondary Cache: 1024KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x1GB DDR2-400 REG ECC CL3  
 Disk Subsystem: 1x40GB IDE  
 Other Hardware:

### Software

Operating System: Windows Server 2003 EE  
 Compiler: Intel C++ and Fortran Compiler 8.1 Build 20040802Z  
 Microsoft Visual Studio .Net 2003(for libraries)  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -fast -Qansi_alias +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.ammp: -Oa -QxP
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro  
X6DVL-EG2 (3.6GHz, Intel Xeon )

SPECfp2000 =	1544
SPECfp_base2000 =	1519

SPEC license #01176	Tested by: Supermicro	Test date: Apr-2005	Hardware Avail: Dec-2004	Software Avail: Aug-2004
---------------------	-----------------------	---------------------	--------------------------	--------------------------

## Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

The system bus runs at 800 MHz

Tested system can be used with a 420W (minimum) ATX power supply [8-pin (+12V) and 24-pin are required]