



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER850 (2025MHz)

SPECint_rate2000 = 247
SPECint_rate_base2000 = 225

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Apr-2005 Hardware Avail: Jun-2005 Software Avail: Apr-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	145	179	16	138	188
175.vpr	16	127	205	16	125	209
176.gcc	16	148	138	16	82.0	249
181.mcf	16	175	190	16	152	220
186.crafty	16	77.0	241	16	71.3	260
197.parser	16	158	211	16	147	228
252.eon	16	88.0	274	16	87.2	277
253.perlbnk	16	135	248	16	133	251
254.gap	16	108	189	16	105	195
255.vortex	16	80.8	437	16	78.4	450
256.bzip2	16	128	217	16	124	225
300.twolf	16	202	275	16	184	302

Hardware

CPU: SPARC64 V
CPU MHz: 2025
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 1 to 16 (increments of 1)
Parallel: None
Primary Cache: 128KBI + 128KBD on chip
Secondary Cache: 3MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 32768MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 9 4/04
Compiler: (C/C++)
Fujitsu Parallelnavi 2.3 with patch 913287-01
Sun Studio 9
File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (for Parallelnavi 2.3)
fdo_pre0=rm -rf `pwd`/*.f.d
PASS1=-Kpg
PASS2=-Kpu=$(EXEBASE).fbk
FDO: (for Sun Studio 9)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Integer base flags:
(using C compiler of Sun Studio 9)
-fast -xtarget=ultra3cu -xipo=2 ONESTEP=yes FDO
(using C++ compiler of Sun Studio 9)
-fast -xipo=2 ONESTEP=yes FDO
```

```
Integer peak flags:
(using C compiler of Parallelnavi 2.3)
300.twolf: -Kfast_GP2=3,GREG,eval,preex,cfunc -O3 ONESTEP=yes FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER850 (2025MHz)

SPECint_rate2000 = 247
SPECint_rate_base2000 = 225

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Apr-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

(using C compiler of Sun Studio 9)

164.gzip: -xarch=v8plusb -xchip=ultra2 -xcache=128/64/2:4096/64/4
-xalias_level=std -xipo=2 -W2,-whole -xO5 ONESTEP=yes FDO

175.vpr: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=std -xchip=ultra2 -xipo=2 ONESTEP=yes FDO

176.gcc: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -l12amm ONESTEP=yes FDO

181.mcf: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xprefetch_level=3 -W2,-Apf:l1list=3:noinnerl1list
ONESTEP=yes FDO

186.crafty: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -xipo=2 -xpagesize=512K -W2,-Ashort_ldst
ONESTEP=yes FDO

197.parser: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -xipo=2 -xregs=syst -Wc,-Qgsched-T6,
-Qgsched-trace_late=1,-Qipa:valueprediction ONESTEP=yes FDO

253.perlbnk: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xalias_level=std ONESTEP=yes FDO

254.gap: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -xipo=2 -xprefetch_level=3 -xvector
-W2,-Abcopy ONESTEP=yes FDO

255.vortex: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xrestrict -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
-Wc,-Qdepgraph-early_cross_call=1 -l12amm ONESTEP=yes FDO

256.bzip2: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xalias_level=strong -xrestrict ONESTEP=yes FDO

(using C++ compiler of Sun Studio 9)

252.eon: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-noex -xalias_level=compatible -xipo=2
-Qoption cg -Qeps:enabled=1,-Qeps:ws=32 ONESTEP=yes FDO

Portability:

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN

186.crafty: -DSUN

252.eon: -library=iostream

253.perlbnk: -DSPEC_CPU2000_SOLARIS

254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
-DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

System Tunables:

(for /etc/system)

```
set consistent_coloring=1
set tune_t_fsflushr=86400
set autoup=86400
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1
```

Processes were bound to CPUs using "submit=pbind"

Extended Interleave Mode enabled.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER850 (2025MHz)

SPECint_rate2000 = 247

SPECint_rate_base2000 = 225

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Apr-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

Sun Studio 9, posted at URL <http://www.sun.com/software/products/studio/previous/9/index.xml> was used for this submission.