



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro H8DA8 (AMD Opteron (TM) 252)

SPECint2000 = 1777
SPECint_base2000 = 1656

SPEC license #01176 Tested by: Supermicro Test date: May-2005 Hardware Avail: Mar-2005 Software Avail: Jul-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	97.7	1433	97.7	1433	
175.vpr	1400	103	1362	98.8	1417	
176.gcc	1100	58.8	1872	58.2	1889	
181.mcf	1800	177	1016	139	1292	
186.crafty	1000	59.8	1674	54.0	1852	
197.parser	1800	114	1585	112	1605	
252.eon	1300	53.4	2433	46.7	2785	
253.perlbnk	1800	106	1704	106	1704	
254.gap	1100	60.5	1819	60.5	1819	
255.vortex	1900	76.2	2493	69.5	2732	
256.bzip2	1500	112	1341	110	1365	
300.twolf	3000	175	1714	143	2092	

Hardware

CPU: AMD Opteron (TM) 252
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 1024MB PC3200 REG ECC CL3 DDR SDRAM
 Disk Subsystem: 1 X 300GB IDE
 Other Hardware: None

Software

Operating System: Windows Enterprise Server 2003
 Compiler: Intel C++ 8.0 build 20040714Z
 Microsoft Visual Studio .NET 7.0.9466 (libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

Tested by Supermicro

shlw32M7.lib is the SmartHeap library V7.0 from MicroQuill www.microquill.com
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -fast -arch:SSE2 -Oi- +FDO

Baseline C++: -fast -arch:SSE2 -GX -GR

Peak Tuning:

164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 +FDO
 -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
 176.gcc: -fast -arch:SSE2 +FDO -Oi- -Qunroll3
 181.mcf: -fast -QaxN +FDO
 186.crafty: -fast -arch:SSE2 +FDO
 197.parser: -arch:SSE2 +FDO -Oi- -Qipo
 252.eon: -fast -arch:SSE2 +FDO -Qansi_alias
 -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
H8DA8 (AMD Opteron (TM) 252)

SPECint2000 = 1777
SPECint_base2000 = 1656

SPEC license #01176 | Tested by: Supermicro | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Jul-2004

Notes/Tuning Information (Continued)

```
253.perlbnk: basepeak=yes
254.gap:      basepeak=yes
255.vortex:   -fast -arch:SSE +FDO -Oi- shlw32m7.lib
              -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
256.bzip2:   -fast -Qunroll2
300.twolf:   -fast -arch:SSE2 +FDO -Qunroll3 shlw32m7.lib -Qansi_alias
Tested system can be used with a 420W (minimum) ATX power supply
```