



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

PDSGE/4 Motherboard(Intel Pentium Extreme Edition 3.2GHz)

SPECfp_rate2000 = 30.1

SPECfp_rate_base2000 = 30.1

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	132	56.2	4	132	56.3
171.swim	4	455	31.6	4	456	31.5
172.mgrid	4	381	21.9	4	382	21.9
173.applu	4	346	28.2	4	340	28.7
177.mesa	4	190	34.1	4	190	34.1
178.galgel	4	340	39.6	4	341	39.5
179.art	4	383	31.5	4	383	31.5
183.quake	4	198	30.4	4	201	29.9
187.facerec	4	213	41.4	4	214	41.3
188.amp	4	557	18.3	4	554	18.4
189.lucas	4	305	30.4	4	309	30.0
191.fma3d	4	331	29.4	4	331	29.4
200.sixtrack	4	288	17.7	4	286	17.9
301.apsi	4	410	29.4	4	414	29.1

Hardware

CPU: Intel Pentium Extreme Edition 3.2GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip(Hyper-Threading Technology Enabled)
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512MB DDR2-667 ECC Unbuffered
 Disk Subsystem: 1x400GB SATA
 Other Hardware: N/A

Software

Operating System: Windows 2000 AS SP4
 Compiler: Intel C++ and Fortran Compiler 8.1 Build 20040802Z
 Microsoft Visual Studio .Net 2002(for libraries)
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -fast -Qansi_alias +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -Oa -QxP
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

PDSGE/4 Motherboard(Intel Pentium Extreme Edition 3.2GHz)

SPECfp_rate2000 = 30.1

SPECfp_rate_base2000 = 30.1

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested system was built with SC733T-645 chassis and

a 420W (minimum) ATX power supply [4-pin +12V AND (20 or 24-pin)] is required.

See: <http://www.supermicro.com/products/motherboard/DualCore/955/PDSGE.cfm>

The system bus runs at 800 MHz