



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM
4812-001 (2.0 GHz Pentium M)

SPECint_rate2000 = 16.6
SPECint_rate_base2000 = 16.5

SPEC license #: 11 | Tested by: IBM, Rochester, MN | Test date: Aug-2004 | Hardware Avail: Oct-2004 | Software Avail: Oct-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	497	13.1	4	497	13.1
175.vpr	4	443	14.7	4	443	14.7
176.gcc	4	262	19.5	4	262	19.5
181.mcf	4	768	10.9	4	768	10.9
186.crafty	4	291	15.9	4	291	16.0
197.parser	4	558	15.0	4	558	15.0
252.eon	4	303	19.9	4	282	21.4
253.perlbnk	4	486	17.2	4	487	17.1
254.gap	4	327	15.6	4	327	15.6
255.vortex	4	331	26.6	4	331	26.6
256.bzip2	4	559	12.4	4	537	13.0
300.twolf	4	592	23.5	4	592	23.5

Hardware

CPU: Intel Pentium M
400/200 Mhz System/Memory buses
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32K(I) micro-ops + 32KB(D) on chip
Secondary Cache: 2MB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 1 x 1024MB DDR200 Registered ECC
Disk Subsystem: 1 iSeries 2757-001 Disk IOA,
16 x 35.18GB 3516 15k RPM, unprotected.
Other Hardware: 4812 attached within
iSeries 9406-810, cpu 25F0-000

Software

Operating System: Windows Server 2003 Standard Edition Build 3790
Compiler: Intel C++ Compiler 8.0 (20031017Z)
Microsoft Visual Studio .NET (7.0.9466)
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK DIRECTED OPTIMIZATION

ONESTEP=yes

BASE TUNING

C: -QxW -Qipo -O3 +FDO
C++: -QxW -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxW -Qipo -Oa -O3 +FDO
175.vpr: -QxW -Qipo -O3 +FDO
176.gcc: -QxW -Qipo -O3 +FDO
181.mcf: -QxW -Qipo -O3 +FDO
186.crafty: -QxW -Qipo -O3 +FDO
197.parser: -QxW -Qipo -O3 +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM
4812-001 (2.0 GHz Pentium M)

SPECint_rate2000 = 16.6
SPECint_rate_base2000 = 16.5

SPEC license #: 11 | Tested by: IBM, Rochester, MN | Test date: Aug-2004 | Hardware Avail: Oct-2004 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```
252.eon:      -QxW -Qipo      -O3 +FDO
253.perlbnk:  -QxW -Qipo      -O3 +FDO
254.gap:      basepeak=yes
255.vortex    basepeak=yes
256.bzip2:    -Qipo -Oa -Qunroll1 +FDO
300.twolf:    basepeak=yes
```

EXTRA LIBRARIES

This system is a fully contained Intel based processor board. It supports all non-PCI devices directly on the board e.g memory, keyboard, mouse, display. It attaches to the system as another PCI device. The Windows OS is provided PCI device drivers to allow the system to use the PCI devices attached to the host iSeries system. The host OS then supports the use by Windows of the devices such as disks.

More information about the xSeries board in iSeries systems can be found at <http://www.ibm.com/servers/eserver/iseries/library> In particular, there is a Redbook available titled: "Microsoft Windows Server 2003 Integration with iSeries" that provides lots more detailed information.