



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

X6DHP-8G Motherboard(Intel Xeon 3.0GHz 2M Cache)

SPECfp_rate2000 = 25.6

SPECfp_rate_base2000 = 25.0

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	167	44.5	4	163	45.5
171.swim	4	688	20.9	4	660	21.8
172.mgrid	4	442	18.9	4	424	19.7
173.applu	4	476	20.5	4	455	21.4
177.mesa	4	210	31.0	4	210	31.0
178.galgel	4	353	38.1	4	344	39.1
179.art	4	400	30.2	4	400	30.2
183.quake	4	286	21.1	4	277	21.8
187.facerec	4	260	34.0	4	253	34.8
188.amp	4	464	22.0	4	444	23.0
189.lucas	4	455	20.4	4	438	21.2
191.fma3d	4	469	20.8	4	469	20.8
200.sixtrack	4	308	16.6	4	306	16.7
301.apsi	4	465	26.0	4	462	26.1

Hardware

CPU: Intel Xeon 3.0GHz
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Enabled)
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2 X 1GB DDR 333 REG ECC
Disk Subsystem: WD 74GB 10000RPM SATA
Other Hardware:

Software

Operating System: Windows 2003 Enterprise Edition
Compiler: Intel C++ and Fortran Compiler 8.1 Build 20040802Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -fast -Qansi_alias +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -Oa -QxP
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

X6DHP-8G Motherboard(Intel Xeon 3.0GHz 2M Cache)

SPECfp_rate2000 = 25.6

SPECfp_rate_base2000 = 25.0

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested system configuration used an SC814 Series chassis

with a 420W (minimum) ATX power supply [8-pin (+12V) and 24-pin are required]

See <http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHP-8G.cfm>

The system bus runs at 800 MHz