



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro PDSMP-8/i Motherboard

SPECint_rate2000 = 32.6
SPECint_rate_base2000 = 32.7

SPEC license #01176 | Tested by: Supermicro | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	133	24.5	2	134	24.3
175.vpr	2	155	20.9	2	152	21.3
176.gcc	2	64.3	39.7	2	64.3	39.7
181.mcf	2	164	25.4	2	164	25.4
186.crafty	2	85.3	27.2	2	85.9	27.0
197.parser	2	145	28.8	2	144	29.0
252.eon	2	65.2	46.3	2	65.3	46.2
253.perlbnk	2	94.5	44.2	2	98.6	42.4
254.gap	2	68.6	37.2	2	68.6	37.2
255.vortex	2	77.4	56.9	2	77.4	56.9
256.bzip2	2	145	24.0	2	147	23.6
300.twolf	2	194	35.8	2	192	36.2

Hardware

CPU: Intel Pentium D 840 Processor (3.2GHz, 800 MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD/core on chip
Secondary Cache: 1024KB/core on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 X 1024MB DDR2-667 ECC Unbuffered
Disk Subsystem: 1 X IDE Maxtor DiamondMax Plus 9 250GB
Other Hardware: N/A

Software

Operating System: Windows 2003 Enterprise Server
Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
PDSMP-8/i Motherboard

SPECint_rate2000 = 32.6
SPECint_rate_base2000 = 32.7

SPEC license #01176 | Tested by: Supermicro | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M.lib

New 32-bit Windows tools used, approved in May-2005

Tested system was built with 1U SC816S-400 -Redundant Power Supply. Use only with Supermicro 1U chassis recommended

Product description located as of:

<http://www.supermicro.com/products/motherboard/DualCore/E7230/PDSMP-8.cfm>

The system bus runs at 800MHz