



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 254

SPECfp_rate2000 = 19.4
SPECfp_rate_base2000 = 19.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Sep-2005 | Hardware Avail: Nov-2005 | Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	60.2	30.8	1	60.2	30.8
171.swim	1	168	21.4	1	168	21.4
172.mgrid	1	115	18.2	1	115	18.2
173.applu	1	158	15.4	1	158	15.4
177.mesa	1	130	12.5	1	130	12.5
178.galgel	1	106	31.9	1	106	31.9
179.art	1	63.4	47.6	1	63.4	47.6
183.quake	1	83.8	18.0	1	83.8	18.0
187.facerec	1	102	21.7	1	102	21.7
188.amp	1	186	13.7	1	186	13.7
189.lucas	1	128	18.2	1	128	18.2
191.fma3d	1	138	17.7	1	138	17.7
200.sixtrack	1	130	9.78	1	130	9.78
301.apsi	1	173	17.4	1	173	17.4

Hardware

CPU: AMD Opteron (TM) 254 processor (2.80 GHz)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB (I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB DDR-RAM PC3200R
Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: PGI Fortran compiler 6.0-4 for Windows XP, PGI C compiler 6.0-4 for Windows XP
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Mpfi PASS2=-Mpfo
ONESTEP is set to 1 for every compile with the PGI compilers.

Portability flags

178.galgel: -Mfixed

Base tuning flags

for Fortran programs: -fastsse -Mipa=fast,inline +FDO
for C programs: -fastsse -Mipa=fast,inline

Peak tuning flags

same as baseline (basepeak=yes set globally)

boot options: /NoExecute=alwaysoff



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 254

SPECfp_rate2000 = 19.4

SPECfp_rate_base2000 = 19.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Sep-2005 | Hardware Avail: Nov-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>