



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 2850 (3.8GHz Intel Xeon)

SPECint2000 = **1764**
SPECint_base2000 = **1744**

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Aug-2005 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	111	1261	112	1254	
175.vpr	1400	114	1228	114	1228	
176.gcc	1100	52.9	2080	52.9	2080	
181.mcf	1800	95.6	1883	95.6	1883	
186.crafty	1000	72.2	1385	71.4	1401	
197.parser	1800	118	1524	118	1524	
252.eon	1300	54.7	2375	55.0	2363	
253.perlbmk	1800	92.3	1950	81.4	2212	
254.gap	1100	55.5	1980	55.5	1980	
255.vortex	1900	69.3	2742	69.3	2744	
256.bzip2	1500	114	1312	114	1316	
300.twolf	3000	160	1873	159	1890	

Hardware

CPU: Intel Xeon (3.8GHz, 2MB L2, 800MHz system bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2GB (dual-ranked) ECC 400MHz DDR2 SDRAM
Disk Subsystem: 1 x 36GB 15000RPM SCSI
Other Hardware: None

Software

Operating System: Windows Server 2003, Standard Edition, Service Pack 1
Compiler: Intel C/C++ Compiler 8.1 for IA32 (20041119Z)
Microsoft Visual Studio .NET 2003(7.1.3088, for libraries)
MicroQuill SmartHeap Library 7.1
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: srcalt=stdcpp
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: basepeak=yes
252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 2850 (3.8GHz Intel Xeon)

SPECint2000 =	1764
SPECint_base2000 =	1744

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Aug-2005 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap:      basepeak=yes
255.vortex   -fast +FDO
256.bzip2:   -fast -Qunroll11 -Oa +FDO
300.twolf:   -fast +FDO shlw32M.lib
```