



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Supermicro X6DAE/8-G2 Motherboard

SPECint\_rate2000 = 42.4  
SPECint\_rate\_base2000 = 42.4

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Nov-2004 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	170	38.1	4	173	37.5
175.vpr	4	241	27.0	4	236	27.5
176.gcc	4	89.5	57.0	4	89.5	57.0
181.mcf	4	343	24.3	4	343	24.3
186.crafty	4	138	33.7	4	137	33.8
197.parser	4	199	42.0	4	198	42.2
252.eon	4	110	54.9	4	110	54.7
253.perlbnk	4	172	48.5	4	173	48.2
254.gap	4	109	46.7	4	109	46.7
255.vortex	4	127	69.4	4	127	69.4
256.bzip2	4	192	36.2	4	191	36.4
300.twolf	4	264	52.8	4	263	53.0

### Hardware

CPU: Intel Xeon 3.8GHz processor (3.8 GHz, 2MB L2, 800 MHz bus)  
CPU MHz: 3800  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Enabled)  
CPU(s) orderable: 1, 2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8GB (8x1GB DDR2 400 ECC REG)  
Disk Subsystem: 1 X 40GB IDE  
Other Hardware: N/A

### Software

Operating System: Windows 2003 EE SP1  
Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)  
Microsoft Visual Studio .Net 2003(for libraries)  
SmartHeap Library Version 7.4 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDDL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro  
X6DAE/8-G2 Motherboard

SPECint\_rate2000 = 42.4

SPECint\_rate\_base2000 = 42.4

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Nov-2004 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

255.vortex basepeak=yes  
256.bzip2: -fast -Oa -Qunroll1 +FDO  
300.twolf: -fast -O3 +FDO shlw32M.lib  
New 32-bit Windows tools used, approved in May-2005  
Tested system was built with SC743S1-645 - Low Noise Chassis.  
Product description located as of:  
<http://www.supermicro.com/products/motherboard/Xeon800/E7525/X6DA8-G2.cfm>  
The system bus runs at 800MHz