



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S2, Intel Xeon processor 3.40GHz, 2MB L2

SPECint2000 = 1627

SPECint_base2000 = 1627

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Sep-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	124	1132	124	1132
175.vpr	1400	125	1121	125	1121
176.gcc	1100	56.3	1954	56.3	1954
181.mcf	1800	98.1	1834	98.1	1834
186.crafy	1000	79.6	1256	79.6	1256
197.parser	1800	129	1396	129	1396
252.eon	1300	64.6	2012	64.6	2012
253.perlbnk	1800	89.8	2004	89.8	2004
254.gap	1100	60.4	1820	60.4	1820
255.vortex	1900	69.2	2744	69.2	2744
256.bzip2	1500	121	1243	121	1243
300.twolf	3000	174	1729	174	1729

Hardware

CPU: Intel Xeon processor 3.40GHz, 2MB L2, 800MHz system bus
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x512 MB DDRII-RAM PC2-3200R
Disk Subsystem: Seagate ST336753LC(U320 SCSI, 15krpm)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ Compiler 9.0
Build 20050722Z (for 32-bit applications)
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries)
SmartHeap Library Version 7.4
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: Approved srcalt stdcpp is used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX200 S2, Intel Xeon processor 3.40GHz, 2MB L2

SPECint2000 =	1627
SPECint_base2000 =	1627

SPEC license #:	22	Tested by:	Fujitsu Siemens Computers	Test date:	Nov-2005	Hardware Avail:	Oct-2005	Software Avail:	Sep-2005
-----------------	----	------------	---------------------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>