



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM

IBM eServer 326m, 2.2 GHz Dual Core AMD Opteron(tm) Processor 275

SPECfp\_rate2000 = 70.2

SPECfp\_rate\_base2000 = 63.9

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	74.8	99.3	4	70.3	106
171.swim	4	250	57.5	4	247	58.3
172.mgrid	4	162	51.6	4	158	52.7
173.applu	4	140	69.8	4	128	75.9
177.mesa	4	96.5	67.3	4	74.4	87.3
178.galgel	4	130	103	4	124	109
179.art	4	142	85.1	4	98.8	122
183.equake	4	121	49.8	4	109	55.1
187.facerec	4	103	85.7	4	98.2	89.8
188.amp	4	170	59.9	4	162	63.0
189.lucas	4	161	57.7	4	157	59.0
191.fma3d	4	181	53.8	4	174	55.9
200.sixtrack	4	172	29.7	4	143	35.8
301.apsi	4	185	65.2	4	181	66.8

### Hardware

CPU: Dual Core AMD Opteron(tm) Processor 275  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 1024GB PC3200  
 Disk Subsystem: SCSI, 36GB 15K RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SP2 SLES 64 bit Kernel 2.6.5-7.191-smp (SP2)  
 Compiler: PathScale EKO Compiler Suite, Release 2.2.1  
 AMD Core Math Library 2.5.1  
 File System: Linux/reiserfs  
 System State: Multi-user, run level 3

## Notes/Tuning Information

Tested by IBM Corporation

+ACML: Linked with AMD Core Math Library

Base tuning for C programs: -Ofast -WOPT:mem\_opnds=on +FDO

Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex +FDO

Portability flags:

178.galgel: -fixedform

Peak tuning:

168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3

-OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3

-IPA:linear=on:plimit=50000:callee\_limit=5000

-INLINE:aggressive=on

171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnw

172.mgrid: -Ofast -CG:gcm=off:cflow=on -OPT:IEEE\_a=3:unroll\_size=200

-LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2

-WOPT:memopnds=on:aggstr=0

173.applu: -Ofast -CG:local\_fwd\_sched=on -OPT:ro=3 -TENV:X=3

-LNO:fusion=2:fission=2:full\_unroll\_size=10000:prefetch=3 +FDO

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM

IBM eServer 326m, 2.2 GHz Dual Core AMD Opteron(tm) Processor 275

SPECfp\_rate2000 = 70.2

SPECfp\_rate\_base2000 = 63.9

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Nov-2005

### Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex +ACML +FDO
179.art:       -O3 -OPT:ofast -fno-math-errno -mno-sse2 -m32
183.earthquake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:   -Ofast -LNO:fusion=2
               -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.amp:       -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
               -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
189.lucas:     -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:memopnds=on +FDO
191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
               -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack:  -O3 -OPT:Ofast:Olimit=60000:early_intrinsics=on
               -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:      -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2
BIOS Configuration Notes
Node Interleaving is Disabled
Other Configuration Notes
Taskset utility used to bind process to CPU(s)

```