



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL145 G2 (AMD Opteron (TM) 254)

SPECint2000 = 1921
SPECint_base2000 = 1829

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Dec-2005 Hardware Avail: Sep-2005 Software Avail: Nov-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	90.9	1541	90.9	1541				
175.vpr	1400	94.5	1481	91.5	1530				
176.gcc	1100	54.0	2036	53.7	2048				
181.mcf	1800	151	1194	126	1426				
186.crafty	1000	54.5	1834	49.7	2011				
197.parser	1800	104	1734	104	1736				
252.eon	1300	46.3	2805	42.4	3064				
253.perlbnk	1800	95.5	1885	95.5	1885				
254.gap	1100	56.5	1948	56.5	1948				
255.vortex	1900	67.5	2814	67.9	2799				
256.bzip2	1500	103	1459	101	1482				
300.twolf	3000	160	1874	133	2258				

Hardware

CPU: AMD Opteron (TM) 254
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC3200 CL3.0
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler 8.0 Build 20040318Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -fast -QaxN +FDO ONESTEP=yes
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL145 G2 (AMD Opteron (TM) 254)

SPECint2000 =	1921
SPECint_base2000 =	1829

SPEC license #:	3	Tested by:	Hewlett-Packard Company	Test date:	Dec-2005	Hardware Avail:	Sep-2005	Software Avail:	Nov-2005
-----------------	---	------------	-------------------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2:  -fast -Qunroll2
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
BIOS Configuration Notes
Node Interleaving Disabled
```