



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Acer Incorporated

Acer Altos R510 Mk2 (3.8 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECint\_rate2000 = 22.8

SPECint\_rate\_base2000 = 22.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Dec-2005 | Hardware Avail: Jan-2006 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	167	19.4	2	167	19.4
175.vpr	2	219	14.8	2	214	15.2
176.gcc	2	85.4	29.9	2	85.4	29.9
181.mcf	2	210	19.9	2	210	19.9
186.crafty	2	141	16.5	2	141	16.5
197.parser	2	193	21.6	2	192	21.7
252.eon	2	112	27.0	2	112	26.9
253.perlbnk	2	171	24.5	2	171	24.4
254.gap	2	98.1	26.0	2	98.1	26.0
255.vortex	2	121	36.3	2	121	36.3
256.bzip2	2	182	19.1	2	182	19.2
300.twolf	2	259	26.9	2	260	26.8

### Hardware

CPU: Intel Xeon (3.8 GHz, 2MB L2, 800MHz system bus)  
CPU MHz: 3800  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology Enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 6 x 512MB ECC DDR2-400 SDRAM  
Disk Subsystem: 1 x 160GB 7200RPM SATA HDD  
Other Hardware:

### Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)  
Compiler: Intel C++ Compiler 9.0 Build 20050430Z for IA32  
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)  
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Acer Incorporated**

Acer Altos R510 Mk2 (3.8 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECint\_rate2000 = 22.8

SPECint\_rate\_base2000 = 22.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Dec-2005 | Hardware Avail: Jan-2006 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO  
300.twolf: -fast +FDO shlw32M.lib  
Enable hardware prefetching and adjacent cache line prefetch BIOS setting  
Product description located at <http://www.acer.com>