



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 550 (1650 MHz, 4 CPU)

SPECint_rate2000 = 69.0
SPECint_rate_base2000 = 68.1

SPEC license #: 11 | Tested by: IBM | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	279	46.6	8	277	46.8
175.vpr	8	224	58.1	8	219	59.3
176.gcc	8	140	72.7	8	139	73.3
181.mcf	8	171	97.8	8	197	84.7
186.crafty	8	173	53.5	8	147	63.2
197.parser	8	254	65.7	8	258	64.9
252.eon	8	149	81.1	8	149	81.1
253.perlbnk	8	317	52.7	8	306	54.6
254.gap	8	153	66.9	8	152	67.3
255.vortex	8	159	111	8	154	115
256.bzip2	8	191	72.7	8	184	75.7
300.twolf	8	437	63.7	8	435	64.0

Hardware

CPU: POWER5+
 CPU MHz: 1650
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (SMT on)
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 64KBI+32KBD (on chip)/core
 Secondary Cache: 1920KB unified, shared (on chip)/chip
 L3 Cache: 36MB unified (off-chip)/DCM, 2 DCMs/SUT
 Other Cache: None
 Memory: 8x4GB
 Disk Subsystem: 2x73GB SCSI, 15K RPM
 Other Hardware: None

Software

Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
 File System: AIX/JFS2
 System State: Multi-user

Notes/Tuning Information

Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
253.perlbnk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

Base Optimization Flags:

```
C: -qpdf1/pdf2
   -O5 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
      -O4 -qalign=natural
```

Peak Optimization Flags

```
164.gzip: -qpdf1/pdf2
          -O4 -qfdpr -blpdata
          fdpr -q -O3
175.vpr: -qpdf1/pdf2
         -O5 -qfdpr -blpdata
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 550 (1650 MHz, 4 CPU)

SPECint_rate2000 = 69.0
SPECint_rate_base2000 = 68.1

SPEC license #: 11 | Tested by: IBM | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)

```

176.gcc:      fdpr -q -O3
              -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
181.mcf:      -qpdf1/pdf2
              -O4 -qalign=natural -blpdata
186.crafty:   -qpdf1/pdf2
              -O4 -qalign=natural -q64 -lhm -blpdata
197.parser:   -qpdf1/pdf2
              -O4 -qfdpr -D_ILS_MACROS -blpdata
              fdpr -q -O3
252.eon:      -qpdf1/pdf2
              -O4 -qalign=natural
253.perlbnk:  -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhm
254.gap:      -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
255.vortex:   -qpdf1/pdf2
              -O4 -qfdpr -lhm -blpdata
              fdpr -q -O3
256.bzip2:    -qpdf1/pdf2
              -O5 -qfdpr -blpdata
              fdpr -q -O3
300.twolf:    -O5 -qfdpr -blpdata
              fdpr -q -O3

```

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Technology Level.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

SUT: Acronym for "System Under Test"

Extended C: IBM XL C for AIX invoked as cc
C++: IBM XL C for AIX invoked as xlc

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=800 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \$$ \$$SPECUSERNUM; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.