



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
H8DSL-HTi Motherboard (AMD Opteron (TM) 254)

SPECfp2000 = **1946**
SPECfp_base2000 = **1784**

SPEC license #01176 | Tested by: Supermicro | Test date: Apr-2006 | Hardware Avail: Apr-2006 | Software Avail: Oct-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	57.3	2792	57.9	2765	
171.swim	3100	139	2224	135	2303	
172.mgrid	1800	107	1677	107	1677	
173.applu	2100	141	1485	131	1598	
177.mesa	1400	131	1072	63.8	2195	
178.galgel	2900	97.3	2981	91.0	3187	
179.art	2600	58.9	4414	58.9	4414	
183.quake	1300	77.4	1679	76.7	1694	
187.facerec	1900	93.4	2034	93.4	2034	
188.amp	2200	179	1228	149	1481	
189.lucas	2000	110	1810	98.1	2039	
191.fma3d	2100	131	1608	129	1634	
200.sixtrack	1100	130	845	130	847	
301.apsi	2600	177	1473	177	1470	

Hardware

CPU: AMD Opteron (TM) 254
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: no
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB (I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 X Apacer 78.A1071.404, 2GB DDR-400 CL3 ECC Reg
Disk Subsystem: 1 X IDE, Seagate ST3250823A 250GB
Other Hardware: None

Software

Operating System: Windows server 2003 Enterprise Edition 32-bit Version w/ Service Pack 1
Compiler: Intel C++ 9.0 build 20050912Z for IA32, Intel Fortran 9.0 build 20050912Z for IA32, Microsoft Visual Studio .NET 2003 7.0.9466 (libraries) PGI Fortran compiler 6.0-5 for Windows XP, PGI C compiler 6.0-5 for Windows XP, ACML Version 2.5.3 (bundled with PGI 6.0-5)
File System: NTFS
System State: default

Notes/Tuning Information

```
+FDO:
    icl, ifort  : PASS1=-Qprof_gen  PASS2=-Qprof_use
    pgf90      : PASS1=-Mpfi       PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel:                               -Mfixed
Baseline: C      : pgcc                   -fastsse -Mipa=fast,inline
Baseline: Fortran: pgf90                  -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise:   pgf90                      -fastsse -Mipa=fast,inline -Mvect
171.swim:      ifort                       -Qipo -O3 -QaxN -QxW -Qunroll0 +FDO
172.mgrid:     pgf90                      -fastsse -Mipa=fast,inline
173.applu:     ifort                       -Qipo -O3 -QaxN -QxW -auto +FDO
177.mesa:      icl                         -Qipo -QxW -Qunroll1 -Qansi_alias +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
H8DSL-HTi Motherboard (AMD Opteron (TM) 254)

SPECfp2000 = 1946
SPECfp_base2000 = 1784

SPEC license #01176 | Tested by: Supermicro | Test date: Apr-2006 | Hardware Avail: Apr-2006 | Software Avail: Oct-2005

Notes/Tuning Information (Continued)

```

-Option,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:      pgf90  -fastsse -Mipa=fast,safe -Munix -lacml
                  RM_SOURCES=lapak.f90
179.art:         pgcc   basepeak=yes
183.quake:      icl    -O3 -Qipo -QxW +FDO
187.facerec:    pgf90  basepeak=1
188.ampp:       icl    -Oa  -QxW  -Zp4 -Qansi_alias
189.lucas:      ifort  -Qipo -QxW -Qunroll1
191.fma3d:      pgf90  -Mipa=fast,inline -fastsse -Mnovect +FDO
200.sixtrack:  pgf90  -fastsse -Mipa=fast,inline
301.apsi:       pgf90  -fastsse -Mipa=fast,inline

```

Tested system was built with chassis SC813T-500C,
Product description located as of:

<http://www.supermicro.com/Aplus/motherboard/Opteron/HT1000/H8DSL-HTi.cfm>

To ensure system stability, a 420W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]

Other Configuration Notes

The start /b /wait /affinity command is used to bind CPU(s) to processes.