



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5060 processor, 3.20 GHz

SPECfp_rate2000 = 60.8

SPECfp_rate_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Mar-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	79.8	93.0	4	79.8	93.0
171.swim	4	294	49.0	4	294	49.0
172.mgrid	4	185	45.1	4	185	45.1
173.applu	4	212	45.9	4	212	45.9
177.mesa	4	85.0	76.5	4	85.0	76.5
178.galgel	4	103	131	4	103	131
179.art	4	69.8	173	4	69.8	173
183.quake	4	135	44.7	4	135	44.7
187.facerec	4	134	66.0	4	134	66.0
188.amp	4	183	55.7	4	183	55.7
189.lucas	4	199	46.7	4	199	46.7
191.fma3d	4	193	50.4	4	193	50.4
200.sixtrack	4	174	29.3	4	174	29.3
301.apsi	4	236	51.2	4	236	51.2

Hardware

CPU: Intel Xeon 5060 processor (3.20 GHz, 2x2MB L2, 1066 MHz system bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDRII-RAM PC2-4200F (CAS 4-4-4)
Disk Subsystem: Seagate ST936701SS (SAS, 10 krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5060 processor, 3.20 GHz

SPECfp_rate2000 = 60.8

SPECfp_rate_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Mar-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>