



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Acer Altos R910 (3.0 GHz Intel Xeon Processor 7041)

SPECfp_rate2000 = **45.9**
SPECfp_rate_base2000 = **45.9**

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Jun-2006 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	112	66.2	4	112	66.3
171.swim	4	394	36.5	4	394	36.5
172.mgrid	4	246	34.0	4	246	34.0
173.applu	4	272	35.8	4	272	35.8
177.mesa	4	113	57.4	4	113	57.4
178.galgel	4	117	115	4	117	115
179.art	4	149	81.2	4	149	81.2
183.quake	4	154	39.3	4	154	39.3
187.facerec	4	178	49.6	4	178	49.6
188.amp	4	273	37.3	4	267	38.3
189.lucas	4	259	35.8	4	261	35.6
191.fma3d	4	260	37.5	4	260	37.5
200.sixtrack	4	190	26.9	4	191	26.8
301.apsi	4	273	44.1	4	274	44.1

Hardware

CPU: Intel Xeon Processor 7041 (3.0 GHz, 2x2MB L2, 800MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,3,4
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16 x 1024MB ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 73GB 10000RPM U320 SCSI HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1
Compiler: Intel C++ 9.0 Build 20051130Z for IA32 and Fortran Compiler 9.0 Build 20051130Z for IA32
Microsoft Visual Studio .Net 2003 (7.1.5091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for all Fortran Programs : -fast -Qansi_alias +FDO
Base tuning for all C Programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib
187.facerec: basepeak=yes
188.amp: -Oa -QxP
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R910 (3.0 GHz Intel Xeon Processor 7041)

SPECfp_rate2000 = 45.9

SPECfp_rate_base2000 = 45.9

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Jun-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Enable hardware prefetching and adjacent cache line prefetch BIOS setting