



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5130 processor, 2.0 GHz

SPECfp_rate2000 = 68.8

SPECfp_rate_base2000 = 68.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

250 200 150 100 50					Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
					168.wupwise	4	75.4	98.4	4	75.4	98.4
					171.swim	4	273	52.7	4	273	52.7
					172.mgrid	4	177	47.3	4	177	47.3
					173.applu	4	193	50.4	4	193	50.4
					177.mesa	4	69.2	93.9	4	69.2	93.9
					178.galgel	4	78.1	172	4	78.1	172
					179.art	4	61.8	195	4	61.8	195
					183.equake	4	121	50.0	4	121	50.0
					187.facerec	4	101	87.0	4	101	87.0
					188.amp	4	161	63.2	4	161	63.2
					189.lucas	4	179	52.0	4	179	52.0
					191.fma3d	4	192	50.8	4	192	50.8
					200.sixtrack	4	147	34.7	4	147	34.7
					301.apsi	4	225	53.7	4	225	53.7

Hardware

CPU: Intel Xeon 5130 processor (2.0 GHz, 4MB L2, 1333 MHz system bus)
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KBI + 32KBD on chip, per core
 Secondary Cache: 4096KB(I+D) on chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5)
 Disk Subsystem: Seagate ST936701SS (SAS, 10 krpm, 36GB)
 Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
 Kernel 2.6.5-7.244-smp on an x86_64
 Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
 Build 20060120 (for 64-bit applications)
 File System: ext3
 System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
 PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5130 processor, 2.0 GHz

SPECfp_rate2000 = 68.8

SPECfp_rate_base2000 = 68.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>