



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7020, 2.66 GHz

SPECfp_rate2000 = 44.6

SPECfp_rate_base2000 = 44.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Nov-2005 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	227	65.4	8	227	65.4
171.swim	8	928	31.0	8	928	31.0
172.mgrid	8	613	27.2	8	613	27.2
173.applu	8	682	28.6	8	682	28.6
177.mesa	8	112	116	8	112	116
178.galgel	8	417	64.6	8	417	64.6
179.art	8	502	48.1	8	502	48.1
183.quake	8	479	25.2	8	479	25.2
187.facerec	8	374	47.1	8	374	47.1
188.amp	8	397	51.4	8	397	51.4
189.lucas	8	528	35.2	8	528	35.2
191.fma3d	8	524	37.2	8	524	37.2
200.sixtrack	8	229	44.7	8	229	44.7
301.apsi	8	396	60.9	8	396	60.9

Hardware

CPU: Intel Xeon processor 7020 (2.66 GHz, 2x1MB L2, 667 MHz system bus)
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip, per core
 Secondary Cache: 1024KB(I+D) on chip, per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
 Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
 Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
 Kernel 2.6.5-7.244-smp on an x86_64
 Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
 Build 20060120 (for 64-bit applications)
 File System: ext3
 System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
 PASS1: -prof_gen PASS2: -prof_use

Optimization flags
 ONESTEP=yes set for all benchmarks

Portability flags
 -DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

Base tuning flags
 for Fortran and C programs: -fast +FDO

Peak tuning flags
 same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7020, 2.66 GHz

SPECfp_rate2000 = 44.6

SPECfp_rate_base2000 = 44.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Nov-2005 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 667 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>