



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECint\_rate2000 = 62.0

SPECint\_rate\_base2000 = 62.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	77.3	42.0	2	77.3	42.0
175.vpr	2	73.7	44.1	2	73.7	44.1
176.gcc	2	39.8	64.0	2	39.8	64.0
181.mcf	2	75.6	55.2	2	75.6	55.2
186.crafy	2	36.6	63.4	2	36.6	63.4
197.parser	2	82.9	50.4	2	82.9	50.4
252.eon	2	33.6	89.7	2	33.6	89.7
253.perlbnk	2	51.8	80.6	2	51.8	80.6
254.gap	2	42.0	60.7	2	42.0	60.7
255.vortex	2	44.3	99.5	2	44.3	99.5
256.bzip2	2	78.3	44.4	2	78.3	44.4
300.twolf	2	87.8	79.3	2	87.8	79.3

### Hardware

CPU: Intel Xeon 5160 processor (3.0 GHz, 4MB SLC, 1333 MHz system bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 4096KB(I+D) on chip, per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)  
Compiler: Intel C++ Compiler 9.1  
Build 20060323Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafy: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32m.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32m.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY TX300 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECint\_rate2000 = 62.0

SPECint\_rate\_base2000 = 62.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

BIOS configuration:

Adjacent Sector Prefetch = disable

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>