



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5130 processor, 2.0 GHz

SPECfp\_rate2000 = 38.8

SPECfp\_rate\_base2000 = 38.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	63.9	58.1	2	63.9	58.1
171.swim	2	211	34.1	2	211	34.1
172.mgrid	2	148	28.2	2	148	28.2
173.applu	2	160	30.5	2	160	30.5
177.mesa	2	68.3	47.5	2	68.3	47.5
178.galgel	2	74.6	90.1	2	74.6	90.1
179.art	2	55.8	108	2	55.8	108
183.quake	2	89.4	33.7	2	89.4	33.7
187.facerec	2	96.7	45.6	2	96.7	45.6
188.amp	2	160	31.9	2	160	31.9
189.lucas	2	153	30.2	2	153	30.2
191.fma3d	2	159	30.6	2	159	30.6
200.sixtrack	2	146	17.5	2	146	17.5
301.apsi	2	213	28.3	2	213	28.3

### Hardware

CPU: Intel Xeon 5130 processor (2.0 GHz, 4MB SLC, 1333 MHz system bus)  
CPU MHz: 2000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 4096KB(I+D) on chip, per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1024 MB DDRII-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)  
Other Hardware: none

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3  
Kernel 2.6.5-7.244-smp on an x86\_64  
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T  
Build 20060120 (for 64-bit applications)  
File System: ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

### GENERAL

+FDO implies feedback-directed optimization  
PASS1: -prof\_gen PASS2: -prof\_use

### Optimization flags

ONESTEP=yes set for all benchmarks

### Portability flags

-DSPEC\_CPU2000\_LP64 applied to all benchmarks  
178.galgel: -FI for fixed-format Fortran

### Base tuning flags

for Fortran and C programs: -fast +FDO

### Peak tuning flags

same as baseline (basepeak=true set globally)



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon 5130 processor, 2.0 GHz

SPECfp\_rate2000 = 38.8

SPECfp\_rate\_base2000 = 38.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

This result was measured on the PRIMERGY TX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>