



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Supermicro

Motherboard X7DB3 ( 3.00GHz, Intel Xeon 5160 processor)

SPECint2000 = 2950

SPECint\_base2000 = 2947

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	77.0	1818	76.8	1822	
175.vpr	1400	67.3	2080	66.3	2110	
176.gcc	1100	37.6	2926	37.6	2926	
181.mcf	1800	41.9	4294	41.9	4294	
186.crafty	1000	36.7	2727	36.6	2729	
197.parser	1800	79.5	2265	79.6	2261	
252.eon	1300	33.5	3877	33.5	3882	
253.perlbmk	1800	50.3	3575	50.5	3565	
254.gap	1100	38.5	2858	38.5	2858	
255.vortex	1900	39.3	4841	39.3	4841	
256.bzip2	1500	66.8	2246	66.9	2243	
300.twolf	3000	88.4	3392	88.4	3393	

### Hardware

CPU: Intel Xeon 5160 processor ( 3.00 GHz, 4MB L2 shared, 1333 MHz bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1, 2  
Parallel: No  
Primary Cache: 32KBI + 32KBD on chip per core  
Secondary Cache: 4MB(I+D) on chip (per chip)  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 x 2.0GB 667MHz FBDIMM ECC CL5  
Disk Subsystem: 1X 30GB Fujitsu MHS2030AT SATA HDD  
Other Hardware: N/A

### Software

Operating System: Windows server 2003 Enterprise Edition 32-bits W/ SP1  
Compiler: Intel C++ Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_CC\_P\_9.1.020  
Microsoft Visual Studio 2005 (for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Supermicro**

Motherboard X7DB3 ( 3.00GHz, Intel Xeon 5160 processor)

SPECint2000 = 2950

SPECint\_base2000 = 2947

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO  
300.twolf: -fast -O3 +FDO shlw32M.lib  
Tested systems can be used with SC825TQ-R700LPV case,  
To ensure system stability, a 550W (minimum) ATX power supply  
[4-pin (+12V), 8-pin (+12V) and 24-pin are required]  
Product description located as of X7DB3:  
<http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB3.cfm>  
The system bus runs at 1333 MHz