



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

ION

A20 (Intel Xeon processor 5080, 3.73GHz)

SPECfp_rate2000 = 63.5

SPECfp_rate_base2000 = 63.5

SPEC license #: 2697 | Tested by: ION | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jun-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	78.0	95.2	4	78.0	95.2
171.swim	4	293	49.0	4	293	49.0
172.mgrid	4	183	45.5	4	183	45.5
173.applu	4	199	49.0	4	199	49.0
177.mesa	4	73.3	88.6	4	73.3	88.6
178.galgel	4	97.2	138	4	97.2	138
179.art	4	69.3	174	4	69.3	174
183.equake	4	150	40.2	4	150	40.2
187.facerec	4	127	69.3	4	127	69.3
188.amp	4	170	60.2	4	170	60.2
189.lucas	4	197	47.1	4	197	47.1
191.fma3d	4	189	51.6	4	189	51.6
200.sixtrack	4	151	33.7	4	151	33.7
301.apsi	4	213	56.7	4	213	56.7

Hardware

CPU: Intel Xeon Processor 5080 (1066Mhz System Bus)
 CPU MHz: 3733
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (HyperThreading Technology disabled)
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 12KB(I) + 16KB(D) on chip, per core
 Secondary Cache: 2MB (I+D) on chip, per core
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (8*1GB PC2-5300 FB-DIMMs)
 Disk Subsystem: 1 x 400GB SATA, 7200rpm
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux ES 4 Update 3 for AMD64/Intel EM64T
 Compiler: Intel(R) Fortran Compiler for EM64T, V9.1 (Build 20060519)
 Intel(R) C++ Compiler for EM64T, V9.1 (Build 20060519)
 File System: ext3
 System State: Multi-user

Notes/Tuning Information

Tested by ION Computer Systems
 BIOS 2.00 Build 54
 HyperThreading Technology Disabled in BIOS
 Enhanced SpeedStep Disabled in BIOS
 kernel 2.6.9-34.0.1.ELsmp
 +FDO: PASS1=-prof_gen PASS2=-prof_use

SPEC CFP2000 Baseline optimization flags
 C programs: -fast -ansi_alias +FDO
 Fortran programs: -fast +FDO
 +FDO: PASS1=-prof_gen PASS2=-prof_use

SPEC CFP2000 Peak optimization flags:
 basepeak=yes set globally

Portability Flags:
 178.galgel: -FI