



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS R540, Intel Xeon 5150 processor

SPECfp_rate2000 = 77.4
SPECfp_rate_base2000 = 76.3

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Sep-2006 Hardware Avail: Aug-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	70.2	106	4	70.1	106
171.swim	4	266	54.0	4	267	54.0
172.mgrid	4	171	48.9	4	170	49.0
173.applu	4	191	51.1	4	191	51.1
177.mesa	4	59.0	110	4	58.3	111
178.galgel	4	63.3	212	4	63.3	212
179.art	4	62.0	195	4	61.9	195
183.equake	4	89.6	67.3	4	89.6	67.3
187.facerec	4	94.3	93.5	4	95.6	92.3
188.amp	4	155	66.0	4	130	78.8
189.lucas	4	183	50.6	4	183	50.6
191.fma3d	4	164	59.4	4	162	60.1
200.sixtrack	4	105	48.8	4	105	48.8
301.apsi	4	211	57.1	4	210	57.4

Hardware

CPU: Intel Xeon 5150 processor (2.66 GHz, 1333 MHz system bus)
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KBI + 32KBD on chip, per core
Secondary Cache: 4096KB(I+D) on chip, per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 GB (4x1 GB DDR2 5300F, 2rank, CL5-5-5, with ECC)
Disk Subsystem: Serial ATA 7200 rpm
Other Hardware:

Software

Operating System: Windows XP, 64 bit Edition
Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1,
- Build 20060519Z Package ID: W_CC_P_9.1.025
Intel(R) Fortran Compiler for 32-bit app., Version 9.1,
- Build 20060519Z Package ID: W_FC_P_9.1.025
Microsoft Visual Studio .NET 2003 (for libraries)
MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
File System: NTFS
System State: Default

Notes/Tuning Information

Portability flags:
178.galgel: -FI /F32000000

Feedback optimization:
+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:
for C programs:
-fast +FDO shlW32M.lib
for Fortran programs:
-fast +FDO shlW32M.lib

Peak Tuning Flags:
173.applu: basepeak=yes
168.wupwise: -fast +FDO
171.swim: -fast +FDO
172.mgrid: -fast +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS R540, Intel Xeon 5150 processor

SPECfp_rate2000 = 77.4

SPECfp_rate_base2000 = 76.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Sep-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
173.applu: basepeak=yes
177.mesa: -fast +FDO ONESTEP=yes
178.galgel: -fast +FDO
179.art: -fast +FDO shlW32M.lib
183.equake: -fast +FDO shlW32M.lib
187.facerec: -fast +FDO
188.amp: -fast +FDO
189.lucas: basepeak=yes
191.fma3d: -fast +FDO
200.sixtrack: -fast +FDO
301.apsi: -fast +FDO
```

Extra Libraries:

shlW32M.lib = Microquill SmartHeap Library 8
see www.microquill.com

Compilation was done in
Windows XP Professional, Service Pack 2

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>